

4E KEYLINE SERIES


ROPS

50 - 60HP



Designed to simplify farming life, the popular Deutz-Fahr 4E Keyline Series features two models, 50 hp and 60 hp, and can be packaged with a 4-in-1 loader.

They are ideal for lifestyle and livestock farmers and specialist growers, made tough for Australian conditions, and can be used with a variety of mounted and towed implements. Designed to have a front end loader fitted, forward/reverse shuttle synchronised transmission is equipped as standard across the whole range.



4050E

34KM/H

50HP

4060E

34KM/H

60HP

TECHNICAL DATA & FEATURES

4050E KEYLINE HD ROPS

4060E KEYLINE HD ROPS



POWER + PERFORMANCE

| | | |
|------------------------------|----------------------------|-------------------|
| Engine Type | Deutz Fahr SDF 1000 Series | |
| Emissions | Tier III A | |
| Cylinders / Capacity | 3/3000 | |
| Aspiration | Natural | Turbo Intercooler |
| Max Power - ECE R120 (kW/HP) | 36.8/50 | 44.1/60 |
| Max Torque (Nm) | 184 | 221 |
| Rated Engine Speed (rpm) | 2200 | |
| Fuel Capacity (l) | 55 | 55 |

DRIVE + HANDLING

| | | |
|-------------------------|----------------------------|--|
| Gearbox Type and Gears | Synchronised Shuttle | |
| Number of Gears | 12+12 | |
| Forward/Reverse Shuttle | ■ | |
| Clutch Type | Double Dry Heavy Duty 11" | |
| Min Speed (km/h) | 0.5 | |
| Max Speed (km/h) | 34 | |
| 4WD | ■ | |
| Diff Lock | Mechanically Operated Rear | |
| Brakes (NO / Type) | 2/ Girling Braking System | |
| Wheel Size - Rear | Adjustable 14.9*28 | |
| Wheel Size - Front | Adjustable 11.2*20 | |
| PTO Type | Mechanical Independent | |
| Speeds - Rear | 540 | |
| PTO engine speed (rpm) | 1960 | |

LIFT + FLOW

| | | |
|-------------------------------|-----------------------|--|
| Type | Open Centre | |
| Flow Rate (l/min) | 31 | |
| Remote Valves (sets) | 2 | |
| Remote Valve Type | Detent/Spring | |
| 3 Point Hitch Type | Mechanical with Draft | |
| Category | 2 | |
| Max Lift Capacity - Rear (kg) | 1600 | |

COMFORT + CONVENIENCE

| | | |
|--|-------------------|--|
| 2 Post ROPS | ■ | |
| Sun Canopy | ■ | |
| Driver Seat with Mechanical Suspension | ■ | |
| Display | Analogue | |
| Side Control Levers | ■ | |
| Flat Platform with Rubber Mat | ■ | |
| Upswept Side Mounted Exhaust | ■ | |
| Worklights (No + Type) | 2 Bonnet / 1 Rear | |

WEIGHTS + DIMENSIONS

| | | |
|------------------------|------|--|
| Wheelbase (mm) | 1950 | |
| Length (mm) | 3513 | |
| Min Overall Width (mm) | ?? | |
| Height (mm) | 2460 | |
| Weight (kg) | 2860 | |

CANOPY AND WHEEL WEIGHTS STANDARD



HEAVY DUTY THREE POINT LINKAGE




FORWARD/REVERSE SHUTTLE



SPACIOUS OPERATING AREA



INDEPENDENT PTO



■ Standard