

AGROPLUS F SERIES

CAB

SPECIALIST RANGE

85-106^{HP}



Deutz-Fahr has been one of Europe's leading suppliers of specialist tractors for decades.

The Agroplus V/F/S Series of tractors offers specialist farmers three minimum widths: V - 1110 mm; S - 1220 mm; and F - 1510 mm.

For the Australian market, the F series is stocked as a standard model; however, if operators require a narrower model the V and S variants can be ordered from the factory.

With unique design requirements needed for the specialist grower, the Agroplus V/F/S series is ideal for fruit growers and vineyards looking for a compact and powerful tractor.



**AGROPLUS
F410 DT**

40KM/H

85HP

**AGROPLUS
F430 GS**

40KM/H

106HP

DEUTZ-FAHR



1800 789 633

TECHNICAL DATA & FEATURES

AGROPLUS F410 DT

AGROPLUS F430 GS

POWER + PERFORMANCE

Engine Type	Deutz-Fahr SDF 1000 Series	
Emissions	Tier III	
Cylinders / Capacity	4/4000	
Aspiration	Turbo Intercooled	
Max Power - 2000/25/CE (kW/HP)	63/85	78/106
Max Torque (Nm)	345	390
Rated Engine Speed (rpm)	2200	
Fuel Capacity (l)	55	95

DRIVE + HANDLING

Gearbox Type and Gears	Synchronised Shuttle	Wet Clutch Powershuttle
Number of Gears	30+15	45+45
Powershift Speeds	-	3
Forward/Reverse Shuttle	■	
STOP & Go	-	■
Clutch Type	Self-Adjusting Dry Heavy Duty 12"	Wet Clutch
Min Speed (km/h)	0.18	0.17
Max Speed (km/h)	40 Eco	
4WD	■	
Diff Lock	Electro-Hyd Operated Front + Rear	
Brakes (NO / Type)	4/ Independent Wet Disc	
Wheel Size - Rear	Adjustable 380/70R24	Adjustable 420/70R24
Wheel Size - Front	Adjustable 280/70R16	Adjustable 280/70R18
PTO Type	Electro-Hyd Independent Wet Clutch	
Speeds - Rear	540/540E	540/540E/1000

LIFT + FLOW

Type	Open Centre	
Flow Rate (Type + l/min)	Steering 26 / Hydraulic 54	
Remote Valves (sets)	3	
Remote Valve Type	Spring/Detent/Float with 1 Flow Control	
3 Point Hitch Type	Mechanical with Draft	
Category	2	
Hitch End Type	Hook	
Max Lift Capacity - Rear (kg)	3000	

COMFORT + CONVENIENCE

Air-Conditioned Cabin	■
Radio/MP3 Player	■
Carbon Filters	■
Cloth Driver Seat w/ Pneumatic Suspension	■
Adjustable Steering Wheel	■
Display	Analogue / Digital
Side Control Levers	■
Engine Speed Programming	■
Cabin Mounted on Silent-Block	■
Downswept Side Mounted Exhaust	■
Worklights (No + Type)	2 Bonnet / 4 Cabin

WEIGHTS + DIMENSIONS

Wheelbase (mm)	2120	
Length (mm)	3338	3363
Min Overall Width (mm)	1520	1630
Height (mm)	2290	2315
Weight (kg)	3000	



ECONOMICAL 4 CYLINDER ENGINE



WET CLUTCH POWERSHUTTLE



TIGHT TURNING CIRCLE



ENGINE SPEED PROGRAMMING



SPACIOUS CABIN



Standard