



Engine

SDF 1000 Series Tier 3 Diesel Engine
3 Cyl/3000cc Turbocharged
Liquid/Oil Cooled
Individual Bosch Injector Pumps
62 hp @ 2200 rpm (2005/25/CE)
Torque 244nm
Side mounted cabin exhaust
70lt Fuel Capacity

Transmission

30/15 Synchromesh Gearbox
Forward/Reverse Synchronized Shuttle
Shuttle mounted on Steering Column
Double Dry Heavy Duty 11" Clutch
Gear Levers Located Right Hand Side
Creep Gear Std
4 Wheel Independent Braking
Front Wheel Assist- Mechanical
Front & Rear Diff Lock- Mechanical
40 km/h Road speed

PTO

Independent Rear PTO
540/ 750 Speed PTO
540 PTO @ 1967Rpm
540E PTO @1560 Rpm
Ground Speed PTO
1"3/8 -6 Splines PTO shaft

Wheel Equipment & Miscellaneous

Adjustable Radial Wheel Equipment
320/85R20 Front 380/85R30 Rear
Front weight frame
Dynamic steering fenders

Operator Environment

Air Conditioned Cab
Digital Climate Control
Ergonomic Controls
Adjustable Steering Column
Analogue Dash
Mechanical Sprung Cloth Seat
MP3 Radio Player with Twin Speakers
Telescopic Mirrors
4 Cabin Work lights
2 Bonnet Front Work lights
Rotating Beacon

Hyd/Linkage

Open Centre Hyd Pump System
42 l/min Hyd Pump
Separate 17 L/min Steering Pump
2 Sets of Remotes - Spring
Mechanical Three Point Linkage
EASYLIFT raise and lower switch
Position & draft control Settings
Cat 2 Ball ends
2500kg lift capacity

Weights & Dimensions

Wheelbase	1976mm
Overall Length	3730mm
Total Weight	3050kg



Engine

SDF 1000 Series Tier 3 Diesel Engine
4 Cyl/4000cc Turbocharged Intercooled
Liquid/Oil Cooled
Engine speed programming
Individual Bosch Injector Pumps
80 hp @ 2200 rpm (2005/25/CE)
Torque 325nm
Side mounted cabin exhaust
70lt Fuel Capacity

Transmission

30/15 Synchronesh Gearbox
Forward/Reverse Synchronized Shuttle
Shuttle mounted on Steering Column
Double Dry Heavy Duty 11" Clutch
Gear Levers Located Right Hand Side
Creep Gear Std
Heavy Duty Rear Axle
4 Wheel Independent Braking
Front Wheel Assist- Mechanical
Front & Rear Diff Lock- Mechanical
40 km/h Road speed

PTO

Independent Rear PTO
540/ 750 Speed PTO
540 PTO @ 1967Rpm
540E PTO @1560 Rpm
Ground Speed PTO
1"3/8 -6 Spline PTO shaft

Wheel Equipment & Miscellaneous

Adjustable Radial Wheel Equipment
320/70R24 Front 420/85R30 Rear
Front weight frame
Dynamic steering fenders

Operator Environment

Air Conditioned Cab
Digital Climate Control
Ergonomic Controls
Adjustable Steering Column
Analogue Dash
Mechanical Sprung Cloth Seat
MP3 Radio Player with Twin Speakers
Telescopic Mirrors
4 Cabin Work lights
2 Bonnet Front Work lights
Rotating Beacon

Hyd/Linkage

Open Centre Hyd Pump System
42 l/min Hyd Pump
Separate 17 L/min Steering Pump
3 Sets of Remotes
Spring/Detent on 2 sets / 1 Set Float
Mechanical Three Point Linkage
EASYLIFT raise and lower switch
Position & draft control Settings
Cat 2 Ball ends
3500kg lift capacity

Weights & Dimensions

Wheelbase	2106mm
Overall Length	3990mm
Total Weight	3250kg



4090.4E ROPS



Engine

SDF 1000 Series Tier 3 Diesel Engine
4 Cyl/4000cc Turbocharged Intercooled
Liquid/Oil Cooled
Engine speed programming
Individual Bosch Injector Pumps
85 hp @ 2200 rpm (2005/25/CE)
Side mounted upswept exhaust - Tractor only
Side mounted down swept exhaust - Tractor + FEL
70lt Fuel Capacity

Transmission

30/15 Synchronesh Gearbox
Forward/Reverse Synchronized Shuttle
Shuttle mounted on Steering Column
Double Dry Heavy Duty 11" Clutch
Gear Levers Located Right Hand Side
Creep Gear Std
Heavy Duty Rear Axle
4 Wheel Independent Braking
Front Wheel Assist- Mechanical
Front & Rear Diff Lock- Mechanical
40 km/h Road speed

PTO

Independent Rear PTO
540/ 750 Speed PTO
540 PTO @ 1967 Rpm
540E PTO @1560 Rpm
Ground Speed PTO
1"3/8 -6 Spline PTO shaft

Wheel Equipment & Miscellaneous

Adjustable Radial Wheel Equipment
320/70R24 Front 420/85R30 Rear
Front weight frame
Dynamic steering fenders

Operator Environment

2 Post ROP Frame
Flat Floor ISO Mounted Platform
Rubber Floor Mat
Ergonomic Controls
Telescopic and Tilting Steering Wheel
Analogue Dash
Deluxe PVC Mechanical Seat
Sun Canopy
Telescopic Mirrors
1 Rear Work lights
2 Bonnet Work lights
Rotating Beacon

Hyd/Linkage

Open Centre Hyd Pump System
42 l/min Hyd Pump
Separate 17 L/min Steering Pump
3 Sets of Remotes
Spring/Detent on 2 sets / 1 Set Float
Mechanical Three Point Linkage
EASYLIFT raise and lower switch
Position & draft control Settings
Cat 2 Ball ends
3500kg lift capacity

Weights & Dimensions

Wheelbase	2106mm
Overall Length	3990mm
Total Weight	3100kg

Effective September 2019



4100.4E

Engine

SDF 1000 Series Tier 3 Diesel Engine
4 Cyl/4000cc Turbocharged Intercooled
Liquid/Oil Cooled
Engine speed programming
Individual Bosch Injector Pumps
95 hp @ 2200 rpm (2005/25/CE)
Side mounted cabin exhaust
70lt Fuel Capacity

Transmission

30/15 Synchromesh Gearbox
Forward/Reverse Synchronized Shuttle
Shuttle mounted on Steering Column
Double Dry Heavy Duty 11" Clutch
Gear Levers Located Right Hand Side
Creep Gear Std
Heavy Duty Rear Axle
4 Wheel Independent Braking
Front Wheel Assist- Mechanical
Front & Rear Diff Lock- Mechanical
40 km/h Road speed

PTO

Independent Rear PTO
540/ 750 Speed PTO
540 PTO @ 1967Rpm
540E PTO @1560 Rpm
Ground Speed PTO
1"3/8 -6 Spline PTO shaft

Wheel Equipment & Miscellaneous

Adjustable Radial Wheel Equipment
320/70R24 Front 420/85R30 Rear
Front weight frame
Dynamic steering fenders



Operator Environment

Air Conditioned Cab
Digital Climate Control
Ergonomic Controls
Adjustable Steering Column
Analogue Dash
Mechanical Sprung Cloth Seat
MP3 Radio Player with Twin Speakers
Telescopic Mirrors
4 Cabin Work lights
2 Bonnet Front Work lights
Rotating Beacon

Hyd/Linkage

Open Centre Hyd Pump System
42 l/min Hyd Pump
Separate 17 L/min Steering Pump
3 Sets of Remotes
Spring/Detent on 2 sets / 1 Set Float
Mechanical Three Point Linkage
EASYLIFT raise and lower switch
Position & draft control Settings
Cat 2 Ball ends
3500kg lift capacity

Weights & Dimensions

Wheelbase	2106mm
Overall Length	3990mm
Total Weight	3250kg

Effective September 2019