

5125G Heavy Duty

Engine
FARMotion Tier 4i Diesel Engine
4 Cyl/3849cc Turbocharged/Intercooled
Electronically Controlled
Emission control by DOC unit
Liquid/Oil Cooled with fixed fan
High pressure Diesel injection/common rail
126 hp Max hp @ 2200 rpm (2000/25/CE)
6 Hp Power Boost
Torque 500 Nm @1600 rpm
100% Bio Diesel Compliant
Engine Speed Programming – 2 settings
Powercore Air Filter with Dust Ejectors
Side vertical exhaust
Fuel Tank 150 litres

Transmission
60/60 forward/reverse gears
Sense Clutch - Wet clutch Powershuttle
Shuttle modulation with 5 settings
5 speeds/4 Ranges / 3 stage Powershift
Speed Matching
Comfort Clutch
Stop and Go function
Front Wheel Assist - Push Button
4 Wheel Independent Braking
100% Front & Rear Diff Lock - Push Button
40 km/h Road speed @ Super Economy RPM

Independent wet multidisc clutch 4 Speed PTO 540/540E- 1000/1000E Push Button Control in cab/rear fender Auto PTO Interchangeable PTO Spline Function

1" 3/8 - 6 Spline PTO shaft

Wheel Equipment & Miscellaneous Fixed Fully Welded Radial Wheel Equipment 440/65R28 Front -540/65R38 Rear Tyres Front Weight Frame 12v elec. socket and 7-pin ISO 11786 plug



Operator Environment
D2L Class Air Conditioned Cab
Hydro Silent Block Cabin Suspension
Super Deluxe Air Seat
Tilt and telescopic steering wheel
SDD Rapid Steering circuit
Hi Visibility Glass Roof/rear wiper
INFOCENTER II Digital Display
MP3 Radio Player with Twin Speakers
Telescopic Mirrors
4 Cabin Work lights
2 Bonnet Front Work lights
2 Work lights on Cab Post
Rotating Beacon

Hyd/Linkage
90 L/min On Demand Hydraulic System
Separate 40L/min Steering Pump
3 Sets of Remotes - 3 Detent / 3 Float
Flow control on all valves
Electronic hitch with position & draft control
Free flow return Line
External Raise & lower on Rear Fenders
Cat 2 Hook ends-telescopic stabilisers
5410 kg lift capacity with Assistor Rams

Weights & Dimensions
Wheelbase 2400 mm
Length 4314 mm
Total Height 2730mm
Total Weight 4400kg

