

Agrofarm 100 GS ROPS



Engine

SDF1000 Series Diesel Engine
4 Cyl/4000cc Turbocharged
Liquid/Oil Cooled
Bosch High pressure Individual Diesel injection
96 hp @ 2300 rpm (2005/25/CE)
Torque 342nm
Side mounted exhaust
160lt Fuel Capacity

Transmission

40/40 forward/reverse gears
Wet clutch Powershuttle
2 Speed Powershift
Comfort Clutch
Creep Std
Front Wheel Assist
4 Wheel Independent Braking
100% Front & Rear Diff Lock
40 km/h Road speed

PTO

Independent wet multidisc clutch
4 Speed PTO 540/540E- 1000/1000E
1" 3/8 - 6 Spline PTO shaft
Push Button control
Interchangeable PTO Shaft Function

Wheel Equipment & Miscellaneous

Adjustable Radial Wheel Equipment
420/70R24 Front -480/70R34 Rear
Front Weight Frame

Operator Environment

2 Post ROP Frame
Flat Floor ISO Mounted Platform
Rubber Floor Mat
Ergonomic Controls
Telescopic and Tilting Steering Wheel
Multi Function Digital Dash
Deluxe PVC Mechanical Seat
Sun Canopy
Telescopic Mirrors
2 Rear Canopy Work lights
2 Bonnet Work lights
Rotating Beacon

Hyd/Linkage

Open Centre Hyd Pump System
56 L/min Hyd a Rear Remotes
Separate 44L/min Steering Pump
2 Set of Remotes - 1 Detent /1 Spring
Mechanical Linkage c/w position & draft controls
Cat 2 Hook Ends
4200kg lift capacity

Weights & Dimensions

Wheelbase	2380mm
Length	3950mm
Total Height	2580mm
Total Weight	3650kg

Effective September 2019

Agrofarm 100 DT



Engine

SDF1000 Series Diesel Engine
4 Cyl/4000cc Turbocharged
Liquid/Oil Cooled
Bosch High pressure Individual Diesel injection
96hp @ 2350rpm (2005/25/CE)
Torque 342nm
Side mounted cabin exhaust
160lt Fuel Capacity

Transmission

15/15 forward/reverse gears
Heavy duty 13" dry Cerametallic clutch
Synchronized forward/reverse shuttle
Shuttle lever located left hand side
Front Wheel Assist – Mechanical engagement
4 Wheel Independent Braking
100% Front & Rear Diff Lock- Push button
40 km/h Road speed

PTO

Independent wet multidisc clutch
4 Speed PTO 540/540E/1000/1000E
1" 3/8 – 6 Spline PTO shaft
Push Button control

Wheel Equipment & Miscellaneous

Adjustable Radial Wheel Equipment
420/70R24 Front 480/70R34 Rear

Operator Environment

4 Post Hi visibility Air Conditioned Cab
Ergonomic Controls
Multi Function Digital Dash
Deluxe Mechanical Sprung Seat
MP3 Radio Player with Twin Speakers
Telescopic Mirrors
4 Cabin Work lights
2 Bonnet Front Work lights
Rotating Beacon

Hyd/Linkage

Open Centre Hyd Pump System
56 L/min Hyd a Rear Remotes
Separate 44L/min Steering Pump
2 Set of Remotes – 1 Detent / 1 Spring
Mechanical Linkage c/w position & draft controls
Cat 2 Ball Ends
4200kg lift capacity

Weights & Dimensions

Wheelbase	2380mm
Length	3950mm
Total Height	2740mm
Total Weight	4100kg

Effective September 2019

Agrofarm 115 GS



Engine

SDF1000 Series Diesel Engine
4 Cyl/4000cc Turbocharged
Liquid/Oil Cooled
Bosch High pressure Individual Diesel injection
110hp @ 2350rpm (2005/25/CE)
Torque 396nm
Side mounted cabin exhaust
160lt Fuel Capacity

Transmission

30/30 forward/reverse gears
Wet clutch Powershuttle
Shuttle modulation with 5 settings
5 speeds/3 Ranges / 2 stage Powershift
Comfort Clutch
Front Wheel Assist - Push Button
4 Wheel Independent Braking
100% Front & Rear Diff Lock - Push Button
40 km/h Road speed

PTO

Independent wet multidisc clutch
4 Speed PTO 540/540E- 1000/1000E
Push Button Control in cab/rear fender
Interchangeable PTO Spline Function
1" 3/8 - 6 Spline PTO shaft

Wheel Equipment & Miscellaneous

Adjustable Radial Wheel Equipment
420/70R24 Front 480/70R34 Rear
Front Clevis

Operator Environment

4 Post Air Conditioned Cab
Ergonomic Controls
Multi Function Digital Dash
Deluxe Mechanical Sprung Seat
MP3 Radio Player with Twin Speakers
Telescopic Mirrors
4 Cabin Work lights
2 Bonnet Front Work lights
Rotating Beacon

Hyd/Linkage

Open Centre Hyd Pump System
56 L/min Hyd a Rear Remotes
Separate 44L/min Steering Pump
2 Set of Remotes - 2 Kick out / 1 Float
Mechanical Linkage c/w position & draft controls
Cat 2 Hook Ends
4800kg lift capacity

Weights & Dimensions

Wheelbase	2380mm
Length	3990mm
Total Height	2740mm
Total Weight	4250kg

Effective September 2019