

The COSMO BULLY NBM Series Mulcher is a multi-purpose implement. Its robust design makes light work of bracken, as well as prunings and undergrowth (up to 30mm).

A 2,295 rpm rotor speed, coupled with a rear opening flap, gives the operator flexibility of a quality finish on grassy applications like paddocks and parks and gardens, regardless of grass height..

The NBM Series Mulcher has two bolted mounting positions (21cm apart) allowing the operator to offset the implement on the tractor's three-point linkage.

The 50hp gearbox (max.) is fitted with an integrated freewheel clutch and the NBM Series comes standard with hammers, height adjustable, replaceable skids and a rear roller.



| Code                  | TNBM145  | TNBM155            | TNBM175             |
|-----------------------|--|--------------------|---------------------|
| Size reference        | 1.45m   4'9"   57"   | 1.55m   5'2"   61" | 1.75m   5'10"   69" |
| Side transmission     | Belt drive   |                    |                     |
| Belts                 | Three (3) SPAB   |                    | Four (4) SPAB       |
| Gearbox               | 50hp, 540rpm with free wheel clutch                        |                    |                     |
| PTO Shaft/clutch      | Series 4   |                    |                     |
| Skids                 | Adjustable, four (4) positions                             |                    |                     |
| Rear roller           | Ø121mm, height adjustable, six (6) positions               |                    |                     |
| Finish                | Powder coated  |                    |                     |
| Rotor swing dia. (mm) | 350mm (blade tip to blade tip diameter)                    |                    |                     |
| Rotor diameter (mm)   | 108  |                    |                     |
| Rotor speed (rpm)     | 2295   |                    |                     |
| Type of blade         | Hammer   |                    |                     |
| No. of hammers        | 24   | 24                 | 28                  |
| Tower position/offset | Fixed/bolt on with two (2) mounting positions, 210mm apart |                    |                     |
| Linkage               | Category 1   |                    |                     |
| Guarding              | CE compliant   |                    |                     |
| Overall width (mm)    | 1685   | 1785               | 1985                |
| Working width (mm)    | 1450   | 1550               | 1750                |
| Cutting height (mm)   | 54   |                    |                     |
| Tractor range (hp)    | 30-50  | 35-50              | 40-50               |
| Weight (kg)           | 355  | 362                | 376                 |
| Price                 |  |                    |                     |

#### Parts

17530.1 Bully NBM Series Hammer (each)