

TRUCKSTER XD



CLASS-LEADING POWER AND PRODUCTIVITY.

The Truckster XD makes quick work of your hardest jobs with the industry's largest standard payload and your choice of Kubota petrol or diesel engines. A highly versatile bed - manufactured with strong heavy gauge steel, integrated stake pockets and tie-downs - makes effortless hauling for your heaviest loads. Built to operate in the toughest of conditions with the industry's highest approach angle, and largest ergonomic operator platform, your crew can count on the Truckster XD to handle the strenuous tasks with ease.

LET'S WORK.

32.5 HP

PETROL ENGINE

OR

24.8 HP DIESEL ENGINE

668 L BED VOLUME

1,610 KG
TOTAL PAYLOAD



CUSHMAN TRUCKSTER XD





OPTIONS & ACCESSORIES

- 168 cm (66") Box
- 2" Receiver Hitch
- · Canopy (two or four post ROPS)
- Four-post ROPS Premium Suspension Seat (operator and passenger)
- Hi/Lo Hydraulics with Remote Ports
- Hydraulic PTO
- Throttle Control
- Turn Signals
- Cab
- Doors • Heater
- Auto Tailgate

- Fifth-wheel BallHhitch Including Electric Brake Controller
- Core Harvester
- Top Dresser
- 1500 Vicon Spreader
- Quick Aerator
- Implement Lift
- Mirrors Left and Right
- Windshield for Four-post ROPS Storage Accessory
- Work Light Kit
- Backup Alarm
- Exhaust Spark Arrestor
- Fifth-gear Lock Out

| | PETROL | DIESEL |
|-----------------------|--|-----------------------------------|
| BODY & CHASSIS | | |
| RAME | Powder Coated Steel | |
| BODY & FINISH | Injection Molded | |
| STANDARD COLOUR | Orange or Green | |
| DIMENSIONS | | NAME OF TAXABLE PARTY. |
| OVERALL LENGTH | 132 in. w/o bed, 136 w/ bed | 133 in. w/o bed, 136 w/ bed |
| OVERALL WIDTH | 165 cm (65 in) | |
| OVERALL HEIGHT | 198 cm (78 in) | |
| WHEEL BASE | 165 cm (65 in) | |
| FRONT WHEEL TRACK | 124 cm (49 in) | |
| REAR WHEEL TRACK | 132 cm (52 in) | |
| GROUND CLEARANCE | 16 cm (6.5 in) | |
| CARGO BOX CAPACITY | 0.7 m ³ (23.6 cu ft) | |
| POWER | | 10.70 70.00 0.70 |
| POWER SOURCE | 32.5 HP Kubota Petrol Engine | 24.8 HP Kubota Diesel Engine |
| VALVE TRAIN | 3-Cylinder, 4-Cycle Liquid Cooled EFI | 3-Cylinder, 4-Cycle Liquid Cooled |
| HORSEPOWER | 32.5 HP | 24.8 HP |
| BATTERY (QTY/TYPE) | 12 Volt Battery | |
| KEY OR PEDAL START | Key Start | |
| COOLING SYSTEM | Liquid Cooled | |
| FUEL CAPACITY | 26.5 L (7.0 gal) unleaded | 26.5 L (7.0 gal) diesel |
| DRIVE TRAIN | Engine Shaft Direct Drive | |
| GEAR SELECTION | Five Speed Manual | |
| REAR AXLE RATIO | High 14.2:1 / Low 45:1 | |
| PERFORMANCE | | 20 2 2 6 7 7 7 7 |
| SEATING CAPACITY | 2-Person | |
| VEHICLE LOAD CAPACITY | 1,610 kg (3,550 LBS) | |
| SPEED | 23 mph | 21 mph |
| TOWING CAPACITY | 998 kg, 1587 kg (2,200 lbs, 3,500) w/ trailer brakes | |
| STEERING & SUSPE | ENSION | |
| STEERING | Hydrostatic Power | |
| FRONT/REAR SUSPENSION | Solid axle w/ leaf springs & shock absorbers | |
| SERVICE BRAKE | Heavy-Duty Hydraulic Four Wheel Disk Brakes w/ 10.7 in. Disk | |
| PARKING BRAKE | Hand Lever Actuated Disk Brakes on Rear Wheels | |
| FONT TYRES | 23 x 10.5 - 14 6-ply Ribbed (2WD) / 14 6-ply Treaded (4WD) | |
| REAR TYRES | 26 x 12 - 14 6-ply Ultra Chevron Tread | |

