

AGROFARM C SERIES



DEUTZ-FAHR
AGROFARM 95 C



TECHNICAL DATA

AGROFARM C

95

ENGINE		
Emissions		Tier1
Manufacturer		SDF 1000.4 W
Cylinders/Capacity	No./cc	4/4,000
Turbocharged aspiration		•
Max. homologated power (ECE R 120)	kW/hp	69.9/94
Max. engine speed (rated)	rpm	2,500
Max. torque	Nm	330
Engine control mechanical		•
Cyclone prefilter		◦
Cooling liquid		•
Fuel tank capacity	litres	85
Biodiesel fuel	%	B100
MECHANICAL GEARBOX		
Synchromesh		•
Number of speeds, 5 gears with supercreeper gear	n°	20+20
Min. speed with supercreeper gear	km/h	0.18/1.61
Max. speed	km/h	40
Mechanical dry clutch, single heavy duty 13"		•
REAR PTO		
Hydraulic multi disc clutch		•
Mechanical engagement		•
PTO 540/1,000		•
FRONT AND REAR AXLE		
Front wheel drive mechanically engaged (only 4WD versions)		•
Mechanically operated differential lock		•
Steering angle/turning circle 4WD	degrees/mm	50°/4,500
BRAKES		
Braking system with wet brake discs		•
Mechanical parking brake		•
STEERING		
Hydrostatic steering with independent pump		•
HITCH		
Category		II
Rear hitch mechanical		•
Rear hitch lift capacity	kg	3,084
HYDRAULIC SYSTEM		
Pump output (std)	l/min	42.2
Open-centre hydraulic system		•
Mechanical distributor engagement		•
Rear auxiliary hydraulic distributors	No. of ways	4/6 OPT
DRIVING POSITION		
Side control levers		•
Platform with ROPS		•
Driver seat with mechanical suspension		•
Instrumentation analogue		•
DIMENSIONS AND WEIGHTS		
Standard rear tyres		460/85R34"
Max. length	mm	3,635
Width	mm	3,920-3,990
Wheelbase	mm	2,360
Front track	mm	1,400-1,700
Rear track	mm	1,500-1,600
Max height with roll bar	mm	2,278
Weight	kg	3,200
Maximum load capacity	kg	5,450

STD • OPT ◦ - Not available

Technical specifications and images are purely indicative. DEUTZ-FAHR reserves the right to make updates at any time and without prior notice. For standard equipment and options refer to the current price list and ask your local dealer for details.

