

EQUIPMENT VARIANTS

Fendt 200 Vario V/F/P.

Simply. Top notch.

	Fendt 200 Vario V/F/P	200V	200 F	200 P
Engine	Water-cooled turbo engine	■	■	■
	AGReX external exhaust gas recirculation	■	■	■
	Integrated air filter pre-cleaner	■	■	■
	Automatic cold-start	■	■	■
	Engine preheater	□	□	□
Transmission	TurboDutch function	■	■	■
	Cruise control	■	■	■
	TMS – Tractor Management System	□	□	□
	Automatic maximum output control 2.0	■	■	■
PTO	Rear 540/540E/1000 rpm	■	■	■
	Rear 540/ground/750 rpm	□	□	□
	Front 540 rpm or 1000 rpm	□	□	□
	PTO engagement control, electrohydr. preselection	■	■	■
	External controls for rear PTO	■	■	■
Chassis, driving safety	Front axle suspension self-levelling, lockable	□	□	□
	Shock load stabilising, electro-hydraulic linkage control	■	■	■
	Compressed air system			□
Linkage	Electrohydraulic linkage control EHR	■	■	■
	Swinging power lift	■	■	
	Mech. lateral and tilt control	■	■	
	Hydr. lateral and tilt adjustment with enhanced actuation	□	□	
	Quick coupler	■	■	■
	Steep lift	□	□	□
	Front linkage	□	□	□
Tilt control indicator, swinging power lift	□	□		
4WD/differential locks	Comfort controls 4WD/differential locks steering angle and speed-controlled	■	■	■
	Automatic front differential lock			■
	Rear and front differential with multi-disc locks	■	■	
	Fully protected cardan shaft	■	■	■
Hydraulics	Hydraulic tandem pump (max. 76 l/min) with hydraulic oil cooler	■	■	■
	Displacement pump (max. 106 l/min)	□	□	□
	2 electr. proportional valves – da flow controller floating position	■	■	■
	Up to 6 electr. proportional valves	□	□	□
	Crossgate lever	■	■	■
Impulse socket for external implement operation	■	■	■	

	Fendt 200 Vario V/F/P	200V	200 F	200 P
Operator environment	Safety frame	■		■
	Vario Joystick	■	■	■
	Height and tilt-adjustable steering column	■	■	■
	Self-cancelling flashers	■	■	■
	Additional lights, front (integral)	□	□	□
	Comfort seat with air suspension	■	■	■
	Comfort cab	□	■	□
	Profi equipment level: Multifunction joystick	□	□	□
	Hinged front / rear windows	■	■	■
	Roof window, hinged, with roller shade	■	■	■
	Hot water heater with 3-speed blower	■	■	■
	Integrated air conditioning	□	□	□
	Automatic climate control	□	□	□
	Activated carbon filters	□	□	□
Rear working lights	□	□	□	
Telescoping ext. rearview mirror	□	□	□	
Body	Low roof version	□	□	□
	Implement mounting plate	□	□	□
	Weights	□	□	□
	Socket for electr. speed signals	■	■	■
	Turn signal indicator front roof*	□		

* depends on the country's regulations

FENDT 200 VARIO V/F/P

Technical Specifications.



Fendt 200 Vario V/F/P		207		208		209			210			211			
		V	F	V	F	V	F	P	V	F	P	V	F	P	
Engine	Rated speed (kW/DIN hp) ECER24	51/70	51/70	59/80	59/80	67/90	67/90	67/90	73/100	73/100	73/100	81/110	81/110	81/110	
	Rated power (kW/hp) EC 97/68	28/38	28/38	30/41	30/41	32/44	32/44	32/44	34/46	34/46	34/46	36/49	36/49	36/49	
	Maximum power (kW/hp) EC 97/68	55/75	55/75	63/85	63/85	70/95	70/95	70/95	77/105	77/105	77/105	85/115	85/115	85/115	
	No. of cylinders/cooling	3/water	3/water	3/water	3/water	3/water	3/water	3/water	3/water	3/water	3/water	3/water	3/water	3/water	
	Bore/stroke (mm)	108/120	108/120	108/120	108/120	108/120	108/120	108/120	108/120	108/120	108/120	108/120	108/120	108/120	
	Cubic capacity (cm ³)	3300	3300	3300	3300	3300	3300	3300	3300	3300	3300	3300	3300	3300	
	Rated engine speed (rpm)	2200	2200	2200	2200	2200	2200	2200	2200	2200	2200	2200	2200	2200	
	Opt. fuel consumption (g/kWh)	212	212	212	212	210	210	210	210	210	210	210	210	210	
	Max. torque Nm/rpm 1600 rpm	295	295	337	337	373	373	373	408	408	408	458	458	458	
	Torque rise (%)	35	35	32	32	30	30	30	30	30	30	30	44	44	
	Fuel tank capacity (l)	76	76	76	76	76	76	76	76	76	76	76	76	76	
	Transmission/PTO	Type	continuously variable Vario transmission												
		Speed range (forward / reverse)	0.02 to 40 km/h / 0.02 to 25 km/h												
Maximum speed 4WD (km/h) ²⁾		40	40	40	40	40	40	40	40	40	40	40	40	40	
Powershift rear PTO standard		540 / 540E / 1000													
Optional		540 / 540E / ground PTO ¹⁾													
Powershiftable front PTO ¹⁾	540 or 1000 ¹⁾														
Brakes	Rear brakes	wet ring piston brake													
	Four-wheel braking system for 4WD	Automatic 4WD engagement / hydraulic drum brake													
Electrical equipment	Battery (Ah)	50													
	Alternator	14 V / 120 A													
Weights and dimensions	Unladen weight with cab (kg)	2780	2860	2780	2860	2780	2860	3080	2780	2860	3080	2780	2860	3080	
	Unladen weight with safety bar (kg)	2580	—	2580	—	2580	—	2860	2580	—	2860	2580	—	2860	
	Max. perm. overall weight (kg)	4500	4500	4500	4500	4500	4500	5300	4500	4500	5300	4500	4500	5300	
	Max. hitch load (kg)	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	
	Overall length (mm)	3578	3683	3578	3683	3578	3683	3701	3578	3683	3701	3578	3683	3701	
	Overall width narrow/wide (mm)	1070/1161	1340	1151/1269	1372	1151/1269	1372	1679	1269/1269	1372	1679	1305/1305	1372	1717	
	Wheelbase (mm)	2160	2160	2160	2160	2160	2160	2160	2160	2160	2160	2160	2160	2160	
	Overall height comfort cab (mm)	2360	2443	2390	2462	2390	2462	2486	2390	2462	2486	2390	2462	2488	
	Overall height low roof version (mm)	2210	2293	2240	2312	2240	2312	2336	2240	2312	2336	2240	2312	2338	
	Overall height safety frame (mm)	2383	—	2413	—	2413	—	2509	2413	—	2509	2413	—	2511	

1) Upon request 2) Speed depends on tyres

Contact to Fendt.

fendt.com

Here you will find everything online, from brochures to technical specifications, reports about customers or the company, up to the Fendt event calendar.

Fendt Configurator

With the Fendt Vehicle Configurator, you can choose from all the available equipment variations and put together the optimally equipped vehicle for your farm. The Fendt Configurator is available online at www.fendt.com, where you will find a quick link to it directly on the start page.

fendt.tv

Fendt around the clock – our Fendt Media Library makes it possible. Our internet TV provides you with news and information about Fendt 24/7.

Test drives

At fendt.com, you will find the area Service and Sales under "Fendt World". Select the "tractor demonstration service", then you can already register for a test drive with a tractor.

facebook.com/FendtGlobal

Over 200,000 fans have already friended Fendt on Facebook. Come have a look.

	Tyres		Min. track		Min. width
	Front	Rear	Front	Rear	Rear
207 V	7.5L15	280/85R24	794	777	1070
208 V	7.5R16	320/85R24	862	831	1155
209 V		12.4R24		831	1152
210 V		360/70R24		857	1202
211 V	280/60-15.5	420/65R20	946	887	1297
		400/70R20		927	1325
	10.0/75-15.3	320/70R24	844	831	1151
		12.4R24		831	1152
		360/70R24		857	1202
	11LR-16	380/70R24	948	897	1277
		440/65R24		957	1377
	265/70R16	12.4R24	852	831	1152
		320/70R24		831	1155
		400/60-26.5		957	1357
	280/70R16	320/85R24	852	831	1155
		12.4R24	831	831	1152
		340/80R24		857	1197
		360/70R24		857	1217
		420/65R24		957	1377
	320/65R16	380/70R24	948	897	1277
		440/65R24		957	1377

207 V	7.5L-15	280/85R24	894	831	1124
208 V	7.50R16	320/85R24	962	869	1193
209 V		12.4R24		869	1190
210 V		360/70R24		857	1202
211 V	280/60-15.5	420/65R20	1046	887	1297
	10.0/75-15.3	12.4R24	944	869	1193
		320/70R24		869	1190
	11LR-16	380/70R24	952	897	1277
		440/65R24		957	1377
	320/65R16	380/70R24	952	897	1277
		440/65R24		957	1377

	Tyres		Min. track		Min. width
	Front	Rear	Front	Rear	Rear
207 F – 211 F	280/70R18	12.4R28	1064	1000	1322
		14.9R24		1057	1459
		420/70R24		1088	1508
	280/80R18	13.6R28	1064	1000	1372
		380/70R28		1057	1447
		340/85R28		1000	1343
	11LR16	380/70R24	1048	1057	1497
		440/65R24		1057	1497
	320/65R16	380/70R24	1048	1057	1437
		440/65R24		1057	1497
	320/65R18	420/70R24	1064	1088	1508
		12.4R28		1057	1477
	340/65R18	13.6R28	1064	1000	1372
		340/85R28		1057	1447
		340/85R28		1000	1343
	440/65R28		1057	1477	
209 P – 211 P	280/80R18	380/85R28	1212	1288	1668
		14.9R28		1188	1598
		420/70R28		1288	1703
	280/70R20	420/70R28	1212	1288	1703
		380/85R28		1288	1668
		14.9R28		1188	1598
		480/65R28		1288	1739
	11LR16	14.9R24	1235	1288	1696
		420/70R24		1288	1703
	340/65R18	14.9R28	1352	1788	1598
	380/85R28		1288	1679	
	420/70R28		1288	1708	
	480/65R28		1288	1739	

Note:

Standard equipment

Optional

What can we do for you?

What makes Fendt Service different?

For us, service means knowing and understanding your work in order to meet your demands for reliability and safety and to act in your economic interest. We stand behind our products and have developed them for the highest demands and long-term operation. Our service is the partnership aspect for your work.

What is Fendt Expert?

Become a Vario pro with Fendt Expert driver training: Are you already familiar with all the functions that the technology has to offer? Take advantage of the technology that is found in every Fendt Vario and learn how to optimise the use of all the features with Fendt Expert. Our team of professional instructors offers you competent instruction to enable you to exploit the full performance potential of your Fendt tractor. Inform yourself through your dealer and sign up.



FENDT SPOTLIGHT.
NOTABLE. BETTER.

This symbol stands for solutions that offer special benefits for your daily work and make a Fendt a Fendt.