T540iXP Product no: 967 86 37-12

Husqvarna



Husqvarna T540i XP is our most powerful battery-powered top-handle chainsaw, equivalent to a 40cc petrol saw. This saw is the ideal tool for all professional tree care. Designed for arborists who want a smooth, high performance chainsaw. Features excellent ergonomics, high chain speed, low weight and all the benefits of battery power, without compromising cutting performance. The integrated connectivity makes it easy to keep track of usage stats, service history and last known location in the Husqvarna Fleet Services[™] app.

Li-ion power

The Li-ion battery provides long lasting power and top class performance.



High chain speed High chain speed for fast, smooth cutting

Husqvarna Connect

With the smart Husqvarna Connect app, you'll have easy access to tips, manuals and spare part recommendations. The app also provides additional information such as runtime and charging status as well as maintenance and service needs.

Flip-up oil tank cap

The flip-up oil tank cap is easy to open and the transparent indicator makes it easy to monitor chain oil levels.







savE[™]

Ρ

Choose between normal or savE[™] mode, depending on conditions, for maximum power or maximum runtime.

Efficient brushless motor Our in-house developed, advanced brushless motor is 25% more efficient than a standard brush motor. This means that the motor provides a high and consistent torque.

Rope Attachment and Belt Eyelet

A sturdy point for fastening a rope, making it easy to hoist the saw up into a tree, as well as a belt eyelet for quick and easy to connect the saw to the climbing harness.

Intuitive key pad

Easy to operate key pad that ensures the machine does not switch on accidentally. Also displays battery status.









WWW.HUSQVARNA.COM

T540iXP Product no: 967 86 37-12

Husqvarna

TECHNICAL SPECIFICATIONS				
Battery & Motor specifications		Other Features		
Battery Type	Li-lon	Weatherproof rating	IPX4	
Battery voltage	36 V	Retained Bar nuts	Yes	
Motor type	BLDC (brushless)	Rope attachment	Yes	
Lubricants		Belt eyelet	Yes	
Oil tank volume	0.2 L	Cutting equipment		
Oil pump type	Adjustable	Standard bar length	12"	
Oil pump capacity	0-200 ml/min	Chain pitch	0.325" Pixel	
Vibration & noise data		Chain gauge	.043" (1.1mm)	
Equivalent vibration, front / rear	2.1 / 3.4 m/s ²	Chain speed at max power	24 m/s / 79 fts	
Sound pressure level	92 dB(A)	Overall dimensions		
Sound power level, guaranteed (LWA)	103 dB(A)	Weight (excl. battery)	2.5 kg	
Other		Weight (Incl. BLi200X battery, and cutting equipment)	3.75 kg	
IP rating	IPX4			
Retained Bar Nuts	Yes			

STANDARD EQUIPMENT		
Part Number	Description	
593 91 43-51	12" X-Precision Guide Bar .325" MINI Laminated Small Bar Mount.	
593 91 41-51	51DL Chain Loop, SP21G .325" MINI Pitch .043" (1.1mm)	

ACCESSORIES		
Part Number	Description	
970 44 89-01	Battery BLi200X	
967 07 19-01	Battery BLi300	
967 09 31-01	BLi550X Battery Backpack	
967 09 32-01	BLi950X Battery Backpack	
967 09 15-05	Battery Charger QC500	
590 77 67-01	Battery Belt Flexi - Carrier Kit	
590 77 67-02	Battery Belt Flexi - Adaptor Kit	
585 37 18-01	Battery bag	
585 42 87-01	Battery box - Small	
585 42 88-01	Battery box - Large	
576 86 91-01	Chainsaw bag	
593 91 43-46	10" X-Precision Guide Bar .325" MINI Laminated Small Bar Mount.	
593 91 41-46	46DL Chain Loop, SP21G .325" MINI Pitch .043" (1.1mm)	
593 91 43-59	14" X-Precision Guide Bar .325" MINI Laminated Small Bar Mount.	
593 91 41-59	59DL Chain Loop, SP21G .325" MINI Pitch .043" (1.1mm)	

For parts information relating to this product please refer to Husqvarna parts manual or EPC online. All images are for illustrational purposes only.

HUSQVARNA AUSTRALIA PTY LTD Husqvarna is a r ABN 45 115 475 619 POSTAL ADDRESS Locked Bag 5, Central Coast BC, NSW 2252 AUSTRALIA

Husqvarna is a registered trademark. Copyright © 2019 HUSQVARNA. All rights reserved.

A. All rights reserved. HUSQVARNA NEW ZEALAND LTD CO. NO. 111 861 POSTAL ADDRESS PO Box 76-437, Manukau City, Auckland 2241 NEW ZEALAND

WWW.HUSQVARNA.COM