

# TC242TX

Product no: 960 51 01-99



**Husqvarna**  
READY WHEN YOU ARE



**L** The TC242TX is a high specification machine designed for landowners who need an efficient garden tractor on really large areas all year round. Driven by a powerful Kawasaki V-Twin engine with pedal-operated hydrostatic, fast ground engaging transmission for heavy-duty applications. The large integrated collector ensures a tidy result and the BioClip® from seat function quickly switches the cutting system from collection to mulching mode. Additional features include cruise control, pivoting cast front axle, hour meter with service minder, adjustable sliding seat with arm rests. Rear deflector available as an optional accessory.

### Kawasaki V-Twin engine

Fully pressure-lubricated, two-cylinder Kawasaki engine with oil pump and oil filter. Powerful and quiet.



### BioClip® from seat

Easy switch between collecting and BioClip® (mulching) mode by means of a dashboard-operated central actuation device. You don't have to leave the driver's seat.




### Hydrostatic fast transmission

Speed and direction are managed by pedals, which lets you keep both hands on the steering wheel, for optimum driving control. The fast transmission provides high speed for top performance.



### Electric blade engagement

Easy engagement of cutting blades - simply pull the switch on the control panel.




### Deluxe comfort seat

Deluxe comfort seat features premium vinyl, stitched design and extra thick cushions for improved comfort and superb ride quality.



### Reinforced cutting deck

The stamped cutting deck is reinforced with heavy flat-stock steel for added strength and durability on the leading edge and trim side.



### Air Induction™

Our innovative Air Induction™ mowing system draws clean air from the top and bottom of the deck, enhancing air flow which results in greater grass lift and superior cut.



### Integrated collector

The large, effective collector is perfect for collecting leaves as well as grass. As signal indicates when it is time to empty the collector, which can easily be emptied from the driver's seat.



# TC242TX

Product no: 960 51 01-99



Husqvarna®  
READY WHEN YOU ARE

## TECHNICAL SPECIFICATIONS

Engine		Other	
Engine manufacturer	Kawasaki	Seat type	Deluxe SK 15"
Engine name	FR Series V-Twin	Seat material	Vinyl
Engine type	FR651V-AS28	Steering wheel type	Deluxe overmolded
Gross Horsepower* <small>*As per SAE J1940 as rated by Briggs &amp; Stratton</small>	21.5 hp	Front-end protection	Brush Guard Style Bumper
Cylinder displacement	726 cm <sup>3</sup>	Hour meter	Digital with pre-programmed service intervals
Cylinders	2	Aluminium racing foot pedal	Yes
Engine cooling	Air	Deflector	Available as accessory
Generator	16	Collector	Integrated, 320L
Battery	12 V 14 Ah	BioClip® kit/plug	Included
Air Filter type	Paper	Dimensions	
Fuel Type	Petrol	Tyre size, front	15x6-6"
Fuel tank volume	13.3 litre	Tyre size, rear	18x9.5-8"
Fuel tank location	Front	Turning radius, min	46cm / 18"
Engine lubrication type	Pressure with Oil filter	Wheelbase	119.0cm / 47.0"
Oil capacity	1.66 litre	Base machine, length	252.0cm / 99.2"
Oil filter	Yes	Base machine, width	112.0cm / 44.1"
Drive system		Base machine, height	112.0cm / 44.1"
Transmission type	Hydrostatic	Weight	257 kg
Transmission manufacturer	Tuff Torq	ACCESSORIES	
Transmission model	K57R	Part Number	Description
Drive method	Pedal-operated	960 71 00-42	Rear Deflector
Speed forward, min-max	0 - 11.9 km/h	505 56 88-13	Brush Guard
Speed reverse, min-max	0 - 4.7 km/h	597 65 82-03	Arm rest kit
Cutting deck		967 02 72-01	Spreader, 75kg
Cutting width	108 cm / 42"	954 12 00-46	Spreader, 30kg
Cutting deck type	Stamped, Reinforced	576 21 75-01	Tow-behind Sprayer
Cutting deck material	Steel	505 63 08-82	Tractor Cover
Cutting methods	Collection/BioClip®	531 30 82-28	Tractor Seat Cover
Cutting height, min-max	38 - 102 mm	579 45 01-02	Battery Charger
Cutting height adjustment	Infinity	579 45 21-01	Batter Staus Indicator
Cutting height steps	6	505 69 90-43	Loading Ramps
Cutting height adjuster	Fender-mounted		
Blade engagement	Electric		
Blades	2		
Blade type	Hi Performance		
Anti-scalp wheels	4		
Nose roller	N/A		
Powder-coated cutting deck	Yes		
Deck wash port	Yes		

For parts information relating to this product please refer to Husqvarna parts manual or EPC online.  
All images are for illustrational purposes only.

Husqvarna is a registered trademark. Copyright © 2020 HUSQVARNA. All rights reserved.

HUSQVARNA AUSTRALIA PTY LTD  
ABN 45 115 475 619  
POSTAL ADDRESS Locked Bag 5, Central Coast BC, NSW 2252 AUSTRALIA

HUSQVARNA NEW ZEALAND LTD  
CO. NO. 111 861  
POSTAL ADDRESS PO Box 76-437, Manukau City, Auckland 2241 NEW ZEALAND

WWW.HUSQVARNA.COM