



## Husqvarna TS 114

Purposely engineered for ease of use, this reliable garden tractor delivers an exceptional mowing experience on any large lawn – even in narrow passages. Achieve excellent results without straining your body thanks to its ergonomically placed levers, side-by-side pedals and spring-assisted cutting deck. Conveniently compact for optimised storage, maintenance and operation, enjoy trouble-free ownership and a perfectly cut lawn.



### Adjustable driver seat

Tool-free adjustment of seat position to quickly set a comfortable driving position.



### Hour meter

Hour meter for easy control of operating time and service and maintenance intervals.

### Dual headlights

Dual headlights at the front for clear visibility when driving in dark conditions.



### Ergonomic controls

Comfortable driving position and operation thanks to the adjustable seat and easy-access controls. Spring-assisted cutting height adjustment for easy setting of the desired height.



## FEATURES

- Dual headlights at the front for clear visibility when driving in dark conditions.
- Hour meter for easy control of operating time and service and maintenance intervals.
- Tool-free adjustment of seat position to quickly set a comfortable driving position.
- Comfortable driving position and operation thanks to the adjustable seat and easy-access controls.
- Equipped with a 95cm side discharge cutting deck.
- The cutting deck is equipped with anti-scalp wheels, which reduce the risk of scalping when cutting uneven lawns.
- Compact design for effortless navigation in narrow passages and easy storage while not in use.
- ROS is activated with the start key for quick access to reverse mowing, and to minimise the risk of the function being used unintentionally.
- Fuel level window makes it easy to check the fuel level.
- Dual pedal drive for better drive control and easy, intuitive operation.
- Additional functionality thanks to the included towing hook which enables the use of many accessories.
- Control levers on only one side make it easy to get in and out of the seat on the other side.
- Easy engagement of cutting blades; simply pull the switch on the control panel.
- Easy speed and direction control with pedal-operated hydrostatic transmission.
- Easy to get operating under any weather condition and no choking needed. Just turn the key and go.
- Easily accessible cutting height adjustment for improved ergonomics.

Technical Specifications	
<b>BATTERY</b>	
Battery capacity	20 Ah
Battery voltage	12 V
<b>CAPACITY</b>	
Net power at preset rpm	2800 rpm
Power output	9.0 kW
<b>DIMENSIONS</b>	
Article gross weight	209000 g
Article net weight	169000 g
Base machine, height	110 cm
Base machine, length	166.5 cm
Base machine, width (chute down)	119 cm
Base machine, width	92 cm
Cutting height adjuster	Fender-mounted
Cutting height adjustment	Lever, while seated
Cutting height steps	6
Cutting width	95 cm
Height	110 cm
Seat back height	Medium
Tyre dimensions, front	15x6-6
Tyre dimensions, rear	18x8.5-8
Weight (complete product w/o side packed articles)	184 kg
Wheelbase	115 cm
<b>ENGINE</b>	
Cylinders	1
Cylinder displacement	452 cm <sup>3</sup>
Engine brand	Husqvarna
Engine cooling	Air
Engine name	HS 452AE
Fuel tank volume	6 l
Fuel tank volume	1.59 gal (US)
Generator	12 A
Motor/engine manufacturer	Husqvarna
Motor/engine model	HS 452AE
Transmission manufacturer	Hydro-Gear
Transmission model	T2
Transmission type	Hydrostatic
<b>EQUIPMENT</b>	
Air filter type	Cartridge with pre filter
Anti-scalp wheels	2
BioClip® kit	Available as accessory
Blade engagement	Electric clutch
Blade type	Discharge
Blades	2 pcs
Collector	Available as accessory
Cup holder	Yes
Cutting deck type	Stamped
Cutting methods	Collection/BioClip®/Side discharge
Deck Wash Port	Yes
Deflector	No
Drive method	Dual pedal-operation
Front-End Protection	Available as accessory

Technical Specifications	
Generator	12 A
Greasable mandrels	No
Headlights	Yes
Hour meter type	Digital
Mulching kit	Available as accessory
Powder-coated cutting deck	No
Seat type	Standard
<b>LUBRICANTS</b>	
Engine lubrication type	Pressure with Oilfilter
Fuel consumption	412 g/kWh
Fuel tank location	Front
Oil capacity	1.2 l
Oil filter	Yes
Power/fuel type	Petrol
<b>MATERIALS</b>	
Cutting deck material	Steel
Master pack: Paper + Cardboard	0 g
Metal total	3820 g
Paper + Cardboard total	7410 g
PE total	336.7 g
PET total	0 g
Plastic foil	336.7 g
Plastic rigid	0 g
Plastic total	336.7 g
PS/EPS/HIPS total	0 g
Seat material	PU
<b>PACKAGING</b>	
Packaging height	850 mm
Packaging length	1700 mm
Packaging volume	1640 dm <sup>3</sup>
Packaging width	1135 mm
Quantity in Master pack	1
<b>SOUND AND NOISE</b>	
Sound power level, guaranteed (LWA)	97.6 dB(A)
Sound pressure level at operators ear	83.4 dB(A)
<b>VIBRATIONS</b>	
Vibration level seat	2.0 m/s <sup>2</sup>
Vibration level steering wheel	5.6 m/s <sup>2</sup>