TS142TXD

Product no: 960 41 04-50





The TS142TXD is ideal for home and landowners with larger gardens who need a durable and comfortable garden tractor with high manoeuvrability. Driven by a powerful Kawasaki FR Series V-Twin engine and pedal-operated hydrostatic transmission with automatic differential lock for superior control and traction in all conditions. The side ejection cutting deck provides maximum cutting capacity even on areas that are cut less frequently. Collector and BioClip® kit are available as optional accessories.

Kawasaki V-Twin engine

Fully pressure-lubricated, twocylinder Kawasaki engine with oil pump and oil filter. Powerful and quiet.



Fender-mounted cutting height adjustment

Easy accessible cutting height adjustment for improved ergonomics. The spring-assisted cutting deck makes adjustment easier



Hydrostatic transmission with locking differential

The pedal operated hydrostatic transmission offers a smooth, variable forward and reverse speed while the standard automatic locking rear differential increases traction in all cutting conditions.



Electric blade engagement

Easy engagement of cutting blades - simply pull the switch on the control panel.



Cruise control

Ensures the garden tractor maintains consistent speed, even in rough terrain.



Deluxe comfort seat

Deluxe comfort seat features premium vinyl, stitched design and extra thick cushions for improved comfort and superb ride quality.



Air Induction[™]

Our innovative Air Induction™ mowing system draws clean air from the top and bottom of the deck, enhancing air flow which results in greater grass lift and superior cut.



Pivoting front axle

The pivoting front axle provides excellent balance and driving comfort, ensuring superior access.



TS142TXD

Product no: 960 41 04-50



TECHNICAL SPECIFICATIONS				
Engine		Other		
Engine manufacturer	Kawasaki	Seat type	Deluxe SK, 15"	
Engine name	FR Series V-Twin	Seat material	Vinyl	
Engine type	Model FR651V-AS28	Steering wheel type	Deluxe overmolded	
Gross Horsepower	21.5 hp	Front-end protection	Brushguard bumper	
Cylinder displacement	726 cm ³	Hour meter	Digital with pre-programmed service intervals	
Cylinders	2	Aluminium racing foot pedal	N/A	
Engine cooling	Air	Deflector	Yes - Side discharge	
Generator	15	Collector	Available as accessory	
Battery	12 V 28 Ah	BioClip® kit/plate	Available as accessory	
Air Filter type	Paper	Dimensions		
Fuel Type	Petrol	Tyre size, front	15x6-6"	
Fuel tank volume	11.4 litre	Tyre size, rear	20x10-8"	
Fuel tank location	Rear	Turning radius, min	41cm / 16"	
Engine lubrication type	Pressure with Oil filter	Wheelbase	121.9cm / 48.0"	
Oil capacity	1.89 litre	Base machine, length	179.1m / 70.5"	
Oil filter	Yes	Base machine, width (chute down)	124.4cm / 49.0"	
Drive system		Base machine, width (chute up)	112cm / 44.1"	
Transmission type	Hydrostatic	Base machine, height	110cm / 43.5"	
Transmission manufacturer	Tuff Torq	Weight	215 kg	
Transmission model	K46CR (Locking Differential)			
Drive method	Pedal-operated	ACCESSORIES		
Speed forward, min-max	0 - 6.7 km/h	Part Number	Description	
Speed reverse, min-max	0 - 2.54 km/h	960 73 00-04	Collector	
Cutting deck		960 71 00-44	Mulch Kit	
Cutting width	107 cm / 42"	597 65 82-03	Arm rest kit	

ACCESSORIES			
Part Number	Description		
960 73 00-04	Collector		
960 71 00-44	Mulch Kit		
597 65 82-03	Arm rest kit		
505 56 88-13	Brush Guard Bumper		
967 02 72-01	Spreader, 75kg		
954 12 00-46	Spreader, 30kg		
576 21 75-01	Tow-behind Sprayer		
505 63 08-82	Tractor Cover		
531 30 82-28	Tractor Seat Cover		
579 45 01-02	Battery Charger		
579 45 21-01	Batter Status Indicator		
505 69 99-43	Loading Ramps		

For parts information relating to this product please refer to Husqvarna parts manual or EPC online. All images are for illustrational purposes only.

Stamped, Reinforced Steel

> Side discharge 38 - 102 mm

> > Notch 6

Fender-mounted

Electric 2

High Performance

2

N/A

Yes

Husqvarna is a registered trademark. Copyright © 2020 HUSQVARNA. All rights reserved.

HUSQVARNA AUSTRALIA PTY LTD
ABN 45 115 475 619
POSTAL ADDRESS Locked Bag 5, Central Coast BC, NSW 2252 AUSTRALIA

Cutting deck type

Cutting deck material Cutting methods

Cutting height, min-max Cutting height adjustment

Cutting height steps
Cutting height adjuster

Blade engagement

Powder-coated cutting deck

Blades

Blade type Anti-scalp wheels

Nose roller

Deck wash port

HUSQVARNA NEW ZEALAND LTD
CO. NO. 111 861
POSTAL ADDRESS PO Box 76-437, Manukau City, Auckland 2241 NEW ZEALAND