

# TS242TXD

Product no: 960 41 04-51



Husqvarna®  
READY WHEN YOU ARE



**L** The TS242TXD is a high spec garden tractor designed for landowners who need an efficient machine on really large areas all year round. Driven by a powerful Kawasaki FR Series V-Twin engine with pedal-operated hydrostatic transmission and automatic rear differential lock for superior traction and control. The ClearCut™ fabricated deck not only offers rock solid durability but also industry leading performance and cut quality. Additional features include cruise control, pivoting cast front axle, LED headlights, hour meter with service minder, adjustable sliding seat with arm rests. Collector and BioClip® kit are available as optional accessories.

### Kawasaki V-Twin engine

Fully pressure-lubricated, two-cylinder Kawasaki engine with oil pump and oil filter. Powerful and quiet.



### Fender-mounted cutting height adjustment

Easy accessible cutting height adjustment for improved ergonomics. The spring-assisted cutting deck makes adjustment easier.



### Hydrostatic transmission with locking differential

The dual-pedal drive operated hydrostatic transmission offers a smooth, variable forward and reverse speed while the standard automatic locking rear differential increases traction while cutting on slopes or wet grass.



### Electric blade engagement

Easy engagement of cutting blades - simply pull the switch on the control panel.



### Cruise control

Ensures the garden tractor maintains consistent speed, even in rough terrain.



### Pivoting front axle

The pivoting front axle provides excellent balance and driving comfort, ensuring superior access.



### ClearCut™ fabricated deck

ClearCut™ fabricated cutting deck features deep deck design, air flow control baffles, high performance blades and top discharge. Constructed from welded 10 gauge steel with additional welded reinforcement strips for maximum durability.



### Deluxe comfort seat

Deluxe comfort seat features premium vinyl, stitched design and extra thick cushions for improved comfort and superb ride quality. Arm Rests included.



WWW.HUSQVARNA.COM

# TS242TXD

Product no: 960 41 04-51



Husqvarna®  
READY WHEN YOU ARE

## TECHNICAL SPECIFICATIONS

Engine		Other	
Engine manufacturer	Kawasaki	Seat type	Deluxe SK 15" with Arm rests
Engine name	FR Series V-Twin	Seat material	Vinyl
Engine type	Model FR651V-AS28	Steering wheel type	Deluxe overmolded
Gross Horsepower	21.5 hp	Front-end protection	Brush Guard Style Bumper
Cylinder displacement	726 cm <sup>3</sup>	Hour meter	Digital with pre-programmed service intervals
Cylinders	2	Aluminium racing foot pedal	Yes
Engine cooling	Air	Deflector	Yes - Side discharge
Generator	15	Collector	Available as accessory
Battery	12 V 28 Ah	BioClip® kit/plate	Available as accessory
Air Filter type	Paper Element	Dimensions	
Fuel Type	Petrol	Tyre size, front	15x6-6"
Fuel tank volume	15.1 litre	Tyre size, rear	20x10-8"
Fuel tank location	Rear	Turning radius, min	41cm / 16"
Engine lubrication type	Pressure with Oil filter	Wheelbase	121.9cm / 48"
Oil capacity	1.66 litre	Base machine, length	175.9cm / 69.25"
Oil filter	Yes	Base machine, width (chute down)	144cm / 56.7"
Drive system		Base machine, width (chute up)	110.5cm / 41.4"
Transmission type	Hydrostatic	Base machine, height	106cm / 41.4"
Transmission manufacturer	Tuff Torq	Weight	263 kg
Transmission model	K46CR (Locking Differential)	ACCESSORIES	
Drive method	Dual pedal	Part Number	Description
Speed forward, min-max	0 - 8.9 km/h	587 41 27-01	Collector
Speed reverse, min-max	0 - 4.7 km/h	587 41 23-01	Mulch Kit
Cutting deck		505 56 88-13	Brush Guard
Cutting width	107 cm / 42"	967 02 72-01	Spreader, 75kg
Cutting deck type	Fabricated, ClearCut™	954 12 00-46	Spreader, 30kg
Cutting deck material	Steel	576 21 75-01	Tow-behind Sprayer
Cutting methods	Side discharge	505 63 08-82	Tractor Cover
Cutting height, min-max	38 - 102 mm	531 30 82-28	Tractor Seat Cover
Cutting height adjustment	Notch	579 45 01-02	Battery Charger
Cutting height steps	6	579 45 21-01	Batter Status Indicator
Cutting height adjuster	Fender-mounted	505 69 90-43	Loading Ramps
Blade engagement	Electric		
Blades	2		
Blade type	Hi Performance		
Anti-scalp wheels	2		
Nose roller	Yes		
Powder-coated cutting deck	Yes		
Deck wash port	Yes		

For parts information relating to this product please refer to Husqvarna parts manual or EPC online.  
All images are for illustrational purposes only.

Husqvarna is a registered trademark. Copyright © 2020 HUSQVARNA. All rights reserved.

HUSQVARNA AUSTRALIA PTY LTD  
ABN 45 115 475 619  
POSTAL ADDRESS Locked Bag 5, Central Coast BC, NSW 2252 AUSTRALIA

HUSQVARNA NEW ZEALAND LTD  
CO. NO. 111 861  
POSTAL ADDRESS PO Box 76-437, Manukau City, Auckland 2241 NEW ZEALAND

WWW.HUSQVARNA.COM