

# Z242E

Product no: 970 45 87-01



**Husqvarna**  
READY WHEN YOU ARE



Performance and style hit the grass running with the all new Z200 Series Zero Turn Mowers. Cutting edge design, proven performance and new innovative features combine to make lawn maintenance an event instead of a chore. Packed with features including high performance Clear Cut™ fabricated cutting deck, Removable foot plate, Rear engine guard and Anti-slip foot area.

### Zero-turn steering system

Individual, hydraulic wheel-drive provides very precise manoeuvring and allows the mower to rotate around its own axis, without any turning radius.



### Kawasaki V-Twin engine

Fully pressure-lubricated, two-cylinder Kawasaki engine with oil pump and oil filter. Powerful and quiet.



### Maintenance-Free Transmission

Worry free performance with maintenance free, integrated zero-turn transmissions.



### ClearCut™ Deck

ClearCut™ deck technology features deep deck design, air flow control baffles, high performance blades and top discharge for superior cutting performance whether discharging, bagging or mulching.



### Ergonomic control panel

The ergonomic control panel places everything conveniently at your fingertips.



### Rugged frame and castors

The robust frame and castors ensure durability and reduced chassis flex.



### Convenient deck lift

The deck lift system is spring assisted for ease of use and conveniently located within easy reach of the operator.



### Automatic park brake

The new park brake system (patent pending) automatically activates or deactivates as the steering levers are moved outward or inward, freeing the user of the task.



# Z242E

## Product no: 970 45 87-01



**Husqvarna**  
READY WHEN YOU ARE

### TECHNICAL SPECIFICATIONS

Engine		Other	
Engine manufacturer	Kawasaki	Seat Material	Vinyl
Engine name	FR Series V-Twin	Seat Suspension	Yes
Engine Model	FR600V	Seat back height	High
Gross Horsepower	18.0 hp	Foldable seat	Yes
Cylinder displacement	726 cm <sup>3</sup>	Dimensions	
Cylinders	2	Front Casters Tyres	11 x 4 - 5"
Engine cooling	Air	Rear Drive Tyres	18 x 8.5 - 8"
Generator	TBA	Wheelbase	88.7 cm / 34.9 "
Air Filter type	Paper Element	Ground clearance	105 mm / 4.13 inch
Fuel Type	Petrol	Base machine, length	202 cm / 79.5 inch
Fuel tank volume	13.25 litre	Base machine, width	89 cm / 35 inch
Fuel tank location	Side (Single)	Base machine, height	115 cm / 45.3 inch
Engine lubrication type	Full Pressure	Weight	239 kg / 526.9 lbs
Oil capacity	1.8 litre	Gross weight towed <sup>2</sup>	125 kg / 275.5 lbs
Oil filter	Yes	Productivity	
Drive system		Productivity	2.2 acres/hr
Transmission type	Hydrostatic	ACCESSORIES	
Transmission manufacturer	Hydro-Gear	Part Number	Description
Transmission model	EZT	587 41 24-01	Collector
Pump displacement	10 cm <sup>3</sup>	587 41 23-01	Mulch Kit
Fan-cooled pumps	Yes	532 42 14-99	Arm Rest Kit
Speed forward, min-max	0 - 10.5 km/h	579 45 01002	Battery Charger
Speed reverse, min-max	0 - 5.6 km/h	579 45 21-01	Battery Status Indicator
Cutting deck		505 69 90-43	Loading Ramps
Cutting width	106.68 cm / 42"		
Cutting deck type	Fabricated, ClearCut™		
Cutting methods	3-in-1 capable Side discharge/Collect/Mulch		
Cutting deck material	Steel		
Deck thickness	3.5 mm / 10 gauge		
Cutting height, min-max	38 - 102 mm / 1.5 - 4"		
Cutting height steps	6		
Blade engagement	Electric clutch		
Blades	2		
Blade-tip speed (ft/min)	18500		
Anti scalp wheels	1		
Nose roller	Yes		
Deck lifting system	Manual, hand operated		
Powder-coated cutting deck	Yes		
Spindle/mandrel type	Cast Iron		
Greasable mandrels	Yes		
Deck wash port	Yes		

For parts information relating to this product please refer to Husqvarna parts manual or EPC online. All images are for illustrational purposes only.

Husqvarna is a registered trademark. Copyright © 2020 HUSQVARNA. All rights reserved.

HUSQVARNA AUSTRALIA PTY LTD  
ABN 45 115 475 619  
POSTAL ADDRESS Locked Bag 5, Central Coast BC, NSW 2252 AUSTRALIA

HUSQVARNA NEW ZEALAND LTD  
CO. NO. 111 861  
POSTAL ADDRESS PO Box 76-437, Manukau City, Auckland 2241 NEW ZEALAND

[www.husqvarna.com](http://www.husqvarna.com)