

Z242F

Product no: 970 45 88-01



Husqvarna®
READY WHEN YOU ARE



L Performance and style hit the grass running with the all new Z200 Series Zero Turn Mowers. Cutting edge design, proven performance and new innovative features combine to make lawn maintenance an event instead of a chore. Packed with features including high performance ClearCut™ fabricated cutting deck, Removable foot plate, Rear engine guard and Anti-slip foot area.

Zero-turn steering system

Individual, hydraulic wheel-drive provides very precise manoeuvring and allows the mower to rotate around its own axle, without any turning radius.



Kawasaki V-Twin engine

Fully pressure-lubricated, two-cylinder Kawasaki engine with oil pump and oil filter. Powerful and quiet.



Maintenance-Free Transmission

Worry free performance with maintenance free, integrated zero-turn transmissions.



ClearCut™ Deck

ClearCut™ deck technology features deep deck design, air flow control baffles, high performance blades and top discharge for superior cutting performance whether discharging, bagging or mulching.



Ergonomic control panel

The ergonomic control panel places everything conveniently at your fingertips.



Rugged frame and castors

The robust frame and castors ensure durability and reduced chassis flex.



Convenient deck lift

The deck lift system is spring assisted for ease of use and conveniently located within easy reach of the operator.



Automatic park brake

The new park brake system (patent pending) automatically activates or deactivates as the steering levers are moved outward or inward, freeing the user of the task.



Z242F

Product no: 970 45 88-01



Husqvarna
READY WHEN YOU ARE

TECHNICAL SPECIFICATIONS

Engine		Cutting deck - Continued	
Engine manufacturer	Kawasaki	Powder-coated cutting deck	Yes
Engine name	FR Series V-Twin	Spindle/mandrel type	Cast Iron
Engine Model	FR651V-AS31	Greasable mandrels	Yes
Gross Horsepower	21.5 hp	Deck wash port	Yes
Cylinder displacement	726 cm ³	Other	
Cylinders	2	ROPS	N/A
Engine cooling	Air	Seat type	Deluxe SK 15" with arm rests
Generator	TBA	Seat material	Vinyl
Air Filter type	Paper Element	Seat spring	Yes
Fuel Type	Petrol	Seat back height	High
Fuel tank volume	13.25 litre	Fuel level window	Yes
Fuel tank location	Side (Single)	Hour meter	Digital with pre-programmed service intervals
Engine lubrication type	Full Pressure	Cup holder	Yes
Oil capacity	1.42 litre	Dimensions	
Oil filter	Yes	Tyre size, front	11x6-5"
Drive system		Tyre size, rear	18x8.5-8"
Transmission type	Hydrostatic	Wheelbase	99.6cm / 39.2"
Transmission manufacturer	Hydro-Gear	Base machine, length	190.5cm / 75"
Transmission model	EZT	Base machine, width (chute down)	132.1cm / 52"
Pump displacement	10 cm ³	Base machine, width (chute up)	109.2cm / 43"
Fan-cooled pumps	Yes	Base machine, height	101.6cm / 40"
Speed forward, min-max	0 - 10.5 km/h	Weight	263.09 kg
Speed reverse, min-max	0 - 5.6 km/h	Productivity	
Cutting deck		Productivity	2.2 acres/hr
Cutting width	106.68 cm / 42"	ACCESSORIES	
Cutting deck type	Fabricated, ClearCut™	Part Number	Description
Cutting methods	3-in-1 capable Side discharge/Collect/Mulch	587 41 24-01	Collector
Cutting deck material	Steel	587 41 23-01	Mulch Kit
Deck thickness	3.5 mm / 10 gauge	532 42 14-99	Arm Rest Kit
Cutting height, min-max	38 - 102 mm / 1.5 - 4"	579 45 01-02	Battery Charger
Cutting height steps	6	579 45 21-01	Battery Status Indicator
Blade engagement	Electric clutch	505 69 90-43	Loading Ramps
Blades	2		
Blade-tip speed (ft/min)	18500		
Anti scalp wheels	1		
Nose roller	Yes		
Deck lifting system	Manual, hand operated		

For parts information relating to this product please refer to Husqvarna parts manual or EPC online.
All images are for illustrational purposes only.

Husqvarna is a registered trademark. Copyright © 2020 HUSQVARNA. All rights reserved.

HUSQVARNA AUSTRALIA PTY LTD
ABN 45 115 475 619
POSTAL ADDRESS Locked Bag 5, Central Coast BC, NSW 2252 AUSTRALIA

HUSQVARNA NEW ZEALAND LTD
CO. NO. 111 861
POSTAL ADDRESS PO Box 76-437, Manukau City, Auckland 2241 NEW ZEALAND

www.husqvarna.com