### **Z248F** Product no: 970 45 89-01





Performance and style hit the grass running with the all new Z200 Series Zero Turn Mowers. Cutting edge design, proven performance and new innovative features combine to make lawn maintenance an event instead of a chore. Packed with features including high performance Clear Cut<sup>™</sup> fabricated cutting deck, Removable foot plate, Rear engine guard and Anti-slip foot area.

Zero-turn steering system

Individual, hydraulic wheel-drive provides very precise manoeuvring and allows the mower to rotate around its own axle, without any turning radius.

### Maintenance-Free Transmission

Worry free performance with maintenance free, integrated zero-turn transmissions.

**Ergonomic control panel** The ergonomic control panel places everything conveniently at your fingertips.

**Convenient deck lift** 

The deck lift system is spring assisted for ease of use and conveniently located within easy reach of the operator.







### Kawasaki V-Twin engine

ClearCut<sup>™</sup> Deck

mulching.

chassis flex.

ClearCut<sup>™</sup> deck technology

features deep deck design,

air flow control baffles, high

**Rugged frame and castors** 

The robust frame and castors ensure durability and reduced

performance blades and top discharge for superior cutting performance whether discharging, bagging or

Fully pressure-lubricated, twocylinder Kawasaki engine with oil pump and oil filter. Powerful and quiet.







# www.husqvarna.com

### **Z248F** Product no: 970 45 <u>89-01</u>



Engine manufacturerKawasakiPowder-coated cutting deckYesEngine typeFR Series V-TwinSpindle/mandrel typeCast tronEngine modelFR69IV-AS29Greasable mandrelsYesGross horsepower23 hpDeck wash portYesCylinder displacement726 cm³OtherYesCylinders2ROPSN/AEngine coolingAirSeat typeDeluxe SK 15 with Arm restsGeneratorTBASeat materialVinylAir filter typePaper ElementSeat back heightHighFuel typePaper ElementSeat back heightHighFuel tank volume13.25 litreFuel level windowYesFuel tank locationSide (Single)Hour meterDigital with per-porgrammed service intervalsEngine lubrication typeFull PressureCup holderYesOli capacity1.42 litreDimensionOffve systemTyre size, rear18x6-5*Transmission manufacturerHydro-GearBase machine, length1905cm / 75*Transmission manufacturerHydro-GearBase machine, width (chute down)1518cm / 59.8*Pung displacement10 cm³Base machine, length1905cm / 75*Fan-cooled pumpsYesBase machine, width (chute down)1518cm / 59.8*Speed forward, min-max0 - 10.46 km/hWeight250.89 kgSpeed forward, min-max0 - 56 km/hProductivity25 acres/hrCutting deck KupeFabricaed, ClearCut"52		TECHNICAL SI	PECIFICATIONS	
Engine typeFR Series V-TwinSpindle/mandrel typeCast IronEngine modelFR6SIV-AS29Greasable mandrelsYesGross horsepower23 hpDeck wash portYesCylinder displacement726 cm³OtherCylinder displacement726 cm³OtherFuel typePaper ElementSeat springYesFuel tank volume13.25 litreFuel level windowYesFuel tank locationSide (Single)Hour meterDigital with pre-programmed service intervalsColi capacity14.2 litreDimensionOf capacity14.2 litreDimensionOf capacityHydrostaticWheelbase111tm / 43.75'Of ve systemTyre size, front111tm / 43.75'Transmission manufacturerHydro-GearBase machine, with (chute down)151.8cm / 59.8'Pare-cooled pumpsYesBase machine, length100.5cm / 40'Speed forward, min-max0 - 56 km/hProductivity25 acres/hrCutting deckSide discharge/Collect/Mulch52 55 97-01CollectorCutting deck typeFabricated, ClearCut'52 55 99-01Mulch KitDeck thickness3.5 mm / 10 gauge579 45 01-02<	Engine		Cutting deck - Continued	
Engine modelFR69IV-AS29Greasable mandrelsYesGross horsepower23 hpDeck wash portYesCylinder displacement726 cm³OtherCylinders2ROPSN/AEngine coolingAirSeat typeDeluxe SK 15° with Arm restsGeneratorTBASeat materialVinylAir filter typePaper ElementSeat springYesFuel typePaper ElementSeat springYesFuel typePaper ElementSeat springYesFuel tank locationSide (Single)Hour meterDigital with pre-programmed service intervalsFuel tank locationSide (Single)Hour meterDigital with pre-programmed service intervalsFuel tank locationSide (Single)Hour meterDigital with pre-programmed service intervalsDiffuerYesTyre size. front11k6-5°Drive systemTyre size. front11k6-5°Transmission typeHydrostaticWheelbase111ltm / 4375°Pung displacement10 cm³Base machine, width (chute down)1518cm / 59.8°Pung displacement10 cm³Base machine, height1905cm / 75°Speed forward, min-max0 - 56 km/hProductivity25 acres/hrCutting deckSate ind share/scole (Clarcht)Set 55 99-01Mulch KitCutting deck38-102 m / 48°579 45 01-02Battery Status IndicatorCutting deck typeFabricated. ClearCut*579 45 21-01Battery Status IndicatorCutti	Engine manufacturer	Kawasaki	Powder-coated cutting deck	Yes
Gross horsepower23 hpDeck wash portYesCylinder displacement726 cm³OtherCylinders2ROPSN/AEngine coolingAirSeat typeDeluxe Sk 15 with Arm restsGeneratorTBASeat materialVinylAir filter typePaper ElementSeat springYesFuel typePaper ElementSeat springYesFuel typePatrolSeat back heightHighFuel tank kolume13.25 litreFuel level windowYesFuel tank locationSide (Single)Hour meterDigital with pre-programmed service intervalsFuel tank locationFuel YesTyre size. frontTItA-5"Drive systemTyre size. frontTItA-5"Tyre size. frontTransmission manufacturerHydrostaticWheelbaseTItan. / 4375"Transmission manufacturerHydrostaticMeter	Engine type	FR Series V-Twin	Spindle/mandrel type	Cast Iron
Cylinder displacement 726 cm³ Other N/A   Cylinders 2 ROPS N/A   Engine cooling Air Seat type Deluxe SK 15" with Arm rests   Generator TBA Seat material Vinyl   Air filter type Paper Element Seat spring Yes   Fuel type Petrol Seat back height High   Fuel tank volume 13.25 litre Fuel level window Yes   Seat pring Yes Digital with pre-programmed service intervals   Engine lubrication type Full Pressure Cup holder Yes   Oil capacity 1.42 litre Dimensions Digital with pre-programmed service intervals   Offiter Yes Tyre size, front 11x6-5"   Drive system Tyre size, front 11x6-5"   Transmission manufacturer Hydrostatic Wheelbase 111am / 43.75"   Parne coled pumps Yes Base machine, width (houte down) 1518am / 59.8"   Pump displacement 10 cm³ Base machine, width (houte down) 1518am / 59.8"   Parne coled pumps Yes Base machine, width (houte down) 1518am / 59.8"   Speed reverse, min-max 0 - 10.46 km/h Weight 269.89 kg   Part Number D	Engine model	FR691V-AS29	Greasable mandrels	Yes
Cylinders2ROPSN/AEngine coolingAirSeat typeDeluxe SK 15° with Arm restsGeneratorTBASeat materialVinylAir filter typePaper ElementSeat back heightHighFuel typePetrolSeat back heightHighFuel typePetrolSeat back heightHighFuel tank locationSide (Single)Hour meterDigital with pre-programmed service intervalsEngine lubrication typeFull PressureCup holderYesOil capacity1.42 litreDimensionsDigital with pre-programmed service intervalsOil filterYesTyre size, front11x6-5"Drive systemTyre size, front11x6-5"11x6-5"Transmission typeHydrostaticWheelbase1111en / 4375"Transmission modelEZTBase machine, length1905cm / 75"Transmission modelEZTBase machine, width (chute down)1518cm / 598"Pung displacement10 cm³Base machine, height1016cm / 40"Speed roverse, min-max0 - 10.46 km/hWeight26.98.9 kgCutting deck typeFabricated, ClearCut"Productivity2.5 acres/hrCutting deck typeSide discharge/Collect/Mulch52.5 59-01CollectorCutting deck materialS15 mm / 10 gauge52.5 59-01CollectorCutting deck typeSide discharge/Collect/Mulch52.5 59-01Battery ChargerCutting deck typeSide discharge/Collect/Mulch52.5 59-01B	Gross horsepower	23 hp	Deck wash port	Yes
Engine coolingAirSeat typeDeluxe SK 15° with Arm restsGeneratorTBASeat materialVinylAir filter typePaper ElementSeat springYesFuel typePetrolSeat back heightHighFuel typePetrolSeat back heightHighFuel tank volume13.25 litreFuel level windowYesFuel tank volumeSide (Single)Hour meterDigital with pre-programmed service intervalsFuel tank locationSide (Single)Hour meterDigital with pre-programmed service intervalsFuel tank locationYesUit PressureCup holderYesOit capacity1.42 litreDimensionsTyre size, front11x6-5"Drive systemTyre size, front11x6-5"1905cm / 75"Transmission manufacturerHydro-GearBase machine, length1905cm / 75"Transmission modelEZTBase machine, length1905cm / 75"Punp displacement10 cm³Base machine, length1905cm / 40"Speed reverse, min-max0 - 10.46 km/hWeight269.89 kgSpeed reverse, min-max0 - 55 km/hProductivity25 acres/hrCutting deck typeFabricated, ClearCut"Fat NumberDescriptionSide discharge/Collect/MulchSi2 55 97-01CollectorSide discharge/Collect/MulchSi2 55 97-01Battery ChargerCutting deck typeGatSide discharge/So 90-01Mulch KitDesc thickness3.5 mm / 10 gaugeSide 55 97-01 </td <td>Cylinder displacement</td> <td>726 cm<sup>3</sup></td> <td>Other</td> <td></td>	Cylinder displacement	726 cm <sup>3</sup>	Other	
GeneratorTBASeat materialVinylAir filter typePaper ElementSeat springYesFuel typePetrolSeat back heightHighFuel typePetrolSeat back heightHighFuel tank volume13.25 litreFuel level windowYesFuel tank locationSide (Single)Hour meterDigital with per-programmed service intervalsEngine lubrication typeFull PressureCup holderYesOil capacity1.42 litreDimensionsDigital with per-programmed service intervalsOil capacity1.42 litreDimensionsDigital with per-programmed service intervalsOil capacity1.42 litreDimensionsDiffuerOil capacity1.42 litreDimensions11x6-5"Drive systemTransmission manufacturerHydro-GearBase machine, length190.5cm / 75"Transmission modelEZTBase machine, width (chute oun)151.8cm / 59.8"Pump displacement10 cm³Base machine, height1010.5cm / 40"Speed forward, min-max0 - 10.46 km/hWeight269.89 kgSpeed reverse, min-max0 - 56 km/hProductivity2.5 acres/hrCutting deck3-in-1 capable Side discharge/Collect/Mulch582 55 97-01CollectorSteel35 mm / 10 gauge579 45 21-01Battery ChargerDeck thickness35 mm / 10 gauge579 45 21-01Battery ChargerDeck thickness35 mm / 10 gauge579 45 21-01Battery Charger <td< td=""><td>Cylinders</td><td>2</td><td>ROPS</td><td>N/A</td></td<>	Cylinders	2	ROPS	N/A
Air filter typePaper ElementSeat springYesFuel typePetrolSeat back heightHighFuel tank volume13.25 litreFuel level windowYesFuel tank locationSide (Single)Hour meterDigital with pre-programmed service intervalsEngine lubrication typeFull PressureCup holderYesOil capacity1.42 litreDimensionsOil filterYesTyre size, front11x6-5"Drive systemTyre size, front11x6-5"Transmission typeHydrostactWheelbase111cm / 43.75"Transmission modelEZTBase machine, length190.5cm / 75"Transmission modelEZTBase machine, width (chute down)151.8cm / 59.8"Pump displacement10 cm³Base machine, width (chute up)123.2cm / 48.5"Speed forward, min-max0 - 10.46 km/hWeight269.89 kgSpeed forward, min-max0 - 5.6 km/hProductivity25 acres/hrCutting deckSide discharge/Collect/Mulch582 55 97-01Mulch KitCutting deck typeFabricated, ClearCut"579 45 01-02Battery ChargerCutting height, min-max38 - 102 mm / 15 - 4"579 45 21-01Battery ChargerBlade- tip speed (ft/min)18500AccessorSide discharge/Collect/MulchBlades3Blades3BladesLoading RampsBlades3Steel2Nos erollerLoading RampsSteel505 69 90-43Loading Ramps <td>Engine cooling</td> <td>Air</td> <td>Seat type</td> <td>Deluxe SK 15" with Arm rests</td>	Engine cooling	Air	Seat type	Deluxe SK 15" with Arm rests
Fuel typePetrolSeat back heightHighFuel tank volume13.25 litreFuel level windowYesFuel tank locationSide (Single)Hour meterDigital with pre-programmed service intervalsEngine lubrication typeFull PressureCup holderYesOil capacity1.4.2 litreDimensions11x6-5"Oil systemTyre size, front11x6-5"11x6-5"Transmission typeHydrostaticWheelbase1111cm / 43.75"Transmission manufacturerHydro-GearBase machine, length190.5cm / 75"Transmission modelEZTBase machine, width (chute down)1518cm / 59.8"Pump displacement10 cm³Base machine, width (chute down)1518cm / 49.3"Speed forward, min-max0 - 10.46 km/hWeight269.89 kgSpeed roward, min-max0 - 10.46 km/hWeight25.98 lgCutting deck3-in-1 capable582 55 97-01CollectorCutting deck typeFabricated, ClearCut"582 55 97-01Mulch KitCutting deck typeSide discharge/Collect/Mulch582 55 99-01Mulch KitCutting height, min-max38 - 102 mm / 15 - 4"579 45 21-01Battery Status IndicatorCutting height, min-max38 - 102 mm / 15 - 4"579 45 21-01Battery Status IndicatorCutting height, min-max38 - 102 mm / 18500Anti scalp wheels3Blade- tip speed (tr/min)Roder tip speed (tr/min)185003Side discharge505 69 90-43Loading Ramps	Generator	TBA	Seat material	Vinyl
Fuel tank volume13.25 litreFuel level windowYesFuel tank locationSide (Single)Hour meterDigital with pre-programmed service intervalsEngine lubrication typeFull PressureCup holderYesOil capacity1.42 litreDimensionsOil filterYesTyre size, front11x6-5"Drive systemTyre size, front11x6-5"Transmission typeHydro-GearBase machine, length190.5cm / 75"Transmission modelEZTBase machine, width (chute down)151.8cm / 59.8"Pump displacement10 cm3Base machine, width (chute up)123.2cm / 48.5"Panc-coled pumpsYesBase machine, height101.6cm / 40"Speed forward, min-max0 - 10.46 km/hWeight269.89 kgSpeed reverse, min-max0 - 5.6 km/hProductivity2.5 acres/hrCutting deck typeFabricated, ClearCut"582 55 97-01CollectorCutting deck type3.5 mm / 10 gauge579 45 01-02Battery ChargerCutting height, min-max38 - 102 mm / 15 - 4"579 45 21-01Battery ChargerCutting height, theight steps6505 69 90-43Loading RampsBlade- ins paed (fi/min)18500Action Side Side Sisted3.3Blade- ins paed (fi/min)18500Action Side SistedAction Side Sisted SistedBlade- ins paed (fi/min)YesYesYes	Air filter type	Paper Element	Seat spring	Yes
Fuel tank locationSide (Single)Hour meterDigital with pre-programmed service intervalsEngine lubrication typeFull PressureCup holderYesOil capacity1.42 litreDimensionsOil difterYesTyre size, front11x6-5"Drive systemTyre size, rear18x.95-8"Transmission typeHydrostaticWheelbase1111cm / 43.75"Transmission manufacturerHydro-GearBase machine, length190.5cm / 75"Transmission modelEZTBase machine, width (chute down)151.8cm / 59.8"Pum displacement100 cm³Base machine, width (chute up)123.2cm / 48.5"Speed forward, min-max0 - 10.46 km/hWeight269.89 kgSpeed roward, min-max0 - 56 km/hProductivity2.5 acres/hrCutting deckSide discharge/Collect/Mulch582 55 97-01CollectorCutting deck typeFabricated, ClearCut"Part NumberDescriptionCutting deck materialSteel582 55 97-01CollectorCutting height, min-max38 - 102 mm / 15 - 4"579 45 01-02Battery ChargerCutting height, min-max38 - 102 mm / 15 - 4"579 45 21-01Battery Status IndicatorDick thickness33Blade- tip speed (ft/min)18500Anti scalp wheels23Nose rollerVersNose rollerYesYesNose roller	Fuel type	Petrol	Seat back height	High
Puer Latik locationSide (Single)Hour meterPour meterService intervalsEngine lubrication typeFull PressureCup holderYesOil capacity1.42 litreDimensionsOil filterYesTyre size, front11x6-5"Drive systemTyre size, rear18x.95-8"Transmission typeHydrostaticWheelbase1111.cm / 43.75"Transmission manufacturerHydro-GearBase machine, length190.5cm / 75"Transmission modelEZTBase machine, width (chute down)151.8cm / 59.8"Pump displacement10 cm³Base machine, width (chute up)123.2cm / 48.5"Fan-cooled pumpsYesBase machine, height101.6cm / 40"Speed forward, min-max0 - 10.46 km/hWeight269.89 kgSpeed reverse, min-max0 - 56 km/hProductivity2.5 acres/hrCutting deckTabricated, ClearCut"ACCESSORIESCutting deck typeFabricated, ClearCut"582 55 97-01CollectorCutting deck materialSteel582 55 99-01Mulch KitDeck thickness3.5 mm / 10 gauge579 45 01-02Battery ChargerCutting height, min-max38 - 102 mm / 15 - 4"550 69 90-43Loading RampsBlade engagementElectric clutchBlades3Blade - tip speed (ft/min)18500Acting RampsNose rollerYesYesActing Ramps	Fuel tank volume	13.25 litre	Fuel level window	Yes
Oil capacity1.42 litreDimensionsOil filterYesTyre size, front11x6-5"Drive systemTyre size, rear18x9.5-8"Transmission typeHydrostaticWheelbase1111cm / 43.75"Transmission manufacturerHydro-GearBase machine, length190.5cm / 75"Transmission modelEZTBase machine, width (chute down)151.8cm / 59.8"Pump displacement10 cm³Base machine, width (chute up)123.2cm / 48.5"Fan-cooled pumpsYesBase machine, width (chute up)123.2cm / 48.5"Speed forward, min-max0 - 10.46 km/hWeight269.89 kgSpeed reverse, min-max0 - 5.6 km/hProductivity25 acres/hrCutting deckSide discharge/Collect/Mulch582.55 97-01CollectorCutting methods3.5 mm / 10 gauge579 45 01-02Battery ChargerCutting deck materialSteel582 55 99-01Mulch KitDeck thickness3.5 mm / 10 gauge579 45 21-01Battery ChargerCutting height, min-max38 - 102 mm / 15 - 4"505 69 90-43Loading RampsBlade engagementElectric clutchBattery Status IndicatorBlades33Sof 59 90-43Loading RampsBlade sign page7505 69 90-43Loading RampsNose rollerYesYesSof 59 90-43Loading Ramps	Fuel tank location	Side (Single)	Hour meter	Digital with pre-programmed service intervals
Oli filterYesTyre size, front11x6-5"Drive systemTyre size, rear18x9.5-8"Transmission typeHydrostaticWheelbase1111cm / 43.75"Transmission manufacturerHydro-GearBase machine, length190.5cm / 75"Transmission modelEZTBase machine, width (chute down)151.8cm / 59.8"Pump displacement10 cm³Base machine, width (chute dup)123.2cm / 48.5"Fan-cooled pumpsYesBase machine, height101.6cm / 40"Speed forward, min-max0 - 10.46 km/hWeight269.89 kgSpeed reverse, min-max0 - 5.6 km/hProductivity2.5 acres/hrCutting deckProductivity2.5 acres/hr269.89 kgCutting deck typeFabricated, ClearCut*Part NumberDescriptionSide discharge/Collect/Mulch582 55 97-01CollectorSutting height, min-max38 - 102 mm / 15 - 4*579 45 01-02Battery ChargerCutting height, min-max38 - 102 mm / 15 - 4*579 45 01-02Battery ChargerCutting height steps6505 69 90-43Loading RampsBlade engagementElectric clutchSof 69 90-43Loading RampsBlade-tip speed (ft/min)18500Arti scalp wheels2Nose rollerYesYesYes	Engine lubrication type	Full Pressure	Cup holder	Yes
Drive systemTyre size, rear18x95-8"Transmission typeHydrostaticWheelbase1111cm / 43.75"Transmission manufacturerHydro-GearBase machine, length190.5cm / 75"Transmission modelEZTBase machine, width (chute down)151.8cm / 59.8"Pump displacement10 cm³Base machine, width (chute up)123.2cm / 48.5"Fan-cooled pumpsYesBase machine, height101.6cm / 40"Speed forward, min-max0 - 10.46 km/hWeight269.89 kgSpeed reverse, min-max0 - 5.6 km/hProductivity2.5 acres/hrCutting deckProductivity2.5 acres/hrCutting deck typeFabricated, ClearCut"Productivity2.5 acres/hrCutting deck typeSide discharge/Collect/Mulch582 55 97-01CollectorSide discharge/Collect/MulchSteel582 55 99-01Mulch KitDeck thickness3.5 mm / 10 gauge579 45 01-02Battery ChargerCutting height, min-max38 - 102 mm / 15 - 4"505 69 90-43Loading RampsBlade engagementElectric clutch505 69 90-43Loading RampsBlades33SteelSteelSide discharge2SteelSteelSide discharge3SteelSteelSide discharge6Ste 90-43Loading RampsSide discharge3SteelSte 90-43Side discharge3Ste 90-43Loading RampsBlade - tip speed (ft/min)18500Ste 90-43 <t< td=""><td>Oil capacity</td><td>1.42 litre</td><td>Dimensions</td><td></td></t<>	Oil capacity	1.42 litre	Dimensions	
Transmission typeHydrostaticWheelbase1111cm / 43.75"Transmission manufacturerHydro-GearBase machine, length190.5cm / 75"Transmission modelEZTBase machine, width (chute down)151.8cm / 59.8"Pump displacement10 cm³Base machine, width (chute up)123.2cm / 48.5"Fan-cooled pumpsYesBase machine, height101.6cm / 40"Speed forward, min-max0 - 10.46 km/hWeight269.89 kgSpeed reverse, min-max0 - 5.6 km/hProductivity2.5 acres/hrCutting deckYesProductivity2.5 acres/hrCutting width121.92 cm / 48"ACCESSORIESCutting deck typeFabricated, ClearCut"Part NumberDescriptionSide discharge/Collect/Mulch582 55 97-01CollectorCutting height, min-max38 - 102 mm / 15 - 4"579 45 01-02Battery ChargerCutting height, min-max38 - 102 mm / 15 - 4"579 45 21-01Battery Status IndicatorCutting height steps6505 69 90-43Loading RampsBlade engagementElectric clutchBlades3Blades33Status IndicatorSubarder ip speed (ft/min)18500Status IndicatorAnti scalp wheels2Yes	Oil filter	Yes	Tyre size, front	11x6-5"
Transmission manufacturerHydro-GearBase machine, length190.5cm / 75"Transmission modelEZTBase machine, width (chute down)151.8cm / 59.8"Pump displacement10 cm³Base machine, width (chute up)123.2cm / 48.5"Fan-cooled pumpsYesBase machine, height101.6cm / 40"Speed forward, min-max0 - 10.46 km/hWeight269.89 kgSpeed reverse, min-max0 - 5.6 km/hProductivity2.5 acres/hrCutting deck0 - 5.6 km/hProductivity2.5 acres/hrCutting deck typeFabricated, ClearCut"Productivity2.5 acres/hrCutting deck typeFabricated, ClearCut"StellS82 55 97-01CollectorSude discharge/Collect/Mulch582 55 97-01CollectorS82 55 99-01Mulch KitDeck thickness3.5 mm / 10 gauge579 45 01-02Battery ChargerCutting height, min-max38 - 102 mm / 1.5 - 4"579 45 21-01Battery Status IndicatorCutting height steps6505 69 90-43Loading RampsBlade engagementElectric clutchStatus and classerStatus and classerBlades33Status and classerStatus and classerBlade-tip speed (ft/min)18500Arti scalp wheels2Nose rollerYesYesStatus and classer	Drive system		Tyre size, rear	18x9.5-8"
Transmission modelEZTBase machine, width (chute down)151.8cm / 59.8"Pump displacement10 cm³Base machine, width (chute up)123.2cm / 48.5"Fan-cooled pumpsYesBase machine, width (chute up)123.2cm / 48.5"Speed forward, min-max0 - 10.46 km/hWeight269.89 kgSpeed reverse, min-max0 - 5.6 km/hProductivity25 acres/hrCutting deckProductivity2.5 acres/hrCutting deck typeFabricated, ClearCut"Productivity2.5 acres/hrCutting deck typeSide discharge/Collect/Mulch582 55 97-01CollectorSide discharge/Collect/Mulch582 55 99-01Mulch KitDeck thickness3.5 mm / 10 gauge579 45 01-02Battery ChargerCutting height, min-max38 - 102 mm / 1.5 - 4"579 45 21-01Battery Status IndicatorBlade engagementElectric clutch505 69 90-43Loading RampsBlades33Side StatusStatus IndicatorSub acting speed (ft/min)18500Status IndicatorAnti scalp wheels2Yes	Transmission type	Hydrostatic	Wheelbase	111.1cm / 43.75"
Pump displacement10 cm³Base machine, width (chute up)123.2cm / 48.5"Fan-cooled pumpsYesBase machine, height101.6cm / 40"Speed forward, min-max0 - 10.46 km/hWeight269.89 kgSpeed reverse, min-max0 - 5.6 km/hProductivity2.5 acres/hrCutting deckProductivity2.5 acres/hrCutting deck typeFabricated, ClearCut"Part NumberDescriptionCutting deck materialSteel582 55 99-01CollectorCutting height, min-max3.5 mm / 10 gauge579 45 01-02Battery ChargerCutting height, min-max38 - 102 mm / 1.5 - 4"579 45 21-01Battery Status IndicatorCutting height steps6505 69 90-43Loading RampsBlades3318500Arti scalp wheels2Nose rollerYesYesYesIntervention	Transmission manufacturer	Hydro-Gear	Base machine, length	190.5cm / 75"
Fan-cooled pumpsYesBase machine, height101.6cm / 40"Speed forward, min-max0 - 10.46 km/hWeight269.89 kgSpeed reverse, min-max0 - 5.6 km/hProductivityCutting deckProductivity2.5 acres/hrCutting width121.92 cm / 48"ACCESSORIESCutting deck typeFabricated, ClearCut"Part NumberSide discharge/Collect/Mulch582 55 97-01CollectorCutting deck materialSteel582 55 99-01Mulch KitDeck thickness3.5 mm / 10 gauge579 45 01-02Battery ChargerCutting height, min-max38 - 102 mm / 1.5 - 4"579 45 21-01Battery Status IndicatorBlade engagementElectric clutch505 69 90-43Loading RampsBlades333Accession (Cluber)Status IndicatorShade engagementElectric clutch505 69 90-43Loading RampsBlades32Status IndicatorNose rollerYesYesStatus Indicator	Transmission model	EZT	Base machine, width (chute down)	151.8cm / 59.8"
Speed forward, min-max0 - 10.46 km/hWeight269.89 kgSpeed reverse, min-max0 - 5.6 km/hProductivity2.5 acres/hrCutting deckProductivity2.5 acres/hrCutting width121.92 cm / 48"ACCESSORIESCutting deck typeFabricated, ClearCut"Part NumberDescriptionCutting methods3-in-1 capable582 55 97-01CollectorCutting deck materialSteel582 55 99-01Mulch KitDeck thickness3.5 mm / 10 gauge579 45 01-02Battery ChargerCutting height, min-max38 - 102 mm / 1.5 - 4"579 45 21-01Battery Status IndicatorBlades33Blade-tip speed (ft/min)18500Sof 69 90-43Loading RampsNose rollerYesYesYesYesYes	Pump displacement	10 cm <sup>3</sup>	Base machine, width (chute up)	123.2cm / 48.5"
Speed reverse, min-max0 - 5.6 km/hProductivityCutting deckProductivity2.5 acres/hrCutting width121.92 cm / 48"ACCESSORIESCutting deck typeFabricated, ClearCut"ACCESSORIESCutting methods3-in-1 capable Side discharge/Collect/MulchPart NumberDescriptionCutting deck materialSteel582 55 97-01CollectorDeck thickness3.5 mm / 10 gauge579 45 01-02Battery ChargerCutting height, min-max38 - 102 mm / 1.5 - 4"579 45 21-01Battery Status IndicatorCutting height steps6505 69 90-43Loading RampsBlade engagementElectric clutch505 69 90-43Loading RampsBlades3318500Arti scalp wheels2Nose rollerYesYesYesYes	Fan-cooled pumps	Yes	Base machine, height	101.6cm / 40"
Cutting deckProductivity2.5 acres/hrCutting width121.92 cm / 48"ACCESSORIESCutting deck typeFabricated, ClearCut"ACCESSORIESCutting methods3-in-1 capable Side discharge/Collect/MulchPart NumberDescriptionCutting deck materialSteel582 55 97-01CollectorCutting height, min-max3.5 mm / 10 gauge579 45 01-02Battery ChargerCutting height steps6505 69 90-43Loading RampsBlade engagementElectric clutch505 69 90-43Loading RampsBlade-tip speed (ft/min)18500Anti scalp wheels2Nose rollerYesYesYes	Speed forward, min-max	0 - 10.46 km/h	Weight	269.89 kg
Cutting width121.92 cm / 48"ACCESSORIESCutting deck typeFabricated, ClearCut"Part NumberDescriptionCutting methods3-in-1 capable Side discharge/Collect/MulchSteelSte2 55 97-01CollectorCutting deck materialSteel582 55 99-01Mulch KitDeck thickness3.5 mm / 10 gauge579 45 01-02Battery ChargerCutting height, min-max38 - 102 mm / 1.5 - 4"579 45 21-01Battery Status IndicatorCutting height steps6505 69 90-43Loading RampsBlade engagementElectric clutchSto0Sto1Sto2Blades33YesSto2Sto2	Speed reverse, min-max	0 - 5.6 km/h	Productivity	
Cutting deck typeFabricated, ClearCut"ACCESSORIESCutting methods3-in-1 capable Side discharge/Collect/MulchPart NumberDescriptionCutting deck materialSteel582 55 97-01CollectorCutting deck materialSteel582 55 99-01Mulch KitDeck thickness3.5 mm / 10 gauge579 45 01-02Battery ChargerCutting height, min-max38 - 102 mm / 1.5 - 4"579 45 21-01Battery Status IndicatorCutting height steps6505 69 90-43Loading RampsBlade engagementElectric clutch505 69 90-43Loading RampsBlades3318500Yes	Cutting deck		Productivity	2.5 acres/hr
Cutting deck typeFabricated, ClearCutCutting methods3-in-1 capable Side discharge/Collect/MulchPart NumberDescriptionCutting deck materialSteel582 55 99-01CollectorDeck thickness3.5 mm / 10 gauge579 45 01-02Battery ChargerCutting height, min-max38 - 102 mm / 1.5 - 4"579 45 21-01Battery Status IndicatorCutting height steps6505 69 90-43Loading RampsBlade engagementElectric clutch505 69 90-43Loading RampsBlades3318500Yes	Cutting width	121.92 cm / 48"		
Cutting methodsSide discharge/Collect/Mulch582 55 97-01CollectorCutting deck materialSteel582 55 99-01Mulch KitDeck thickness3.5 mm / 10 gauge579 45 01-02Battery ChargerCutting height, min-max38 - 102 mm / 1.5 - 4"579 45 21-01Battery Status IndicatorCutting height steps6505 69 90-43Loading RampsBlade engagementElectric clutch505 69 90-43Loading RampsBlades3318500Yes	Cutting deck type	Fabricated, ClearCut <sup>™</sup>	ACCES	
Deck thickness3.5 mm / 10 gauge579 45 01-02Battery ChargerCutting height, min-max38 - 102 mm / 1.5 - 4"579 45 21-01Battery Status IndicatorCutting height steps6505 69 90-43Loading RampsBlade engagementElectric clutch505 69 90-43Loading RampsBlades3318500Anti scalp wheels2Nose rollerYesYesYesYes	Cutting methods			
Cutting height, min-max38 - 102 mm / 1.5 - 4"579 45 21-01Battery Status IndicatorCutting height steps6505 69 90-43Loading RampsBlade engagementElectric clutchBlades3Blade-tip speed (ft/min)18500Anti scalp wheels2Nose rollerYes	Cutting deck material	Steel	582 55 99-01	Mulch Kit
Cutting height, min-max38 - 102 mm / 1.5 - 4"579 45 21-01Battery Status IndicatorCutting height steps6505 69 90-43Loading RampsBlade engagementElectric clutchBlades3Blade-tip speed (ft/min)18500Anti scalp wheels2Nose rollerYes	Deck thickness	3.5 mm / 10 gauge	579 45 01-02	Battery Charger
Cutting height steps6505 69 90-43Loading RampsBlade engagementElectric clutchBlades3Blade-tip speed (ft/min)18500Anti scalp wheels2Nose rollerYes	Cutting height, min-max			
Blade engagement Electric clutch   Blades 3   Blade-tip speed (ft/min) 18500   Anti scalp wheels 2   Nose roller Yes	Cutting height steps	6		
Blade-tip speed (ft/min)18500Anti scalp wheels2Nose rollerYes	Blade engagement	Electric clutch		
Anti scalp wheels2Nose rollerYes	Blades	3		
Anti scalp wheels2Nose rollerYes	Blade-tip speed (ft/min)	18500		
Nose roller Yes	Anti scalp wheels	2		
	Nose roller	Yes		
	Deck lifting system			

For parts information relating to this product please refer to Husqvarna parts manual or EPC online. All images are for illustrational purposes only.

Husqvarna is a registered trademark. Copyright © 2020 HUSQVARNA. All rights reserved.

HUSQVARNA AUSTRALIA PTY LTD ABN 45 115 475 619 POSTAL ADDRESS Locked Bag 5, Central Coast BC, NSW 2252 AUSTRALIA

# www.husqvarna.com