Z254F Product no: 970 45 90-01





Performance and style hit the grass running with the all new Z200 Series Zero Turn Mowers. Cutting edge design, proven performance and new innovative features combine to make lawn maintenance an event instead of a chore. Packed with features including high performance Clear Cut[™] fabricated cutting deck, Removable foot plate, Rear engine guard and Anti-slip foot area.

Zero-turn steering system

Individual, hydraulic wheel-drive provides very precise manoeuvring and allows the mower to rotate around its own axle, without any turning radius.



Maintenance-Free Transmission

Worry free performance with maintenance free, integrated zero-turn transmissions.

Ergonomic control panel The ergonomic control panel places everything conveniently at your fingertips.

Convenient deck lift

The deck lift system is spring assisted for ease of use and conveniently located within easy reach of the operator.











Automatic park brake

Kawasaki V-Twin engine

and quiet.

ClearCut[™] Deck

mulching.

chassis flex.

ClearCut[™] deck technology

features deep deck design,

air flow control baffles, high

Rugged frame and castors

The robust frame and castors ensure durability and reduced

performance blades and top discharge for superior cutting performance whether discharging, bagging or

Fully pressure-lubricated, two-

cylinder Kawasaki engine with

oil pump and oil filter. Powerful

The new park brake system (patent pending) automatically activates or deactivates as the steering levers are moved outward or inward, freeing the user of the task.









www.husqvarna.com

Z254F Product no: 970 45 90-01



	TECHNICAL SI	PECIFICATIONS	
Engine		Cutting deck - Continued	
Engine manufacturer	Kawasaki	Powder-coated cutting deck	Yes
Engine type	FR Series V-Twin	Spindle/mandrel type	Cast Iron
Engine model	FR730V-CS13	Greasable mandrels	Yes
Gross horsepower	24 hp	Deck wash port	Yes
Cylinder displacement	726 cm ³	Other	
Cylinders	2	ROPS	N/A
Engine cooling	Air	LED Headlights	Yes
Generator	15A	Seat type	Deluxe SKI 15" with Armrest
Air filter type	Paper Element	Seat material	Vinyl
Fuel type	Petrol	Seat spring	Yes
Fuel tank volume	13.25 litre	Seat back height	High
Fuel tank location	Side (Single)	Fuel level window	Yes
Engine lubrication type	Full Pressure	Hour meter	Digital with pre-programmed service intervals
Oil capacity	2.1 litre	Cup holder	Yes
Oil filter	Yes	Dimensions	
Drive system		Tyre size, front	11x6-5"
Transmission type	Hydrostatic	Tyre size, rear	18x9.5-8"
Transmission manufacturer	Hydro-Gear	Wheelbase	112cm / 44"
Transmission model	EZT	Base machine, length	191cm / 75"
Pump displacement	10 cm ³	Base machine, width (chute down)	172cm / 67.5"
Fan-cooled pumps	Yes	Base machine, width (chute up)	145cm / 57"
Speed forward, min-max	0 - 10.46 km/h	Base machine, height	102cm / 40"
Speed reverse, min-max	0 - 5.6 km/h	Weight	290 kg
Cutting deck		Productivity	
Cutting width	121.92 cm / 54"	Productivity	2.8 acres/hr
Cutting deck type	Fabricated, ClearCut [™]	ACCESSORIES	
Cutting methods	3-in-1 capable Side discharge/Collect/Mulch	Part Number	Description
Cutting deck material	Steel	591 11 14-01	Collector
Deck thickness	3.5 mm / 10 gauge	591 10 21-01	Mulch Kit
Cutting height, min-max	38 - 102 mm / 1.5 - 4"	579 45 01-02	Battery Charger
Cutting height steps	6	579 45 21-01	Battery Status Indicator
Blade engagement	Electric clutch	505 69 90-43	Loading Ramps
Blades	3		
Blade-tip speed (ft/min)	18500		
Anti scalp wheels	4		
Nose roller	Yes		
Deck lifting system	Manual, hand operated		

For parts information relating to this product please refer to Husqvarna parts manual or EPC online. All images are for illustrational purposes only.

Husqvarna is a registered trademark. Copyright © 2020 HUSQVARNA. All rights reserved.

HUSQVARNA AUSTRALIA PTY LTD ABN 45 115 475 619 POSTAL ADDRESS Locked Bag 5, Central Coast BC, NSW 2252 AUSTRALIA

www.husqvarna.com