



ISEKI

TM Range Compact Tractors All torque. All Action.

22 & 26hp

ISEKI TM RANGE TRACTORS

The ultimate compact tractor, that was the goal at Iseki when we set out to redesign the TM Series. You'll feel the difference right from the moment you get behind the wheel.

Everything is in its right place – the controls have been moved up onto the fenders for easier access, so there is no more reaching for levers and controls. The Independent PTO button is smartly positioned in front of the operator and now features a two-speed modulation button for slower engagement, further adding to operator convenience.

The repositioning for the controls has allowed for a bigger and improved spring suspension seat and combined with the Iso-mounted platform provides an even smoother and comfortable ride.

The new range now also features the 26hp TM3267 model providing the option of extra power if required.

Iseki's TM Series, feel the difference today!




FEATURES



ENGINE

- Powerful Iseki 3 cylinder water-cooled engines.
- Quiet and efficient.
- Large displacement offers full power at low engine RPM.
- Removable side panels allow easy access to the engine, making service and regular maintenance easier.



HYDROSTATIC TRANSMISSION

- Three range hydrostatic transmission give you more options and more working ranges.
- Easy to use side by side forward and reverse pedals make directional changes smooth.
- 4 wheel drive and differential lock for exceptional traction in all conditions.



INDEPENDENT PTO

- Independent 540 rear PTO and 2000 mid PTO for quick and easy operation by the flick of a switch.
- The PTO can be engaged or disengaged at any time even on the move.
- A Two speed modulation control button for slower PTO engagement.


THE ISEKI DIFFERENCE

When you choose Iseki, you're choosing a brand backed by decades of industry-leading engineering and manufacturing experience, specialising in the production of high quality machinery tailored for today's demanding applications.

Combining its Japanese heritage and over 30 years in our market, Iseki continues to deliver quality products and services that work tirelessly for your farming needs.

Your local Iseki dealer has expertise like no other and will be able to guide you through the entire Iseki range to find the right tractor or mower for your requirements. Flexible finance options are available to assist you in getting your Iseki tractor out on the field when you need it.

Iseki customers can always be assured that they will be supported with excellent service support and genuine parts - that is why we call it the Iseki Difference.



OPERATORS PLATFORM

- Large operator's platform sit on rubber mounts isolating the operator from the chassis reducing vibration and operator fatigue.
- Operator controls are mounted on both fenders putting the operator in control of the tractor and the implements.
- A large spring suspension seat with adjustable armrests is standard with an increased capacity of 130kg with adjustability to suit each operator.



HYDRAULICS & LINKAGE

- 2 rear double acting auxiliary remotes are standard on the TM series. Controls are located conveniently on the right hand fender.
- With two hydraulic pumps and up to a max 33 l/min flow you fill in control and loader work becomes a breeze.
- Large three point linkage capacity of 600kg @ ball ends.
- Clevis drawbar



OPTIONS

- Ag and turf tyres option are available.
- Standard with a mid PTO a 60" mid mount mower deck is easily fitted.
- 7 stage height adjustment from 25-115mm and a hydraulic deck lift when not in use.
- Robust front and rear axles, great for front end loaders.

ISEKI TM Series SPECIFICATIONS



TM 3200 R.O.P.S

Model	TM3247	TM3267
Drive	4WD	4WD
Engine Specification		
Engine	E3112	E3CD
Number Cylinders/cc	3/1123	3/1498
Engine Power kW/hp	16.8/22.5	18.9/25.3
@ Rated speed	2600	2600
Speed control	HST 3-range & cruise control	
PTO		
PTO kW/hp	13.7/18.4	15.9/21.3
Type	Independent	
Speeds Rear/Mid	540/2000	
Transmission		
Type	Hydrostatic	
Speeds Fwd/Rev	3 / 3	
Speed Range	F: 0-24.4 R:0-15.2	

Model	TM3247	TM3267
Hydraulic System		
Description	Open centre	
Pump Type	Gear	
Max l/min	33	
Remote outlets Std/max	2/2	
3 Point Linkage		
Type	Cat 1	
Control	Position	
Lift – kg @ BE	600	
Brakes and Steering		
Brake type	Wet disc	
Steering type	Hydrostatic	

Model	TM3247	TM3267
Tyre Equipment		
Standard Front (AG)	6.0-12	
Standard Rear (AG)	9.5-18	
Standard Front (TURF)	24x8.5-12	
Standard Rear (TURF)	315/75R15	
Dimension/Weights		
Minimum Width	1110	
Height	2380	
Wheelbase	1560	
Dry Shipping Weight	830	860
Capacities		
Fuel	28	

Specifications, standard and optional equipment on products change from time to time. Please consult your local dealer to ensure your expectations are matched by the product which will be available locally at the time you take delivery.



www.iseki.com.au