

SLF530



SUPER-LIGHTWEIGHT REEL MOWER WITH UNMATCHED CONTOUR FOLLOWING.

Introducing the SLF530, a highly manoeuvrable mower delivering unrivalled quality of cut with a superb power to weight ratio. Designed with versatility and application flexibility in mind, the SLF530 is packed full of standard features, including a high-res full colour screen, which puts advanced on-board diagnostics at your fingertips. With Jacobssen's renowned quality-of-cut the SLF530 is the perfect choice for golf and sports stadiums where appearance is paramount.

GROUND PRESSURE
OPTIMISED
FOR PERFORMANCE

3 OR 4
WHEEL DRIVE

COLOUR LCD
SCREEN
OPERATOR INTERFACE

2.0 M
WIDTH OF CUT



SLF530

JACOBSEN® ADVANTAGE

For over 95 years Jacobsen has been renowned for industry-leading turf maintenance equipment. A strong focus on engineering innovative technology has led to advancements that deliver impeccable quality of cut on user-friendly equipment.



CLASSIC XP REELS



LCD CONTROL SCREEN



EQUIPPED AS STANDARD

- Maintenance-free, wet parking brakes
- Advanced on-board diagnostics
- 4in. high visibility full colour LCD control screen
- Biodegradable hydraulic fluids
- Ergonomic operator area
- Adjustable transport speeds
- Adjustable mow speeds
- Backlap capable
- Tilt steering wheel
- Easy access hood
- Fully adjustable armrest
- Patented dual-pivot arm lifting system
- Slick tyres
- Expandable mesh storage net

OPTIONS

- Treaded tyres
- Full selection of Classic XP Reel configurations
- Choose either 3WD or 4WD to best suit your application.

ENGINE		
TYPE	Kubota® D1105 liquid cooled, diesel	
RATED HORSEPOWER* (GROSS)	18.5kW (24.8HP) @ 3000 rpm	
EMISSION LEVEL	EU Stage IIIB - (EPA Tier 4 Final)	
COOLING SYSTEM	Side-by-side radiator/hydraulic oil cooler; pressurised	
FUEL CAPACITY	29 litre (6.4 gallon)	
ELECTRICAL SYSTEM	12-volt, input/output controller. 60 amp alternator. Overload protection with automotive type fuses	
TRACTION & DRIVE		
	3WD	4WD
TRACTION SYSTEM	Parallel series 3-wheel drive, 2-wheel drive in reverse	Pure Parallel 4-wheel system with selectable 2 or 4-wheel drive and automatic 2-wheel drive in reverse
CUTTING UNIT DRIVE	Fixed displacement hydraulic motors	
HYDRAULIC SYSTEM	10 micron remote charge filtration, suction screen at tank, oil cooler, side by side radiator	
HYDRAULIC COOLING	Side-by-side pressurised hydraulic oil cooler	
SPEED (MAXIMUM)		
MOWING	10 km/h	
TRANSPORT	14 km/h	
REVERSE	6 km/h	
TYRES, BRAKES & STEERING		
FRONT TYRES	55.8 cm tubeless	
REAR TYRES	50.8 cm tubeless	
SERVICE BRAKE	Hydrostatic braking	
PARKING BRAKE	Wet parking brakes integrated into wheel motors	
STEERING	Hydrostatic powered equal displacement cylinder to rear wheels	
CUTTING UNITS		
NUMBER & TYPE	Five 12.7 cm diameter x 45.7 cm	
NUMBER OF BLADES	8 and 11 blades	
CUTTING FREQUENCY	8 Blade: 1.03 mm/km/h 11 Blade: 0.77 mm/km/h	
OVERALL CUTTING WIDTH	2.08 m	
HEIGHT-OF-CUT**	7.62 - 177.78 mm. Available high-cut kit raises cutting height to 23.8 mm using low profile, heavy bedknife	
WEIGHT & DIMENSIONS		
	3WD	4WD
WORKING WEIGHT	887.2 kg	931.2 kg
LENGTH	2.59 m	
HEIGHT	2.08 m including ROPS	
TRANSPORT WIDTH	2.49 m	
WIDTH-OF-CUT	2.08 m	

* Engine power is provided by engine manufacturer. Actual operating power output may vary due to conditions of specific use. "Kubota" is either a registered trademark or trademark of Kubota Tractor Corporation in the United States and/or other countries.

** Height-of-cut depends on turf condition, reel wear and bedknife installed.

NOTE: Specifications, while correct at time of printing, may change without notice.