

BERENDS

Slashers



TWIN ROTOR SLASHERS

"Heavy duty slashers designed for tough conditions - available in trailing or three point linkage models."

- Available in 8', 10' and 12' in three-point linkage models, or 10' and 12' in the trailing models.
- Trailing models fitted with 14" Light truck tyres and three point linkage models fitted with solid rubber tyres. Puncture proofing is available.
- Twin rotors fitted to two 75HP and gearboxes and connected by an extra heavy 110HP centre gearbox. Two-plate slip clutch between each gearbox provides gearbox protection.
- Contra rotating rotors form a flat windrow behind the centre of the slasher, however, two small windrows can be created by reversing the direction of the rotors.
- Front and rear chains can be fitted on request.
- Full 12 month warranty against faulty materials or workmanship.

Specifications

	8'	10'	12'
Cutting width	2.3m	2.9m	3.50m
Weight (linkage)	620kg	875kg	975kg
Weight (trailing)	N/A	825kg	925kg
Width (Overall)	2.52m	3.12m	3.72m
Body construction	5mm top, 6mm sides	5mm top, 6mm sides	5mm top, 6mm sides
Tractor HP range	50 HP+	60 HP+	70 HP+
PYO	Series 7 shaft	Series 7 shaft	Series 7 shaft
Gearbox/PTO speed	540rpm	540rpm	540rpm
Centre Gearbox	110HP	110HP	110HP
End Gearboxes	75HP	75HP	75HP
Gearboxes Protection	2 plate slip clutch	2 plate slip clutch	2 plate slip clutch



Manufactured in Australia by

John Berends Implements Pty Ltd

Manufacturers of Agricultural Machinery

130 Frankston-Dandenong Rd, Dandenong South 3175 Victoria Australia

Phone: 03 9791 2494 Fax: 03 9794 5568

Email: berends@johnberendsimplements.com.au Website: www.johnberendsimplements.com.au

ABN 79007035369

* Due to our policy of continuous improvement, machines may differ from those illustrated. We reserve the right to change design and/or specifications without prior notice or obligation.