



CK3710 SERIES

ROPS



THE TRACTOR YOU NEED TO EXPERIENCE FOR YOURSELF.

The Kioti CK3710 HST ROPS tractor is a versatile and powerful machine designed to meet the demands of modern farming and property management.

Equipped with a 37-horsepower diesel engine, this tractor delivers reliable performance and fuel efficiency for a variety of tasks, from mowing and tilling to hauling and landscaping.

The hydrostatic transmission (HST) provides seamless and intuitive speed control, making operation smooth and effortless, especially for users who prefer ease of use over manual shifting.



CK3710 ROPS
37HP



@kiotiaustralia



@kiotitractorsaustralia



kioti.com.au



CK3710 HST COMPACT ROPS

ENGINE

- Daedong 3B183LWM-E
- Liquid Cooled 3 Cylinder Diesel
- 1826cc Displacement
- 37 HP @ 2600 rpm
- 34 Litre Fuel Tank Capacity

TRANSMISSION

- 3 Range Hydrostatic Drive
- Cruise Control HST Models
- 4 Wheel Drive
- Rear Differential Lock
- Link Pedal System

HYDRAULICS & LINKAGE

- Manual Linkage Control
- 44.4 l/min Total Flow
- Category 1 Three Point Linkage
- Draw Bar
- 4 Hydraulic Remotes (2 Rear, 2 Front w/ Joystick)
- 740kg Max Rear Lift Capacity 600mm Behind Lift

POWER TAKE OFF

- 540 rpm Rear PTO Speed

BRAKES

- Independent Oil Immersed Disc Brakes
- Cast Iron Transmission and Axle Housing

OPERATOR ENVIRONMENT

- Front Work Lights with Indicators/Brake Lights
- Step Through Platform
- Under Bonnet Muffler
- Comfort Seat
- Tool Box

TRAVEL SPEEDS

- Infinite Speeds from 0-25 km/h F/R

DIMENSIONS

Overall Length
3070mm

Overall Height
2650mm

Overall Width
1400mm

Wheelbase
1670mm

Ground Clearance
340mm

Weight
1240kg

TYRES
Industrial Front
25 / 8.5 x 14

Industrial Rear
15/19.5

Turf Front
27 x 8.5-15

Turf Rear
41 x 14.00-12.4

OPTIONAL EQUIPMENT



BACKHOE



SLASHER

*Note: The specifications are subject to change for the purpose of improvement without any notice. Images for illustration purposes only.

DEALER DETAILS



SCAN TO
LEARN MORE



CK4210 SERIES

ROPS



WORK SMARTER NOT HARDER.

The Kioti CK4210 Series includes two versatile models: the CK4210 Manual ROPS and the CK4210 HST ROPS tractors, each designed to cater to different operator preferences and farming requirements.

Both models are powered by a robust 42-horsepower diesel engine, providing reliable performance and fuel efficiency for a wide range of agricultural tasks. The Manual ROPS version features a traditional gear-driven transmission, offering precise control and flexibility for experienced operators who prefer manual shifting.

On the other hand, the CK4210 HST ROPS model is equipped with a hydrostatic transmission, allowing for seamless and effortless speed adjustments, making it ideal for users seeking ease of operation.



CK4210 MANUAL ROPS
42HP



CK4210 HST ROPS
42HP



@kiotiaustralia



@kiotitractorsaustralia



kioti.com.au



CK4210M/HST COMPACT ROPS

ENGINE

- Daedong 3B183LWM-E
- Liquid Cooled 3 Cylinder Diesel
- 1826cc Displacement
- 42 HP @ 2600 rpm
- 34 Litre Fuel Tank Capacity

TRANSMISSION

- 9x3 Synchro Shuttle or 3 Range Hydrostatic Drive
- Cruise Control HST Models
- 4 Wheel Drive
- Rear Differential Lock
- Link Pedal System (HST Transmission Only)

HYDRAULICS & LINKAGE

- Manual Linkage Control
- 44.4 l/min Total Flow
- Category 1 Three Point Linkage
- Draw Bar
- 4 Hydraulic Remotes (2 Rear, 2 Front w/ Joystick)
- 740kg Max Rear Lift Capacity 600mm Behind Lift

POWER TAKE OFF

- 540 rpm Rear PTO Speed

BRAKES

- Independent Oil Immersed Disc Brakes

OPERATOR ENVIRONMENT

- Front Work Lights with Indicators/ Brake Lights
- Step Through Platform
- Under Bonnet Muffler
- Comfort Seat
- Tool Box

TRAVEL SPEEDS

- Speed Range 1.52 - 23.56 km/h (Manual)
- Infinite Speeds from 0 - 25 km/h F/R (HST)

DIMENSIONS

Overall Length
3070mm

Overall Height
2650mm

Overall Width
1400mm

Wheelbase
1670mm

Ground Clearance
340mm

Weight (HST)
1240kg

Weight (Man)
1215kg

TYRES
Industrial Front
25 / 8.5 x 14

Industrial Rear
15 / 19.5

Turf Front
27 x 8.5 - 15

Turf Rear
41 x 14.00 - 12.4



OPTIONAL EQUIPMENT



BACKHOE



SLASHER

*Note: The specifications are subject to change for the purpose of improvement without any notice. Images for illustration purposes only.

DEALER DETAILS



SCAN TO
LEARN MORE



CK4220 SERIES

CAB



WORK SMARTER NOT HARDER.

Versatile and gutsy, the new generation Kioti compact CK4220 42 hp Daedong diesel engine tractor comes with either manual or hydrostatic transmission.

HST models feature performance proven, heavy duty HST drives that deliver power and efficiency. The three range transmission — high, mid, low — along with a twin pedal operation makes your job easier, smoother and safer. HST models employ a two pedal system for forward and reverse with smooth engagement, acceleration and deceleration.

Pedal pressure is minimised, reducing operator fatigue during long hours of use and when doing repetitive tasks.

Manual transmission models feature 12 forward and 12 reverse speeds delivering heavy duty performance. Second and reverse gears are synchronised for efficient forward and reverse operations requiring frequent shifting. A maximum ground clearance of 340mm makes working on rocky or uneven terrain simpler.

If you are searching for comfort, efficiency and strength look no further than the CK Series, it has you covered.



CK4220 MANUAL CAB
42HP



CK4220 HST CAB
42HP



@kiotiaustralia



@kiotitractorsaustralia



kioti.com.au



CK4220 COMPACT CAB

ENGINE

- Daedong 3B183LWM-E
- Liquid Cooled 3 Cylinder Diesel
- 1826cc Displacement
- 42 HP @ 2600 rpm
- 34 Litre Fuel Tank Capacity

TRANSMISSION

- 12x12 Synchro Shuttle or 3 Range Hydrostatic Drive
- Fwd/Rev Shuttle on Manual Model
- 4 Wheel Drive
- Rear Differential Lock
- Link Pedal System (HST Transmission Only)

HYDRAULICS & LINKAGE

- Manual Linkage Control
- 44.4 l/min Total Flow
- Category 1 Three Point Linkage
- Draw Bar
- 4 Hydraulic Remotes (2 Rear, 2 Front w/ Joystick)
- 740kg Max Rear Lift Capacity 600mm Behind Lift

POWER TAKE OFF

- 540 rpm Rear PTO Speed

BRAKES

- Independent Oil Immersed Disc Brakes

OPERATOR ENVIRONMENT

- Front Work Lights with Indicators/Brake Lights
- Step Through Platform
- Under Bonnet Muffler
- Comfort Seat
- Tool Box

TRAVEL SPEEDS

- Speed Range 1.52 - 23.56 km/h (Manual)
- Infinite Speeds from 0 - 25 km/h F/R (HST)

DIMENSIONS

Overall Length
3070mm

Overall Height
2650mm

Overall Width
1400mm

Wheelbase
1670mm

Ground Clearance
340mm

Weight (Manual)
1318kg

Weight (HST)
1335kg

TYRES
Industrial Front
25 / 8.5 x 14

Industrial Rear
15 / 19.5

Turf Front
27 x 8.5 - 15

Turf Rear
41 x 14.00 - 12.4

OPTIONAL EQUIPMENT



BACKHOE



SLASHER

*Note: The specifications are subject to change for the purpose of improvement without any notice. Images for illustration purposes only.

DEALER DETAILS



SCAN TO
LEARN MORE