



PX9520 SERIES

ROPS



VERSATILE WORKHORSE.

The dynamic and acclaimed PX range with a weight of 4 tonne is designed for serious farming and the ideal tractor for front end loader work. With a generous 120 litre fuel tank and a fuel efficient engine, the PX9520 can keep on working for a long time between fuel breaks. Equipped with hydrostatic power steering, this tractor provides smooth responsive steering that requires minimal operator effort.

Featuring a versatile transmission system that provides smooth operation and precise control, the PX9520 makes it easy to navigate challenging terrains and heavy workloads. Additionally, it is built with durable components and straightforward maintenance points, ensuring longevity and ease of upkeep.

With its combination of power, safety, and user-friendly features, the Kioti PX9520 ROPS tractor is an excellent choice for farmers seeking dependable performance and versatility in their agricultural operations.



PX9520 ROPS
95HP



@kiotiaustralia



@kiotitractorsaustralia



kioti.com.au



PX9520 UTILITY ROPS

ENGINE

- Perkins 1104C-44TTG
- Liquid Cooled 4 Cylinder Diesel Turbo
- 4399cc Displacement
- 95 HP @ 2200 rpm
- 120 Litre Fuel Tank Capacity
- Dual Stage Air Cleaner

TRANSMISSION

- Synchro Forward and Reverse Shuttle
- 16F X 16R
- Differential Lock
- 4 Wheel Drive

HYDRAULICS & LINKAGE

- Implement Pump - 48.4 lpm
- Power Steering Pump - 30.8 lpm
- Total Hydraulic Flow - 79.2 lpm
- Category 2 Three Point Linkage
- Hook Type 3PL
- 2400kg Maximum Rear Lift Capacity
- Power Steering
- Clevis Type Rear Draw Bar

POWER TAKE OFF

- Independent
- 540 / 1000 rpm
- Auto PTO

BRAKES

- Wet Multi Disc Type

OPERATOR ENVIRONMENT

- High Quality Fully Adjustable Seat with Armrests and Backrest
- Adjustable Steering Wheel and Instruments
- Flat Operator Deck

TRAVEL SPEEDS

- Forward 0.82 - 38.36 kph
- Reverse 0.80 - 37.33 kph

DIMENSIONS

Overall Length (inc 3PL)
4120mm

Overall Height
2950mm

Overall Width (min Tread)
2000mm

Wheelbase
2305mm

Ground Clearance (Min)
475mm

Weight
3500kg

TYRES
AG Tyres Front
12.4 - 24 8PR

AG Tyres Rear
18.4 - 34 8PR

OPTIONAL EQUIPMENT



BALE SPIKE



PALLET FORK

*Note: The specifications are subject to change for the purpose of improvement without any notice. Images for illustration purposes only.

DEALER DETAILS



SCAN TO
LEARN MORE



PX1052 SERIES

CAB



WHEN YOU NEED POWER, PRECISION & PERFORMANCE.

The innovative and highly regarded PX range with a weight of 4 tonnes is designed for serious farming and is the ideal tractor for front end loader work. With a large 120 litre fuel tank and a fuel efficient engine, the PX1052 can keep on working for a long time between fuel breaks. Equipped with hydrostatic power steering, it provides smooth responsive steering that requires minimal operator effort and is ideal for loader work.

The spacious cab is designed for maximum operator comfort, featuring climate control, ergonomic seating, and intuitive controls, all aimed at reducing fatigue during long working hours.

With a focus on durability and ease of maintenance, the Kioti PX1052 cab tractor is an excellent choice for professional farmers seeking reliable and high-performing equipment for their agricultural needs.



PX1052 CAB
105HP



@kiotiaustralia



@kiotitractorsaustralia



kioti.com.au



PX1052 CAB

ENGINE

- Perkins 1104C-44TTG
- Liquid Cooled 4 Cylinder Diesel Turbo
- 4399cc Displacement
- 105 HP @ 2400 rpm
- 120 Litre Fuel Tank Capacity
- Dual Air Cleaner

TRANSMISSION

- Synchro Mesh
- Power Shuttle
- Push Button Hand Clutch
- Wet Multi Disc Clutch
- 32F x 32R Speed with Hydraulic High/Low
- Rear Differential Lock

HYDRAULICS & LINKAGE

- Main Pump Capacity - 48.4lpm
- Steering Pump Capacity - 30.8lpm
- Total Maximum Flow - 79.2lpm
- 2400kgs Maximum Rear Linkage Lift Capacity
- Power Steering
- Category 2 Three Point Linkage
- Position, Draft, Mixed Control Lift System
- 4 Rear Remote Outlets
- Clevis Type Rear Draw Bar

POWER TAKE OFF

- Independent 540 / 1000 rpm PTO
- Auto PTO

BRAKES

- Wet Multi Disc Type

OPERATOR ENVIRONMENT

- High Quality Fully Adjustable Seat with Armrests and Backrest
- Adjustable Steering Wheel and Instruments
- Flat Operator Deck

CABIN

- Deluxe Cabin with A/C and Heating
- Radio
- Front and Rear Wipers
- Internal / External Air Exchanger Filters
- 12v Refrigerator

TRAVEL SPEEDS

- Forward 0.82 - 38.36 kph
- Reverse 0.80 - 37.33 kph

DIMENSIONS

Overall Length (inc 3PL)
4120mm

Overall Height
2770mm

Overall Width (min Tread)
2200mm

Wheelbase
2305mm

Ground Clearance (Min)
495mm

Weight
3630kg

TYRES
AG Radial Tyres Front
340 / 85R24

AG Radial Tyres Rear
460 / 85R34



OPTIONAL EQUIPMENT



BALE SPIKE



PALLET FORK

*Note: The specifications are subject to change for the purpose of improvement without any notice. Images for illustration purposes only.

RE-ORDER #KI-KB020

DEALER DETAILS



SCAN TO
LEARN MORE



PX1153 SERIES

CAB



THE NEXT STEP FORWARD.

The Kioti PX1153 cab tractor is a high-performance agricultural machine designed for demanding tasks and optimal operator comfort.

Equipped with a powerful 110-horsepower diesel engine, the PX1153 delivers robust performance and efficiency, making it ideal for heavy-duty farming operations. Its advanced transmission system ensures smooth and precise control, while the hydraulic system provides exceptional lifting capacity and implement compatibility. The spacious, climate-controlled cab is designed with the operator in mind, featuring ergonomic controls, an adjustable seat, and excellent visibility for reduced fatigue and increased productivity.

The PX1153 also includes modern technological features such as a digital dashboard, easy-to-access maintenance points, and comprehensive safety mechanisms. Whether plowing, planting, or harvesting, the Kioti PX1153 cab tractor offers reliable power, comfort, and efficiency for professional farmers and agricultural enterprises.



PX1153 CAB
115HP



@kiotiaustralia



@kiotitractorsaustralia



kioti.com.au



PX1153 CAB

ENGINE

- Perkins 1104D-44TAG
- Liquid Cooled 4 Cylinder Diesel Turbo
- 4399cc Displacement
- 115 HP @ 2400 rpm
- 120 Litre Fuel Tank Capacity
- Dual Air Cleaner

TRANSMISSION

- Synchro Mesh
- Power Shuttle
- Push Button Hand Clutch
- Wet Multi Disc Clutch
- 32F x 32R Speed with Hydraulic High/Low
- Rear Differential Lock

HYDRAULICS & LINKAGE

- Main Pump Capacity - 74.8lpm
- Steering Pump Capacity - 46.5lpm
- Total Maximum Flow - 121.3lpm
- 3630kg Maximum Rear Linkage Lift Capacity
- Power Steering
- Category 2 Three Point Linkage
- Position, Draft, ELC Mixed Control Lift System
- 4 Rear Remote Outlets
- Clevis Type Rear Draw Bar

POWER TAKE OFF

- Independent 540 / 1000 rpm PTO
- Auto PTO

BRAKES

- Wet Multi Disc Type

OPERATOR ENVIRONMENT

- High Quality Fully Adjustable Air Suspension Seat with Armrests and Backrest
- Adjustable Steering Wheel and Instruments
- Flat Operator Deck

CABIN

- Deluxe Cabin with A/C and Heating
- Radio
- Front and Rear Wipers
- Internal / External Air Exchanger Filters
- 12v Refrigerator

TRAVEL SPEEDS

- Forward 0.65 - 39.64 kph
- Reverse 0.65 - 39.37 kph

DIMENSIONS

Overall Length (inc 3PL)
4120mm

Overall Height
2750mm

Overall Width (min Tread)
2293mm

Wheelbase
2305mm

Ground Clearance (Min)
475mm

Weight
3702kg

TYRES
AG Radial Tyres Front
440 / 65R24

AG Radial Tyres Rear
540 / 65R34



OPTIONAL EQUIPMENT



BALE SPIKE



PALLET FORK

*Note: The specifications are subject to change for the purpose of improvement without any notice. Images for illustration purposes only.

DEALER DETAILS



SCAN TO
LEARN MORE