



RX6030 SERIES

CAB



GET BEHIND THE WHEEL TO EXPERIENCE THE POWER.

The Kioti RX Series tractors are fitted with a new streamlined hood which improves visibility for the operator. Maintenance is made easy with the hood opening to a 90 degree angle. Other improvements are larger tyres, 50% more lift capacity, higher road speed, increased fuel capacity and better hydraulic flow.

The RX Series is a versatile work-horse that will suit a variety of applications, such as vineyard work and loader work, and is compact enough to do smaller jobs around the farm. Some of the standard features are 24×24 transmission, 4WD power steering, forward reverse shuttle and independent rear PTO.



RX6030 CAB
60HP



@kiotiaustralia



@kiotitractorsaustralia



kioti.com.au



RX6030 UTILITY CAB

ENGINE

- Daedong 4B243DTM-A
- Liquid Cooled 4 Cylinder Diesel Turbo
- 2600cc Displacement
- 60 HP @ 2600 rpm
- 95 Fuel Tank Capacity

TRANSMISSION

- 24 Forward Speeds / 24 Reverse Speeds
- Synchro Fwd / Rev Shuttle
- Creeper Range
- 4 Wheel Drive

HYDRAULICS & LINKAGE

- Position & Draft Control
- 67.6 l/min Total Flow
- Cassette Type Ball Ends (Cat 2)
- Swinging Draw Bar
- 4 Sets of Hydraulic Remotes (2 Rear / 2 Front)
- 2075kg Rear Lift Capacity

POWER TAKE OFF

- Independent
- Electro-Hydraulic Engagement
- Auto PTO
- 540 / 750 rpm Rear PTO Speed

BRAKES

- Wet Multi Disc Type

OPERATOR ENVIRONMENT

- High Quality Fully Adjustable Seat with Backrest
- Adjustable Steering Wheel and Instruments
- Flat Operator Deck

CABIN

- Deluxe cabin with A/C and Heating
- Radio
- Front Wiper
- Internal / External Air Exchanger Filters

TRAVEL SPEEDS

- 0.16 - 36.36 Forward
- 0.16 - 35-75 Reverse

DIMENSIONS

Overall Length
3685mm

Overall Height
2630mm

Overall Width
1800mm

Wheelbase
2100mm

Ground Clearance (Min)
420mm

Weight
2630kg

TYRES
AG Tyres Front
11.2 - 20

AG Tyres Rear
14.9 - 30



OPTIONAL EQUIPMENT



POST HOLE DIGGER



SLASHER

*Note: The specifications are subject to change for the purpose of improvement without any notice. Images for illustration purposes only.

DEALER DETAILS



SCAN TO
LEARN MORE



RX7030/RX8030 SERIES CAB



READY FOR THE DEMANDS OF ANY JOB.

The Kioti RX Series tractors are fitted with a new streamlined hood which improves visibility for the operator. Maintenance is made easy with the hood opening to a 90 degree angle. Other improvements are larger tyres, 50% more lift capacity, higher road speed, increased fuel capacity and better hydraulic flow.

The RX Series is a versatile work-horse that will suit a variety of applications, such as vineyard work and loader work, and is compact enough to do smaller jobs around the farm. Some of the standard features are 24×24 transmission, 4WD power steering, forward reverse shuttle and independent rear PTO.



RX7030P CAB
70HP



RX8030P CAB
80HP



@kiotiaustralia



@kiotitractorsaustralia



kioti.com.au



RX7030P/RX8030P UTILITY CAB

ENGINE

- Daedong 4F243DTP-A (RX7030)
- Daedong 4FT-TP2-A (RX8030)
- Liquid Cooled 4 Cylinder Diesel Turbo
- 2435cc Displacement
- 70 HP @ 2600 rpm (RX7030)
- 80 HP @ 2600 rpm (RX8030)
- 85 Litre Fuel Tank Capacity (RX7030)
- 95 Litre Fuel Tank Capacity (RX8030)

TRANSMISSION

- Power Shuttle
- 4 Main Gear x 6 Range Gear Shift
- 24F X 24R Speed
- 4 Wheel Drive with Wet Multi Disc Engagement

HYDRAULICS & LINKAGE

- Total Hydraulic Flow - 67.6 lpm (RX7030)
- Total Hydraulic Flow - 72.8 lpm (RX8030)
- Category 2 Three Point Linkage
- Cassette Type Lower Link
- 2075kg Maximum Rear Lift Capacity (RX7030)
- 2256kg Maximum Rear Lift Capacity (RX8030)
- Clevis Type Rear Draw Bar
- Standard 2 Pair Hydraulic Rear Remotes
- Hydraulic Power Steering

POWER TAKE OFF

- Independent
- 540 / 750 rpm
- SAE 1-3/8, 6 Spline

BRAKES

- Wet Multi Disc Type

OPERATOR ENVIRONMENT

- High Quality Fully Adjustable Seat with Backrest
- Adjustable Steering Wheel and Instruments
- Flat Operator Deck

CABIN

- Deluxe Cabin with A/C and Heating
- Radio
- Front Wiper
- Internal / External Air Exchanger Filters

TRAVEL SPEEDS

- Forward 0.16 - 36.36 kph (RX7030)
- Reverse 0.16 - 35.75 kph (RX7030)
- Forward 0.17 - 37.86 kph (RX8030)
- Reverse 0.17 - 37.23 kph (RX8030)

DIMENSIONS

RX7030

Overall Length
3685mm

Overall Height
2655mm

Overall Width (min Tread)
1800mm

Wheelbase
2100mm

Ground Clearance (Min)
420mm

Weight
2630kg

TYRES
AG Tyres Front
11.2 - 20

AG Tyres Rear
14.9 - 30

RX8030

Overall Length
3685mm

Overall Height
2655mm

Overall Width (min Tread)
1960mm

Wheelbase
230mm

Ground Clearance (Min)
440mm

Weight
2795kg

TYRES
Radial Tyres Front
280 / 85R24

Radial Tyres Rear
420 / 85R30



OPTIONAL EQUIPMENT



FLAIL MOWER



SLASHER

*Note: The specifications are subject to change for the purpose of improvement without any notice. Images for illustration purposes only.

DEALER DETAILS



SCAN TO
LEARN MORE



RX7030/RX8030 SERIES ROPS



GET BEHIND THE WHEEL TO EXPERIENCE THE POWER.

The Kioti RX Series tractors are fitted with a new streamlined hood which improves visibility for the operator. Maintenance is made easy with the hood opening to a 90 degree angle. Other improvements are larger tyres, 50% more lift capacity, higher road speed, increased fuel capacity and better hydraulic flow.

The RX Series is a versatile work-horse that will suit a variety of applications, such as vineyard work and loader work, and is compact enough to do smaller jobs around the farm. Some of the standard features are 24×24 transmission, 4WD power steering, forward reverse shuttle and independent rear PTO.



RX7030 ROPS
70HP



RX8030 ROPS
80HP



@kiotiaustralia



@kiotitractorsaustralia



kioti.com.au



RX7030/RX8030 UTILITY ROPS

ENGINE

- Daedong 4F243DTP-A
- Liquid Cooled 4 Cylinder Diesel Turbo
- 2435cc Displacement
- 70 HP @ 2600 rpm (**RX7030**)
- 80 HP @ 2600 rpm (**RX8030**)
- 85 Litre Fuel Tank Capacity

TRANSMISSION

- Power Shuttle
- 4 Main Gear x 6 Range Gear Shift
- 24F X 24R Speed
- 4 Wheel Drive with Wet Multi Disc Engagement

HYDRAULICS & LINKAGE

- Total Hydraulic Flow - 67.6 lpm (**RX7030**)
- Total Hydraulic Flow - 72.8 lpm (**RX8030**)
- Category 2 Three Point Linkage
- Cassette Type Lower Link
- 2075kg Maximum Rear Lift Capacity (**RX7030**)
- 2256kg Maximum Rear Lift Capacity (**RX8030**)
- Clevis Type Rear Draw Bar
- Standard 2 Pair Hydraulic Rear Remotes
- Hydraulic Power Steering

POWER TAKE OFF

- Independent
- 540 / 750 rpm
- SAE 1-3/8, 6 Spline

BRAKES

- Wet Multi Disc Type

OPERATOR ENVIRONMENT

- High Quality Fully Adjustable Seat with Backrest
- Adjustable Steering Wheel and Instruments
- Flat Operator Deck

TRAVEL SPEEDS

- Forward 0.16 - 36.36 kph (**RX7030**)
- Reverse 0.16 - 35.75 kph (**RX7030**)
- Forward 0.17 - 37.86 kph (**RX8030**)
- Reverse 0.17 - 37.23 kph (**RX8030**)

DIMENSIONS

RX7030

Overall Length
3685mm

Overall Height
2730mm

Overall Width (min Tread)
1800mm

Wheelbase
2100mm

Ground Clearance (Min)
420mm

Weight
2360kg

TYRES
AG Tyres Front
11.2 - 20

AG Tyres Rear
14.9 - 30

RX8030

Overall Length
3685mm

Overall Height
2730mm

Overall Width (min Tread)
1800mm

Wheelbase
2100mm

Ground Clearance (Min)
420mm

Weight
2540kg

TYRES
Radial Tyres Front
280 / 85R24

Radial Tyres Rear
420 / 85R30

OPTIONAL EQUIPMENT



FLAIL MOWER



SLASHER

*Note: The specifications are subject to change for the purpose of improvement without any notice. Images for illustration purposes only.

DEALER DETAILS



SCAN TO
LEARN MORE