



**MASSEY FERGUSON**

23 - 25 HP

# MF GC1700

The Perfect All-Rounder





# Massey Ferguson GC Series Compact Tractors

## The Perfect All-Rounder

Massey Ferguson's GC Series compact tractors are the perfect all-around machines for tackling your everyday jobs. Whether you're a farmer, small landowner or commercial enterprise, the MF GC1700 Series is designed and engineered to help you get a wide variety of jobs done right. With engines ranging up to 25 horsepower and unmatched versatility, the MF GC1700 Series can handle everything from mowing, loading, general farm work and more.

These easy-to-drive workhorses deliver straightforward, intuitive performance in a compact-sized machine. So if your workload demands a real tractor, check out the MF GC1700 Series. It delivers on every job, every time.





# Sophisticated Styling and Ergonomic Layout

## Modern design

The MF GC1700 Series has been redesigned to offer maximum comfort, including:

- ▶ 12V socket
- ▶ Cup holder
- ▶ Covered storage area




## Excellent forward visibility

Whether you're mowing, loading, landscaping or simply carting, the MF GC1700 Series ensures you have full visibility of where you need to go.



## Visual controls

For ease of use, operator convenience and to simply take the guess work out, each lever has been colour coded to ensure you know which to pull and when to pull it.



TILT STEERING WHEEL

FOOT BRAKE  
DIFFERENTIAL LOCK

FLAT FOOT DECK

PTO GEAR LEVERS

GRAB HANDLE

CUP HOLDER

REVERSIBLE SEAT  
FOR BACKHOE  
(MF GC1725M ONLY)

ANALOG/DIGITAL DASH

HAND THROTTLE

FORWARD/REVERSE  
DUAL HYDROSTATIC PEDALS

INTEGRATED LOADER JOYSTICK  
AS STANDARD

COVERED STORAGE  
12V POWER SOCKET  
(MF GC1725M ONLY)

GRAB HANDLE


SUSPENDED SEAT  
WITH ARMRESTS

FUEL FILL

SEATBELT

## Unquestionably Massey Ferguson

Taking its cue from its larger siblings, the stylish ergonomic design ensures the MF GC1700 Series looks and performs like any other model in the Massey Ferguson range.




## Comfortable joystick position

An integrated joystick, placed next to the operator for greater comfort, ensures that you have total control over your operation at all times throughout the day.



## Dashing design & tilt steering

The MF GC1700 Series is for everyone. A tiltable, deep dish steering wheel and digital dash ensures the perfect position and provides easy to read visual feedback during operation – keeping you comfortable and always in control.





# Outstanding Performance

Performance and versatility is the key to a compact tractor and that's exactly what you get with the MF GC1700 Series. Heavy duty axles and high lift capacity on the three point linkage allow for a wide range of attachments and implements so you can perform a wide range of tasks.

The MF GC1700 Series is easy to use and manoeuvre and is ideal for squeezing into narrow spaces and around tight contours. Clever features such as dual hydrostatic pedal control and cruise control make hard work a breeze and allow for an easier day's work.



## Largest engine in its class

- ▶ Powerful 3-cylinder liquid cooled engine
- ▶ Solid metal hood with tilt design and open/close handle for easy access to serviceable areas
- ▶ Radiator with removable mesh screen to shield radiator from debris and allow access for cleaning
- ▶ 1.123 litre engine providing high torque at lower rpm



## Dual Hydrostatic Control Pedals

- ▶ Dual control pedals allow forward and reverse control with maximum comfort
- ▶ 2 range hydrostatic transmission for ultimate driving comfort and easy operation



## Differential lock

- ▶ The differential lock can be easily engaged using the foot pedal. Combined with 4WD, it ensures consistent and reliable traction through tough and slippery conditions.



## Cruise control

- ▶ Newly designed cruise control
- ▶ Improves driving comfort
- ▶ Can result in better fuel efficiency





### Axles

- ▶ Robust front and rear axles to handle a wide range of accessories and front end loaders



### Tyres

- ▶ Turf, Ag or Industrial options are available to best suit the tasks at hand
- ▶ 18x8.5-10 front tyres
- ▶ 26x12.00-12 rear tyres



### Three point linkage

- ▶ A large three point linkage lift capacity of 540kg
- ▶ 3 point hitch provided as standard



# Quick Attach Implements

## The Perfect All-Rounder

The MF GC1700 is ready to work when you are. Whether it's mowing, pulling, shifting or lifting, there's a choice of quick and easy attachments that have been perfectly matched to ensure maximum performance and efficiency. Choose from standard or

four-in-one front loaders and professional quality cutting decks that mow high volumes of grass and deliver a fine cut. A fully integrated backhoe combines heavy duty construction, a cast iron bucket link and a boom float typically found in construction grade equipment.



### Quick Attach Implements

- ▶ Quick attach loader available (Standard and 4 in 1)
- ▶ Quick attach backhoe available (1725M only)
- ▶ Drive over mower deck

### Professional Quality Mowing Decks

- ▶ Full floating decks deliver a top-notch cut on every type of terrain
- ▶ All spindle assemblies are made of cast iron for greater durability
- ▶ 60 inch side discharge deck
- ▶ Easy drive over attachment

### Easy mounting and removal

- ▶ Make full use of the three point linkage without removing the backhoe sub-frame with a four-point mounting system and quick-attach design. The self-standing backhoe can also be easily removed.

### Boom float

- ▶ The boom float makes it much easier for the operator to position the bucket, create an even floor bed in the cut and provide smooth grading operation when backfilling. Achieve increased operator comfort and productivity from faster digging speeds and cycle times, while reducing overall fuel consumption.



# MF GC1700 Series Specifications

Model	MF GC1723E	MF GC1725M
<b>Engine</b>		
Engine Power hp (kW)	22.8 (16.8)	24 (17.9)
Rated Engine Speed	2600	3000
Type	3-cylinder diesel	
Displacement in <sup>3</sup> (cc)	68.5 (1123)	
Torque (nM)	65 @ 2000	65 @ 2200
Cooling System	Liquid cooled	
Fuel Tank Capacity (L)	25	
<b>Transmission</b>		
Control	Dual foot pedal	
Hydrostatic	2-range with cruise	
Max forward speed km/h (mph)	14.7 (9.1)	
Rear brakes	Wet disc	
<b>Rear PTO</b>		
Rear PTO Power hp (kW)	18.3 (13.6)	18.5 (13.8)
Type	Independent	
Speed	540 @ 2532	
Shaft	Fixed	
Configuration	6 spline	
<b>Mid PTO</b>		
Type	Independent	
Speed	2000 @ 2476	
Configuration	15 spline	
<b>Hydraulics</b>		
Type of system	Open centre	
Total flow l/min (gpm)	24 (6.3)	26.3 (6.8)
Factory Joystick	Standard	
<b>3-point hitch</b>		
ASAE hitch	Cat I.	
Rate of drop control	Standard	
<b>Lift capacity</b>		
@ BE (kg)	540	
@ 24"	300	
Type of stabilisers	Turnbuckle	
Type of link ends	Fixed	
<b>Operator Area</b>		
Platform - ROPS	Fixed	Foldable
Seat Type	Coil Spring Suspension	
Seatbelt type	Retractable	
Covered storage area	Standard	
Cup holder	Standard	
12V socket	N/A	Standard
<b>Dimensions (AG)</b>		
Overall length mm (in)	2480 (97.6)	
Min width @ rear combo light mm (in)	1185 (46.6)	
Max height over ROPS mm (in)	1850 (72.8)	2180 (85.5)
Ground clearance mm (in)	170 (6.7)	
Wheelbase mm (in)	1450 (57.1)	
Shipping weight kg (lbs)	690 (1523)	
<b>Compatible implements</b>		
3-point hitch (Cat I)	Standard	
Front End Loader	Optional	
Mower Deck	Optional	
Backhoe	N/A	Optional

# Implement Specifications

<b>Deck Model:</b>	<b>GC2300</b>
<b>Type</b>	
60" Mid mount	Drive-Over Rotary Deck
<b>General</b>	
Discharge Type	Side
Number of Blades	3 (overlapping)
Gearbox Drive	Shaft
Speed (rpm)	2000
Blade Tip Speed (rpm)	18856
Gauge Wheels	4
Anti-Scalp rollers	3
Raise and Lower Actuation	Via 3-Point Linkage
Height Control	Manual Adjustment
Transport Height	150
<b>Dimensions</b>	
Cutting Width (mm)	1524
Overall Width (mm)	1900
Weight (kg)	200
Overall Height (mm)	524
<b>Capacities</b>	
Gearbox (cc)	800

<b>Backhoe Model</b>	<b>CB25</b>
<b>Type</b>	
Quick Attach	Standard
<b>General</b>	
Max Digging Depth (mm)	1970
Max Reach (mm)	2730
Transport Height (mm)	1800
Max Length with GC1725M & Loader (mm)	4490
Transport Stabiliser Spread (mm)	1200
Operating Stabiliser Spread (mm)	2040
Loading Height (mm)	1680
Angle of Departure	20°
Swing Arc	150°
Bucket Rotation	177°
Shipping Weight (kg)	288
Digging Force (Bucket) (kg)	1126
Digging Force (Dipper) (kg)	793

<b>Loader Model</b>	<b>2400SL</b>
<b>Type</b>	
Quick Attach	Standard
<b>General</b>	
Max Digging Depth (mm)	60
Max Reach (mm)	1200
Max lifting height to pin (mm)	1800
Max dumping angle	45°
Max dumping clearance (mm)	1450
Max dumping reach at max height (mm)	460
Max bucket rollback angle	40°
Break out force @ 500mm forward (kg)	376
Shipping Weight (kg)	250

Web: [www.MasseyFerguson.com.au](http://www.MasseyFerguson.com.au)  
 Facebook: [www.facebook.com/MasseyFergusonGlobal](https://www.facebook.com/MasseyFergusonGlobal)  
 Twitter: [Twitter.com/MF\\_EAME](https://twitter.com/MF_EAME)  
 Instagram: [Instagram.com/MasseyFergusonGlobal](https://www.instagram.com/MasseyFergusonGlobal)  
 YouTube: [www.YouTube.com/MasseyFergusonGlobal](https://www.youtube.com/MasseyFergusonGlobal)  
 Blog: [Blog.MasseyFerguson.com](http://Blog.MasseyFerguson.com)



Every effort has been made to ensure that the information contained in this publication is as accurate and current as possible. However, inaccuracies, errors or omissions may occur and details of the specifications may be changed at any time without notice. Therefore, all specifications should be confirmed with your Massey Ferguson Dealer or Distributor prior to any purchase.



MASSEY FERGUSON® is a worldwide brand of AGCO.



**MASSEY FERGUSON**