



CHEETAH

48" & 52" models

**Fast. Maneuverable.
Comfortable.**

Specifications

Engine Options:

- 22hp Kawasaki FX, air-cooled, V-Twin, vertical shaft
- 23hp Kohler Command, air-cooled, V-Twin, Electronic Fuel Injection (EFI)
- 23hp Kawasaki FX, air-cooled, V-Twin, vertical shaft
- 25hp Kohler Command, air-cooled, V-Twin, Electronic Fuel Injection (EFI)
- 28hp Briggs Cyclonic, air-cooled, V-Twin, vertical shaft

Fuel Capacity/Design:

10 gallons, dual fuel tanks. Extra-large fuel neck for easy filling.

Travel Control:

Twin lever steering controls with gas dampers for smooth, precise maneuverability. Adjustable damper positions.

Ground Speed:

10.5 mph forward, 5 mph reverse

Main Frame Construction:

Single tube, steel frame, full-length, fully-welded

Drive Tires:

23 x 9.5 - 12, 4 ply

Caster Tires:

13 x 6.5 - 6, 4 ply; Flat-Free, semi-pneumatic

Caster Wheel Bearings:

Tapered roller bearings

Front Caster Arm Design:

Bolt-on for easy replacement if necessary

Drive System:

Dual Hydro-Gear ZT-3400 integrated transaxles (2 separate units) with charge pumps spin-on oil filters and cooling fans

Hydraulic Oil Filter:

25 micron spin-on filter

Electrical System:

12 Volt battery, "maintenance-free" battery, accessory charging outlet and Solenoid shift starter.

WWW.SCAG.COM



(Continued)

SCAG
POWER EQUIPMENT

Belts:	Kevlar cord. Self-adjusting, spring-loaded, self-tightening
Drive/Load Pulleys:	Split-steel design -- stronger and lighter weight than cast-iron
Instrument Panel :	Tiger Eye Advanced Monitoring System, key switch, throttle, manual choke, PTO switch, digital hour meter

Tiger Eye Advanced Monitoring System:

Depending on engine selection following systems are monitored: hour meter, volt meter, air filter condition, control lever circuit, PTO circuit, parking brake circuit, seat switch circuit and safety interlock module.

- Operator Suspension System:**
- Isolates the entire operator station from the effects of rough terrain.
 - Coil-over shock provides effective suspension action right where it's needed, and only where it's needed for a smooth ride.
 - Thick-cushioned, bolstered seat, fully adjustable, with adjustable, folding arm rests.
 - 3-Position adjustable deck lift foot pedal allows for easy deck lift for all operators

PTO - Electric Clutch: • Ogura GT3.5 - 250 ft lb; adjustable air-gap

Cutter Decks: 48" & 52" Velocity Plus decks. Floating, adjustable, anti-scalping design.

Cutter Deck Construction: Tri-Plate, welded: 10-gauge top, 7 gauge skirts, 7 gauge & 11 gauge reinforcement plates.

Cutter Deck Drive: Belt-driven -- straight alignment for increased reliability & longevity

- Number of Anti-Scalp Wheels:**
- 48": 3 wheels in 3 positions, 1 rear anti-scalp roller
 - 52": 3 wheels in 3 positions, 1 rear anti-scalp roller

Cutter Deck Spindles: Scag Heavy-Duty Spindles w/cast-iron housing & tapered roller bearings, backed by 3-year limited warranty

Cutter Deck Height Adjustment: Foot pedal lift (3-position adjustable) with self-locking mechanism at transport position

Cutting Range: 1" to 5.5" in .25" increments

Number of Cutter Blades: 3 Marbain blades

Total Length: 81.75"

Total Width (with discharge chute in mowing position):

- 48" models: 61.25"
- 52" models: 65.25"

Total Width (with discharge chute in transport position):

- 48" models: 49.75"
- 52" models: 53.75"

Height (with ROPS): 67"

Height (with ROPS folded): 48"

- Weight (with ROPS):**
- 48" models: 1075 lbs.
 - 52" models: 1080 lbs.

- Warranty:**
- 2 Yr. Commercial Mower Warranty—Parts & labor.
 - 3 Yr. / 500 Hour Non-Commercial Mower Warranty—Parts & labor.
 - 3 Yr. Deck Warranty—First & second years parts & labor; third year parts.
 - 3 Yr. Spindle Warranty—First & second years parts & labor; third year parts.
 - 2 Yr. Engine Warranty—Minimum two-year warranty covered directly through the individual engine manufacturer.



All specifications subject to change without notice. Actual ground speeds may vary.





CHEETAH

61" & 72" models

The Fastest Cat on Earth.

Specifications

Engine Options:

- 27hp Kawasaki FX, air-cooled, V-Twin, vertical shaft
- 29hp Kohler Command EFI, air-cooled, V-Twin, vertical shaft
- 31hp Kawasaki FX, air-cooled, V-Twin, vertical shaft
- 35hp Kohler Command EFI, air-cooled, V-Twin, vertical shaft

Fuel Capacity/Design:

15 gallons, dual fuel tanks mounted low on the mower to lower the center-of-gravity and improve hillside stability and traction.

Travel Control:

Twin "Quick-Fit" steering controls with gas dampers for smooth, precise maneuverability. Adjustable to fit various operator sizes. Adjustable damper positions.

Ground Speed:

- 16mph forward, 8 mph reverse in high-range
- 12mph forward, 5 mph reverse in low-range

Main Frame Construction:

Double tube, steel frame, full-length, fully-welded

Drive Tires:

24 x 12 - 12, 4 ply

Caster Tires:

13 x 6.5 - 6, 4 ply; Flat-Free, semi-pneumatic

Caster Wheel Bearings:

Tapered roller bearings

Front Caster Arm Design:

Bolt-on for easy replacement if necessary

Drive System:

Dual Hydro-Gear ZT-5400, 2-speed, integrated transaxles (2 separate units); 16cc displacement pump; 21cc displacement wheel motor; 9" cooling fan on each unit

Hydraulic Oil Cooling:

Yes - 9" fan on each unit

Hydraulic Oil Filter:

25 micron spin-on filter

Electrical System:

12 Volt battery, "maintenance-free" battery, accessory charging outlet and Solenoid shift starter.

WWW.SCAG.COM



(Continued)

SCAG
POWER EQUIPMENT

Belts:	Kevlar cord. Self-adjusting, spring-loaded, self-tightening
Drive/Load Pulleys:	Split-steel design -- stronger and lighter weight than cast-iron
Instrument Panel :	Tiger Eye Advanced Monitoring System, key switch, throttle, manual choke (non-EFI models), PTO switch, digital hour meter

Tiger Eye Advanced Monitoring System:

Depending on engine selection following systems are monitored: hour meter, volt meter, air filter condition, control lever circuit, PTO circuit, parking brake circuit, seat switch circuit and safety interlock module.

- Operator Suspension System:**
- Isolates the entire operator station from the effects of rough terrain.
 - Coil-over shock provides effective suspension action right where it's needed, and only where it's needed, for a smooth ride.
 - High-back seat, fully adjustable, with adjustable, folding arm rests.
 - "Quick-Fit" steering control levers feature incredible range of adjustment for optimal comfort and control
 - 3-Position adjustable deck lift foot pedal allows for easy deck lift for all operators

- PTO - Electric Clutch:**
- Ogura GT3.5 - 250 ft lb; adjustable air-gap (61" models)
 - Ogura GT5 - 350 ft lb; adjustable air-gap (31FX, 35CV-EFI & All 72" models)

Cutter Decks: 61" & 72" Velocity Plus side-discharge decks; 61" rear-discharge (RD) deck. Floating, adjustable, anti-scalping design.

Cutter Deck Construction: Tri-Plate, welded: 10 gauge top, 7 gauge skirts, 7 gauge & 11 gauge reinforcement plates.

Cutter Deck Drive: Belt-driven -- straight alignment for increased reliability & longevity

- Number of Anti-Scalp Wheels:**
- 61" side-discharge: 7 wheels in 5 positions, 2 rear anti-scalp rollers
 - 61" rear-discharge: 5 wheels in 3 positions
 - 72" side-discharge: 7 wheels in 5 positions, 2 rear anti-scalp rollers

Cutter Deck Spindles: Scag Heavy-Duty Spindles w/cast-iron housing & tapered roller bearings, backed by 3-year limited warranty

Cutter Deck Height Adjustment: Foot pedal lift (3-position adjustable) with self-locking mechanism at transport position

Cutting Range: 1.25" to 5" in .25" increments

Number of Cutter Blades: 3 Marbain blades

- Total Length:**
- 61" models: 85.5"
 - 72" models: 91"

- Total Width (with discharge chute in mowing position):**
- 61" models: 73.5"
 - 61" RD models: 63.5"
 - 72" models: 83"

- Total Width (with discharge chute in transport position):**
- 61" models: 62.75"
 - 72" models: 73"

Height (with ROPS): 67"

Height (with ROPS folded): 49.5"

- Weight (with ROPS):**
- 61" models: 1350-1365 lbs.
 - 72" models: 1385-1400 lbs.

- Warranty:**
- 2 Yr. Commercial Mower Warranty—Parts & labor.
 - 3 Yr. / 500 Hour Non-Commercial Mower Warranty—Parts & labor.
 - 3 Yr. Deck Warranty—First & second years parts & labor; third year parts.
 - 3 Yr. Spindle Warranty—First & second years parts & labor; third year parts.
 - 2 Yr. Engine Warranty—Minimum two-year warranty covered directly through the individual engine manufacturer.



All specifications subject to change without notice. Actual ground speeds may vary.

WWW.SCAG.COM

