



FREEDOM Z
Made in the USA by **SCAG**

Reclaim Your Weekend

Specifications

Engine Options:	<ul style="list-style-type: none">• 22hp Kohler 7000 Series, air-cooled, twin cylinder, vertical shaft• 24hp Kohler 7000 Series, air-cooled, twin cylinder, vertical shaft
Fuel Capacity/Design:	6.5 gallon fuel tank with molded-in cupholder & storage tray
Travel Control:	Twin padded steering controls with gas dampers for smooth, precise maneuverability. Levers are adjustable.
Ground Speed:	Up to 8mph forward, 5mph reverse
Main Frame Construction:	Steel tube frame, full-length, fully-welded
Drive Tires:	20 x 10 - 8, 2-ply
Caster Tires:	11 x 4.5 - 5, 4 ply
Caster Pivot Bearings:	Sealed ball bearings
Drive System:	Dual Hydro-Gear ZT-2800 integrated transaxles with charge pumps and spin-on oil filters; steel plate oil filter guards protect filters from damage
Mower Maintenance:	“Low Maintenance” mower design has no grease points, saving you maintenance time
Electrical System:	12 Volt battery. Bendix starter.

WWW.SCAG.COM



(Continued)

SCAG
POWER EQUIPMENT

Belts:	Kevlar cord. Self-adjusting, spring-loaded, self-tightening.
Drive/Load Pulleys:	Split steel pulleys. Steel dust and debris covers over idler pulley bearings to keep foreign material out and extend bearing life.
Instrument Panel :	Key switch, throttle, manual choke, PTO switch, digital hourmeter
Seat:	Adjustable (tools required), fully cushioned seat with padded arm rests; retractable seat belt
Foot Plate:	Extra-large foot plate for improved comfort; easy to get on and off of mower. Pierced, extruded steel tread ensures solid footing.
PTO - Electric Clutch:	Ogura clutch with adjustable air-gap for long component life
Cutter Decks:	48" or 52" deck. Floating, adjustable, anti-scalping design.
Cutter Deck Construction:	Welded steel with 7-gauge deck skirt, 10-gauge top with 11-gauge reinforcement plate/baffles
Cutter Deck Drive:	Belt driven -- Straight belt for long life, not a twisted "mule" drive
Anti-Scalp:	One roller on left-front edge, two rollers on center-front edge, skid plate at rear-center of deck
Cutter Deck Spindles:	Heavy-duty, no-maintenance spindles with cast aluminum housing & sealed ball bearings; reliable, worry-free performance day in and day out
Cutter Deck Height Adjustment:	Foot pedal/peg lift with self-locking mechanism at transport position. Large knurled foot pedal/peg for "no-slip" deck lifting.
Cutting Range:	1" to 4.5" in .25" increments. Easily adjustable while seated.
Number of Cutter Blades:	3 Marbain blades
Deck Leveling:	4-corner cutter deck adjustment mechanisms allow for easy deck leveling and pitch adjustment to ensure a smooth, even cut
Total Length:	72"
Total Width (with discharge chute in mowing position):	<ul style="list-style-type: none"> ● 48" models = 60.5" ● 52" models = 64.5"
Total Width (with discharge chute in transport position):	<ul style="list-style-type: none"> ● 48" models = 49" ● 52" models = 53"
Height:	60"
Weight:	<ul style="list-style-type: none"> ● 48" models = 745 lbs. ● 52" models = 765 lbs.
Warranty:	<ul style="list-style-type: none"> ● 3 Yr. / 500 Hour Non-Commercial Mower Warranty*—Parts & labor ● 1 Yr. Commercial Mower Warranty*—Parts & labor ● 2 Yr. Engine Warranty—Minimum two-year warranty covered directly through the individual engine manufacturer.

*See Limited Warranty statement for complete details.



All specifications subject to change without notice. Actual ground speeds may vary.

WWW.SCAG.COM

