

LIBERATE YOUR WEEKEND

Specifications

Engine Options: • 22hp Kohler 7000 Series Pro, air-cooled, twin cylinder, vertical shaft

• 24hp Kohler 7000 Series Pro, air-cooled, twin cylinder, vertical shaft

Fuel Capacity/Design: 5.5 gallon fuel tank with molded-in cupholder

Travel Control: Twin padded steering controls with gas dampers for smooth, precise

maneuverability. Levers are adjustable.

Ground Speed: Up to 7mph forward, 5mph reverse

Main Frame Construction: Steel tube frame, full-length, fully-welded

Drive Tires: 20 x 10 - 8, 2-ply **Caster Tires:** 11 x 4 - 5, 4 ply

Caster Pivot Bearings: Sealed ball bearings

Drive System: Dual Hydro-Gear ZT-2800 integrated transaxles with charge pumps and

spin-on oil filters; composite plate oil filter guards protect filters from

damage

Mower Maintenance: Low-maintenance mower design has fewer grease points, saving you

maintenance time

Electrical System: 12 Volt battery. Bendix starter.



(Continued)



Belts: Kevlar cord. Self-adjusting, spring-loaded, self-tightening.

Drive/Load Pulleys: Split steel pulleys. Steel dust and debris covers over idler pulley bearings

to keep foreign material out and extend bearing life.

Instrument Panel: Key switch, throttle, manual choke, PTO switch, digital hourmeter

Seat: Adjustable (tools required), fully cushioned seat

Foot Plate: Extra-large foot plate for improved comfort; easy to get on and off of

mower. Pierced, extruded steel tread ensures solid footing.

PTO - Electric Clutch: Ogura clutch with adjustable air-gap for long component life Cutter Decks: 48" or 52" deck. Floating, adjustable, anti-scalping design.

Cutter Deck Construction: Welded steel with 10-gauge deck skirt, 10-gauge top with 11-gauge

reinforcement plate/baffles

Cutter Deck Drive:Belt driven -- Straight belt for long life, not a twisted "mule" driveAnti-Scalp:Two rollers on center-front edge, skid plate at rear-center of deckCutter Deck Spindles:Heavy-duty, no-maintenance spindles with cast aluminum housing &

sealed ball bearings; reliable, worry-free performance day in and day out

Cutter Deck Height Adjustment:

Foot pedal lift

Cutting Range: 1.5" to 4.5" in .25" increments. Easily adjustable while seated.

Number of Cutter Blades: 3 Marbain blades

Deck Leveling: 4-corner cutter deck adjustment mechanisms allow for easy deck leveling

and pitch adjustment to ensure a smooth, even cut

Total Length: 73

Total Width (with discharge chute in mowing position):

48" models = 60.5"52" models = 64.5"

Total Width (with discharge chute in transport position):

48" models = 49"52" models = 53"

Height: 43"

Weight: ● 48" models = 620 lbs.

• 52" models = 640 lbs.

Warranty: • 5 Yr. / 750 Hour Non-Commercial Mower Warranty*—Parts & labor

2 Yr. Consumer Engine Warranty—Minimum two-year warranty covered

directly through the individual engine manufacturer.

*See Limited Warranty statement for complete details.

All specifications subject to change without notice. Actual ground speeds may vary.



