



### Engine

SDF 1000 Series Tier 3 Diesel Engine  
 3 Cyl/3000cc Turbocharged  
 Liquid/Oil Cooled  
 Individual Bosch Injector Pumps  
 62Hp @ 2200 rpm (2005/25/CE)  
 Torque 244nm  
 Side Mounted Cabin Exhaust  
 70lt Fuel Capacity

### Transmission

30/15 Synchronmesh Gearbox  
 Forward/Reverse Synchro Shuttle  
 Shuttle Mounted on Steering Column  
 Double Dry Heavy Duty 11" Clutch  
 Gear Levers Located Right Hand Side  
 Creep Gear Std  
 4 Wheel Independent Braking  
 Front Wheel Assist- Mechanical  
 Front & Rear Diff Lock- Mechanical  
 40 km/h Road Speed

### PTO

Independent Rear PTO  
 540/ 750 Speed PTO  
 540 PTO @ 1967Rpm  
 540E PTO @1560 Rpm  
 1"3/8 -6 Spline PTO Shaft

### Wheel Equipment & Miscellaneous

Adjustable Radial Wheel Equipment  
 9.5R20 Front 340/85R28 Rear  
 Front Weight Frame  
 Dynamic Steering Fenders

### Operator Environment

Air Conditioned Cab  
 Digital Climate Control  
 Ergonomic Controls  
 Adjustable Steering Column  
 Analogue Dash  
 Mechanical Sprung Cloth Seat  
 MP3 Radio Player with Twin Speakers  
 Telescopic Mirrors  
 4 Cabin Work lights  
 2 Bonnet Front Work lights  
 Rotating Beacon

### Hyd/Linkage/Drawbar

Open Centre Hydraulic System  
 42 l/min Hyd Pump  
 Separate 17 L/min Steering Pump  
 2 Sets of Remotes - Spring  
 Mechanical Three Point Linkage  
 EASYLIFT Raise and Lower Switch  
 Position & Draft Control Settings  
 Cat 2 Ball ends  
 2500kg lift Capacity  
 Swinging Drawbar - CAT A

### Weights & Dimensions

Wheelbase	1976mm
Overall Length	3730mm
Total Weight	3050kg



### Engine

SDF 1000 Series Tier 3 Diesel Engine  
 4 Cyl/4000cc Turbocharged Intercooled  
 Liquid/Oil Cooled  
 Engine Speed Programming  
 Individual Bosch Injector Pumps  
 80Hp @ 2200 rpm (2005/25/CE)  
 Torque 325nm  
 Side Mounted Cabin Exhaust  
 70lt Fuel Capacity

### Transmission

30/15 Synchronmesh Gearbox  
 Forward/Reverse Synchro Shuttle  
 Shuttle mounted on Steering Column  
 Double Dry Heavy Duty 11" Clutch  
 Gear Levers Located Right Hand Side  
 Creep Gear Std  
 Heavy Duty Rear Axle  
 4 Wheel Independent Braking  
 Front Wheel Assist- Mechanical  
 Front & Rear Diff Lock- Mechanical  
 40 km/h Road Speed

### PTO

Independent Rear PTO  
 540/ 750 Speed PTO  
 540 PTO @ 1967Rpm  
 540E PTO @1560 Rpm  
 1"3/8 -6 Spline PTO shaft

### Wheel Equipment & Miscellaneous

Adjustable Radial Wheel Equipment  
 320/70R24 Front 420/85R30 Rear  
 Front Weight Frame  
 Dynamic Steering Fenders

### Operator Environment

Air Conditioned Cab  
 Digital Climate Control  
 Ergonomic Controls  
 Adjustable Steering Column  
 Analogue Dash  
 Mechanical Sprung Cloth Seat  
 MP3 Radio Player with Twin Speakers  
 Telescopic Mirrors  
 4 Cabin Work lights  
 2 Bonnet Front Work lights  
 Rotating Beacon

### Hyd/Linkage/Drawbar

Open Centre Hydraulic System  
 42 l/min Hyd Pump  
 Separate 17 L/min Steering Pump  
 3 Sets of Remotes  
 Spring/Detent on 2 sets / 1 Set Float  
 Mechanical Three Point Linkage  
 EASYLIFT Raise and Lower Switch  
 Position & Draft Control Settings  
 Cat 2 Ball Ends  
 3500kg Lift Capacity  
 Swinging Drawbar – CAT A

### Weights & Dimensions

Wheelbase	2106mm
Overall Length	3990mm
Total Weight	3250kg

# 4090.4E

## 4WD ROPS



### Engine

SDF 1000 Series Tier 3 Diesel Engine  
4 Cyl/4000cc Turbocharged Intercooled  
Liquid/Oil Cooled  
Engine speed programming  
Individual Bosch Injector Pumps  
85Hp @ 2200 rpm (2005/25/CE)  
Side mounted upswept exhaust – Tractor only  
Side mounted down swept exhaust – Tractor + FEL  
70lt Fuel Capacity

### Transmission

30/15 Synchronmesh Gearbox  
Forward/Reverse Synchro Shuttle  
Shuttle mounted on Steering Column  
Double Dry Heavy Duty 11" Clutch  
Gear Levers Located Right Hand Side  
Creep Gear Std  
Heavy Duty Rear Axle  
4 Wheel Independent Braking  
Front Wheel Assist- Mechanical  
Front & Rear Diff Lock- Mechanical  
40 km/h Road Speed

### PTO

Independent Rear PTO  
540/ 750 Speed PTO  
540 PTO @ 1967 Rpm  
540E PTO @1560 Rpm  
1"3/8 -6 Spline PTO Shaft

### Wheel Equipment & Miscellaneous

Adjustable Radial Wheel Equipment  
320/70R24 Front 420/85R30 Rear  
Front Weight Frame  
Dynamic Steering Fenders

### Operator Environment

2 Post ROP Frame  
Flat Floor ISO Mounted Platform  
Rubber Floor Mat  
Ergonomic Controls  
Telescopic and Tilting Steering Wheel  
Analogue Dash  
Deluxe PVC Mechanical Seat  
Sun Canopy  
Telescopic Mirrors  
1 Rear Work lights  
2 Bonnet Work lights  
Rotating Beacon

### Hyd/Linkage/Drawbar

Open Centre Hydraulic System  
42 l/min Hyd Pump  
Separate 17 L/min Steering Pump  
3 Sets of Remotes  
Spring/Detent on 2 sets / 1 Set Float  
Mechanical Three Point Linkage  
EASYLIFT raise and lower switch  
Position & draft control Settings  
Cat 2 Ball ends  
3500kg lift capacity  
Swinging Drawbar – CAT A

### Weights & Dimensions

Wheelbase	2106mm
Overall Length	3990mm
Total Weight	3100kg



# 4100.4E



## Engine

SDF 1000 Series Tier 3 Diesel Engine  
4 Cyl/4000cc Turbocharged Intercooled  
Liquid/Oil Cooled  
Engine Speed Programming  
Individual Bosch Injector Pumps  
95Hp @ 2200 rpm (2005/25/CE)  
Side Mounted Cabin Exhaust  
70lt Fuel Capacity

## Transmission

30/15 Synchronmesh Gearbox  
Forward/Reverse Synchro Shuttle  
Shuttle mounted on Steering Column  
Double Dry Heavy Duty 11" Clutch  
Gear Levers Located Right Hand Side  
Creep Gear Std  
Heavy Duty Rear Axle  
4 Wheel Independent Braking  
Front Wheel Assist- Mechanical  
Front & Rear Diff Lock- Mechanical  
40 km/h Road Speed

## PTO

Independent Rear PTO  
540/ 750 Speed PTO  
540 PTO @ 1967Rpm  
540E PTO @1560 Rpm  
1"3/8 -6 Spline PTO Shaft

## Wheel Equipment & Miscellaneous

Adjustable Radial Wheel Equipment  
320/70R24 Front 420/85R30 Rear  
Front Weight Frame  
Dynamic Steering Fenders

## Operator Environment

Air Conditioned Cab  
Digital Climate Control  
Ergonomic Controls  
Adjustable Steering Column  
Analogue Dash  
Mechanical Sprung Cloth Seat  
MP3 Radio Player with Twin Speakers  
Telescopic Mirrors  
4 Cabin Work lights  
2 Bonnet Front Work lights  
Rotating Beacon

## Hyd/Linkage/Drawbar

Open Centre Hydraulic System  
42 l/min Hyd Pump  
Separate 17 L/min Steering Pump  
3 Sets of Remotes  
Spring/Detent on 2 sets / 1 Set Float  
Mechanical Three Point Linkage  
EASYLIFT Raise and Lower Switch  
Position & Draft Control Settings  
Cat 2 Ball Ends  
3500kg Lift Capacity  
Swinging Drawbar – CAT A

## Weights & Dimensions

Wheelbase	2106mm
Overall Length	3990mm
Total Weight	3250kg