



5105.4G Heavy Duty



Engine

FARMotion Tier 4i Diesel Engine
4 Cyl/3849cc Turbocharged/Intercooled
Electronically Controlled
Emission Control by DOC Unit
Liquid/Oil Cooled with Fixed Fan
High pressure Diesel injection/common rail
102Hp Max hp @ 2200 rpm (2000/25/CE)
5Hp Power Boost
Torque 408 Nm @1600 rpm
Engine Speed Programming – 1 setting
Powercore Air Filter with Dust Ejectors
Side Vertical Exhaust
Fuel Tank 150 litres

Transmission

40/40 forward/reverse gears
Wet clutch Powershuttle
Shuttle modulation with 5 settings
5 speeds/4 Ranges / 2 stage Powershift
Comfort Clutch
Stop and Go function
Front Wheel Assist – Push Button
4 Wheel Independent Braking
100% Front & Rear Diff Lock - Push Button
40 km/h Road speed @ Super Economy RPM

PTO

Independent Wet Multidisc Clutch
4 Speed PTO 540/540E- 1000/1000E
Push Button Control in Cab/Rear fender
Auto PTO
Interchangeable PTO Spline Function
1" 3/8 – 6 Spline PTO shaft

Wheel Equipment & Miscellaneous

Adjustable Radial Wheel Equipment
420/70R24 Front -480/70R34 Rear Tyres
Front Weight Frame
12v elec. socket

Operator Environment

D2L Class Air Conditioned Cab
Super Deluxe Air Seat
Tilt and telescopic Steering Wheel
Hi Visibility Glass Roof
INFOCENTER Digital Display
MP3 Radio Player with Twin Speakers
Telescopic Mirrors
4 Cabin Work lights
2 Bonnet Front Work lights
Rotating Beacon

Hyd/Linkage/Drawbar

Open Centre Hydraulic System
55 L/min Hyd Pump
Separate 40L/min Steering Pump
3 Sets of Remotes -1 Kick out / 1 Detent / 1 Float
Flow Control on 1 Remote
Electronic Hitch with Position & Draft Control
Free flow return Line
External Raise & Lower on Rear Fenders
Cat 2 Hook ends-telescopic stabilisers
3600 kg lift capacity
Swinging Drawbar – CAT A

Weights & Dimensions

Wheelbase	2400 mm
Length	4270 mm
Total Height	2700mm
Total Weight	4300 kg

5125G Heavy Duty



Engine

FARMotion Tier 4i Diesel Engine
4 Cyl/3849cc Turbocharged/Intercooled
Electronically Controlled
Emission Control by DOC Unit
Liquid/Oil Cooled with Fixed Fan
High Pressure Diesel Injection/Common Rail
126 Max Hp @ 2200 rpm (2000/25/CE)
6 Hp Power Boost
Torque 500 Nm @1600 rpm
Engine Speed Programming × 2
Powercore Air Filter with Dust Ejectors
Side Vertical Exhaust
Fuel Tank 150 litres

Transmission

60/60 Forward/Reverse Gears
Sense Clutch Wet Clutch Powershuttle
Shuttle Modulation with 5 Settings
5 Speeds / 4 Ranges / 3 Stage Powershift
Speed Matching
Comfort Clutch
Stop and Go Function
Front Wheel Assist – Push Button
4 Wheel Independent Braking
100% Front & Rear Diff Lock - Push Button
40 km/h Road speed @ Super Economy RPM

PTO

Independent Wet Multidisc Clutch
4 Speed PTO 540/540E- 1000/1000E
Push Button Control in Cab/Rear Fender
Auto PTO
Interchangeable PTO Spline Function
1" 3/8 – 6 Spline PTO Shaft

Wheel Equipment & Miscellaneous

Fixed Fully Welded Radial Wheel Equipment
440/65R28 Front -540/65R38 Rear Tyres
Front Weight Frame
12v elec. socket and 7-pin ISO 11786 plug
Deutz-Fahr STOLL Loader Ready includes;
Subframe
Hydraulic Kit
Joystick with Powershift buttons
Electrical switches for loader operation

Operator Environment

D2L Class Air Conditioned Cab
Hydro Silent Block Cabin Suspension
Super Deluxe Air Seat
Tilt and Telescopic Steering Wheel
SDD Rapid Steering Circuit
Hi Visibility Polycarbonate FOPS Roof
INFOCENTER II Digital Display
MP3 Radio Player with Twin Speakers
Telescopic Mirrors
4 Cabin Work Lights
2 Bonnet Front Work Lights
2 Duplicate Headlights on Cab Post
2 Work lights on Cab Post
Rotating Beacon

Hyd/Linkage/Drawbar

90 L/min On Demand Hydraulic System
Separate 40L/min Steering Pump
3 Sets of Remotes - 3 Detent / 3 Float
Flow Control on All Valves
Electronic Hitch with Position & Draft Control
Free flow Return Line
External Raise & lower on Rear Fenders
Cat 2 Hook ends-telescopic stabilisers
5410 kg lift capacity with Assistor Rams
Swinging Drawbar – CAT A

Weights & Dimensions

Wheelbase	2400 mm
Length	4314 mm
Total Height	2730mm
Total Weight	4400kg