

AGROLUX 410

4WD ROPS

Engine

SDF 1000 Series Tier 3 Diesel Engine
4 Cyl/4000cc Turbo Intercooled
Liquid/Oil Cooled
Individual Bosch Injector Pumps
75Hp @ 2350 rpm (2005/25/CE)
Torque 285nm
Down Swept Exhaust
65lt Fuel Capacity

Transmission

15/15 Synchronmesh Gearbox
Forward/Reverse Synchro Shuttle
Double Dry Heavy Duty 12" Clutch
Gear Levers Located Right Hand Side
Heavy Duty Rear Axle
4 Wheel Independent Braking
Front Wheel Assist
Front & Rear Diff Lock
40 km/h Road Speed

PTO

Independent Rear PTO
540 Speed PTO
540 @ 1965 Rpm
1"3/8 -6 Spline PTO shaft

Operator Environment

2 Post Foldable ROPS Frame
Rubber Semi Platform
Left Rear Telescopic Mirror
Comfort PVC Seat
1 Rear Work light
2 Bonnet Lights with Hi/Lo Beam
Rotating Beacon



Hyd/Linkage/Drawbar

Open Centre Hydraulic System
42 l/min Hyd Pump
Separate 17 L/min Steering Pump
2 Sets of Remotes – 1 Detent / 1 Spring
Mechanical Three Point Linkage
Position & draft control Settings
Cat 2 Ball ends
3000 kg lift capacity
Swinging Drawbar – CAT A

Wheel Equipment

Fully Adjustable Wheels
11.2*24 Front -16.9*30 Rear Ply Tyres

Weights & Dimensions

Wheelbase	2015mm
Overall Length	3445mm
Total Weight	2900kg

April 2022

AGROLUX 95

4WD ROPS



Engine

SDF1000 Series Tier 1 Diesel Engine
4 Cyl/4000cc Turbocharged
Liquid/Oil Cooled
Individual Bosch Injection System
92Hp @ 2500 rpm (2005/25/CE)
Torque 288nm
Up Swept Side Exhaust
Air Cleaner with Cyclone Pre Cleaner
100lt Fuel Capacity

Transmission

20/20 Synchronmesh Gearbox
Heavy Duty Dry 13" Cerametallic Clutch
Forward/Reverse Synchro Shuttle
Gear Levers Located Right Hand Side
Creep Gear Std
Front Wheel Assist
4 Wheel Independent Braking
Front & Rear Diff Lock
40 km/h Road Speed

PTO

Independent Hydraulic Rear PTO
2 Speed PTO 540/1000

Operator Environment

2 Post Foldable ROPS Frame
Step Through Platform
Comfort PVC Seat
Sun Canopy
1 Rear Work Light
2 Bonnet Lights with Hi/Lo Beam

Hyd/Linkage/Drawbar

Open Centre Hydraulic System
56 l/min Hyd Pump
Separate 37 L/min Steering Pump
2 Sets of Remotes - 1 Detent/ 1 Spring
Mechanical Three Point Linkage
Position & Draft Control Settings
Cat 2 Ball Ends
4300kg lift Capacity
Swinging Drawbar - CAT A

Wheel Equipment

Adjustable Wheel Equipment
14.9R24 Front -18.4R30 Rear Radial Tyres

Weights & Dimensions

Wheelbase	2360mm
Overall Length	4075mm
Overall Height	2464mm
Total Weight	3200kg