

TECHNICAL SPECIFICATIONS - TILLER

TILLER	TR348
Article Number	970448601
Net power @ preset rpm	4.5kW @ 3300rpm
Engine manufacturer	Briggs & Stratton
Fuel tank capacity, litres	3.6
Cultivating width, cm	48
Working depth, cm	15
Rotational speed, rpm	103 - 207
Transmission	Chain / Gear
Speeds, forward / reverse	2 / 1
Weight, kg	73
Counter-rotating tines	-
Fold-down handlebar	-
Adjustable handlebar	•
Carry handles	-
Transport wheels	•
Drive wheel	•
OPTIONAL ACCESSORIES	
Ridger	
Ridger with metal wheels	
Tine de-thatcher	
Weeding tool	
Scarifier	
Edger	-

SOUND AND VIBRATION LEVELS

* Equivalent sound pressure level, as per ISO 22868, is calculated as the time-weighted energy sum for the sound pressure levels at various operational states. Typical variation for equivalent sound pressure level is a standard deviation of 1 dB(A).

TABLE KEY: • = Standard (•) = Optional - = Not applicable

** Equivalent vibration level, as per ISO 22867, is calculated as

the time-weighted energy sum for the vibration levels at various operational states. The data presented for equivalent vibration level has a typical variation (standard deviation) of 1 m / s².