

## TECHNICAL SPECIFICATIONS - ZERO TURNS

ZERO TURNS	Z246	Z146	Z242E	Z242E	Z242F	Z242F	Z248F	Z254F
Article Number	967665401	970458601	967665601	970458701	967665701	970458801	970458901	967681002
Engine	Kawasaki FR Series V-Twin	Kawasaki FR Series V-Twin	Kawasaki FR Series V-Twin	Kawasaki FR Series V-Twin	Kawasaki FR Series V-Twin	Kawasaki FR Series V-Twin	Kawasaki FR Series V-Twin	Kawasaki FR Series V-Twin
Engine type	Model FR600V	Model FR600V	Model FR651V	Model FR600V	Model FR651V	Model FR651V	Model FR691V	Model FR730V
Power, hp as rated by engine manufacturer	18.0	18	21.5	18	21.5	21.5	23	24.0
Cylinder displacement, cm <sup>3</sup>	603	603	726	603	726	726	726	726
Air filter	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Cutting width, inches	46	46	42	42	42	42	48	54
Adjustable cutting height, mm	38 - 102	38 - 102	38 - 102	38 - 102	38 - 102	38 - 102	38 - 102	39 - 102
Deck lift system	Hand-operated	Hand-operated	Hand-operated	Hand-operated	Hand-operated	Hand-operated	Hand-operated	Hand-operated
Anti-scalp wheels	3	3	-	-	-	-	2	4
Nose roller	-	-	•	•	•	•	•	-
Deck type	Reinforced Stamped	Reinforced Stamped	ClearCut™ Fab. 10 Ga.	ClearCut™ Fab. 10 Ga.	ClearCut™ Fab. 10 Ga.	ClearCut™ Fab. 10 Ga.	ClearCut™ Fab. 10 Ga.	ClearCut™ Fab. 10 Ga.
Number of cutting blades	2	2	2	2	2	2	3	3
Blade Spindle type	Cast aluminium	Cast aluminium	Cast aluminium	Cast iron	Cast iron	Cast iron	Cast iron	Cast iron
Electric clutch, ft/lb	-	-	-	-	-	-	-	-
Hydro pumps - wheel motors, cu.in./cc	EZT	EZT	EZT	EZT	EZT	EZT	EZT	EZT
Speed min, max (fwd / rev), km/h	0-10.5 / 0-5.6	0-10.5 / 0-5.6	0-10.5 / 0-5.6	0-10.5 / 0-5.6	0-10.5 / 0-5.6	0-10.5 / 0-5.6	0-10.5 / 0-5.6	0-10.5 / 0-5.6
Automatic Park Brake	•	•	•	•	•	•	•	•
Front caster tires, inches	11 x 6-5	11 x 4-5	11 x 4-5	11 x 4-5	11 x 6-5	11 x 6-5	11 x 6-5	11 x 6-5
Rear drive tires, inches	18 x 9.5-8	18 x 9.5-8	18 x 8.5-8	18 x 8.5-8	18 x 8.5-8	18 x 8.5-8	18 x 9.5-8	18 x 9.5-8
Fuel capacity, litres	13.25	13.25	13.25	13.25	13.25	13.25	13.25	13.2
Weight, kgs	263	263	263	263	263	263	269.89	290.2
Base machine width (chute up), cm	121.9	121.9	109.2	109.2	109.2	109.2	123.2	145.0
Base machine length/height, cm	190.5 / 101.6	190.5 / 101.6	190.5 / 101.6	190.5 / 101.6	190.5 / 101.6	190.5 / 101.6	190.5 / 101.6	190.5 / 101.6
Productivity, acres / hr*	2.4	2.4	2.2	2.2	2.2	2.2	2.5	2.8
Seat type	15" High-back	15" High-back	15" High-back	15" High-back	15" High-back with arm rests	Deluxe SK 15"(slide) with Armrest Kit	Deluxe SK 15"(slide) with Armrest Kit	15" High-back with arm rests
Digital hour meter	•	•	•	•	•	•	•	•
LED Headlights	•	Optional	Optional	Optional	•	•	•	•
Ergonomic, adjustable steering levers	•	•	•	•	•	•	•	•
Heavy-duty dampeners	-	-	-	-	-	-	-	-
Foldable ROPS	-	-	-	-	-	-	-	-
Drink holder	•	•	•	•	•	•	•	•
<b>ACCESSORIES</b>								
Mulch Kit	(•)	(•)	(•)	(•)	(•)	(•)	(•)	(•)
Collection system	(•)	(•)	(•)	(•)	(•)	(•)	(•)	(•)
Optional blades	(•)	(•)	(•)	(•)	(•)	(•)	(•)	(•)
Suspension seat	-	-	-	-	-	-	-	-

TABLE KEY: •= Standard (•)= Optional - = Not applicable

## TECHNICAL SPECIFICATIONS - ZERO TURNS

ZERO TURNS	Z254F	MZ48	MZ54	MZT61	Z554	Z560X	Z572X
Article Number	970459001	967665901	967696102	967177010	967669602	967669703	967669802
Engine	Kawasaki FR Series V-Twin	Kawasaki FR Series V-Twin	Kawasaki FR Series V-Twin	Kawasaki FS Series V-Twin	Kawasaki FX Series V-Twin	Kawasaki FX Series V-Twin	Kawasaki FX Series V-Twin
Engine type	Model FR730V	Model FR691V	Model FR730V	Model FS691V	Model FX751V	Model FX921V	Model FX921V
Power, hp as rated by engine manufacturer	24	23.0	24.0	23.0	24.5	31.0	31.0
Cylinder displacement, cm <sup>3</sup>	726	726	726	726	852	999	999
Air filter	Standard	Standard	Standard	Standard	Heavy-Duty Canister	Heavy-Duty Canister	Heavy-Duty Canister
Cutting width, inches	54	48	54	61	54	60	72
Adjustable cutting height, mm	39 - 102	38 - 102	38 - 114	38.1 - 114.3	25 - 127	25 - 127	25 - 127
Deck lift system	Hand-operated	Foot-activated	Foot-activated	Foot-activated	Foot-activated	Foot-activated	Foot-activated
Anti-scalp wheels	4	4	4	2	2	2	2
Nose roller	-	-	-	•	•	2	2
Deck type	ClearCut™ Fab. 10 Ga.	ClearCut™ Fab. 10 Ga.	ClearCut™ Fab. 10 Ga.	Fabricated 11 Ga.	Fabricated 10/7 Ga.	Fabricated 7 Ga.	Fabricated 7 Ga.
Number of cutting blades	3	3	3	3	3	3	3
Blade Spindle type	Cast iron	Cast iron	Cast iron	Cast iron	Commercial Cast aluminium	Cast iron	Cast iron
Electric clutch, ft/lb	-	90	90	200	150	250	250
Hydro pumps - wheel motors, cu.in. / cc	EZT	ZT3100	ZT3100	ZT3400	ZT4400	ZT5400	ZT5400
Speed min, max (fwd / rev), km/h	0-10.5 / 0-5.6	0-13.7 / 0-8.05	0-13.7 / 0-7.2	0-16.1 / 0-8.1	0-19.3 / 0-9.7	0-19.3 / 0-9.7	0-19.3 / 0-9.7
Automatic Park Brake	•	-	-	-	•	•	•
Front caster tires, inches	11 x 6-5	13 x 6.5-6	13 x 6.5-6	13 x 6.5-6	13 x 6.5-5	13 x 6.5-6 flat free	13 x 6.5-6 flat free
Rear drive tires, inches	18 x 9.5-8	22 x 10-10	22 x 10-10	23 x 10.5-12	23 x 10.5-12	24 x 12-12	24 x 12-12
Fuel capacity, litres	13.2	18.9	18.9	18.9	45.4	45.4	45.4
Weight, kgs	290.2	319.8	350.0	358.3	499.0	594.0	616.0
Base machine width (chute up), cm	145	123.2	145.0	158.2	145.0	162.0	199.0
Base machine length/height, cm	190.5 / 101.6	191.8 / 106.7	191.8 / 106.7	191.8 / 115.6	206 / 117	206 / 117	206 / 117
Productivity, acres / hr*	2.8	3.3	3.5	4.9	4.0-4.4	5.3 - 5.8	5.8 - 7.0
Seat type	Deluxe SK 15"(slide) - with Armrest Kit*	18" Premium High-back with arm rests	18" Premium High-back with arm rests	PZT Premium	Premium Heavy bolstered Non-suspension	Premium Heavy bolstered Full-suspension	Premium Heavy bolstered Full-suspension
Digital hour meter	•	•	•	•	•	•	•
LED Headlights	•	Optional	Optional	Optional	Optional	Optional	Optional
Ergonomic, adjustable steering levers	•	•	•	•	•	•	•
Heavy-duty dampeners	-	-	-	-	•	•	•
Foldable ROPS	-	•	•	•	•	•	•
Drink holder	•	•	•	•	•	•	•
<b>ACCESSORIES</b>							
Mulch Kit	(•)	(•)	(•)	(•)	(•)	(•)	(•)
Collection system	(•)	(•)	(•)	(•)	(•)	(•)	(•)
Optional blades	(•)	(•)	(•)	(•)	(•)	(•)	(•)
Suspension seat	-	-	-	-	(•)	•	•

TABLE KEY: •= Standard (•)= Optional - = Not applicable