



PRODUCT CATALOGUE.

# INDUSTRY LEADING WARRANTY



INCLUDES SPINDLES & GEARBOXES

EXPERIENCED SERVICE & SUPPORT NETWORK



# POWERS PERFORMANCE.

From humble beginnings in New Zealand, to a world leader in Commercial Mowing - our success is driven by a passion to help customers find a better way.

We listen to how you use our products, designing with customer focused innovation to solve problems you encounter. The result? Mowing solutions which increase productivity, reduce maintenance and can be relied on day-afterday, for years of full time commercial use.



LONG
COMMERCIAL LIFE.



LOW TOTAL-COST-OF-OWNERSHIP.



EASE OF MAINTENANCE.



INTUITIVE TO USE.



INDUSTRY LEADING CUT PRESENTATION.



SERVICE THAT EXCEEDS EXPECTATIONS.









STRIKER



PROCUT/S5



PROCUT/S5 SR



PROCUT/S5 FM



TOPPER/S3



STEALTH/S3



SNAKE/S2



STEALTH/S3 SR



PEGASUS S



**PEGASUS/S5 SR** 



X-WAM



FLAILDEK /FX



EZEEMOW/FX



**FORCE** 



WARLORD/S3

FLAIL MOWERS.

ROTARY MOWERS.



## TRIMAX STRIKER

Trimax STRIKER is a multi-spindled rotary mower with extremely low maintenance requirements and is ideal for use on compact tractors.

The Trimax Striker is designed to give a high cut quality and an excellent spread of clippings. Highly versatile, the Striker is capable of mowing grass 10 to 100mm. With an enclosed cutting chamber and a downward rear dispersion of clippings, the Striker has surpassed international safety standards making it one of the safest mowers on the market for use in public spaces.

Fitted with Trimax's exclusive LazerBladez™, the Striker can produce a cut and finish to rival that of a cylinder mower and is ideal for educational and sports facilities where presentation is key!

TALK TO US TODAY ABOUT THE CAPABILITIES OF **STRIKER** IN YOUR ENVIRONMENT.







SPECIFICATIONS	150	190
Cutting Width	1.46m (4' 9½")	1.94m (6' 4½")
Overall Width	1.56m (5' 1½")	2.04m (6' 8½")
Overall Length	1.16m (3' 9½")	1.16m (3' 9½")
Height	0.83m (2' 8½")	0.83m (2' 8½")
Cut Height Range	10 - 100mm (¾" - 4")	10 - 100mm (¾" - 4")
No. of Blade Spindles	3	4
Approx. Weight	322kg (710lbs)	400kg (882lbs)
Min PTO Output	25hp	30hp

<sup>\*</sup>Minimum PTO output is a guide only. Requirement varies with the type of work and the terrain



The Striker has been built to withstand all conditions, a good solid mower. We had a test mow on delivery, the grass was about 150mm high and wet, it went great, made a good even cut leaving an even spread of cut grass, we thought it was the best mower we had ever seen. IAN DUFTY | Morrinsville, NZ

## KEY APPLICATIONS.

▼ School & Sports Fields ▼ Golf & Country Club ▼ Lifestyle & Estates

## WHAT'S NEW ON STRIKER

The Striker was originally designed as a compact solution for sports turf, especially for grounds maintenance for local football and cricket clubs. It features a simpler pan construction than the ProCut and includes maintenance-free ball bearing spindles.



## **PRODUCT** FEATURES.



**LOW COST OF OWNERSHIP** With only 4 grease points on the mower and with robust sealed spindles, the Trimax Striker has incredibly low maintenance requirements.



**SAFETY FOR PUBLIC PLACES** Striker exceeds international safety standards, and can be used with confidence in public spaces, school sports fields and confined



**LAZERBLADEZ™** Available in uplift and flat formation to suit mowing requirements, the unique tilt forward design minimises hang back in tough conditions.



**ADVANCED ENGINEERING** Trimax's meticulous design process manufacturing technologies produce the most accurate rotary



**STRIPING CAPABLE** Fitted with full width front and rear rollers, the Striker can produce striped patterned turf for those spaces where presentation is key.



**COMPACT TRACTOR SUITABLE** Able to be paired with tractors as combined with bespoke, innovative low as 25hp, the Striker is perfect for smaller budgets and compact tractors.

## \*OPTIONAL FEATURES.

## **▼ ROLLER SCRAPERS**

Cleans rollers and reduces clumping in wet conditions.

**✓ NEXABLADES** 

Scientifically designed for high-end turf giving a superior cut and spread when it matters most.





## **TRIMAX** PROCUT/S5

A highly versatile roller mower, the PROCUT SERIES 5 is a multi-spindled roller mower designed to give a high cut quality and a great spread of clippings.

The ProCut has been a successful part of the Trimax range for over 30 years. Mowing parks, reserves, school grounds, sports fields and golf courses around the world - From the grounds of Windsor Castle to your local community sports fields.

The ProCut Series 5, released in 2023 is excellence refined. The Procut S5 builds on the market leading cut and spread quality of the previous series whilst removing all daily maintenance requirements making it the perfect solution for a variety of commercial environments.

TALK TO US TODAY ABOUT THE CAPABILITIES OF PROCUT SERIES 5 IN YOUR ENVIRONMENT.







SPECIFICATIONS	178	210	237	290
Cutting Width	1.74m (5′ 8 ½″)	2.06m (6' 9")	2.32m (7' 7")	2.89m (9' 6")
Overall Width	1.89m (6′ 2 ½″)	2.21m (7' 3")	2.47m (8′ 1″)	3.04m (10')
Overall Length	1.44m (4' 9")	1.51m (4' 11 ½")	1.44m (4' 9")	1.44m (4' 9")
Height	1.08m (3′ 6 ½″)	1.08m (3′ 6 ½″)	1.08m (3′ 6 ½″)	1.08m (3′ 6 ½″)
Cut Height Range	10 - 110mm (¾" - 4 ⅓")	10 - 110mm ( <sup>3</sup> / <sub>8</sub> " - 4 <sup>1</sup> / <sub>3</sub> ")	10 - 110mm ( <sup>3</sup> / <sub>8</sub> " - 4 <sup>1</sup> / <sub>3</sub> ")	10 - 110mm ( <sup>3</sup> / <sub>8</sub> " - 4 <sup>1</sup> / <sub>3</sub> ")
No. of Blade Spindles	3	3	4	5
Approx. Weight	492kg (1085lbs)	543kg (1197lbs)	605kg (1334lbs)	707kg (1559lbs)
Min PTO Output	35hp	40hp	45hp	55hp

<sup>\*</sup>Minimum PTO output is a guide only. Requirement varies with the type of work and the terrain



The ProCut is a great mower. I mow 19 schools at 40mm and the schools always comment on how nice the grounds look. I mow fast and the spread is great. I'd recommend Trimax to anyone!

ALLEN COE | Schools Contractor, NZ

## KEY APPLICATIONS.

✓ Municipal & Contractors ✓ School & Sports Fields ✓ Turf ✓ Golf & Country Clubs ✓ Lifestyle & Estates

## WHAT'S NEW ON PROCUT/S5

Maintaining your mower has never been easier with all daily greasing requirements being removed with the implementation of the new Titan Roller Bearings. The new auto-belt tensioning system reduces belt maintenance and improves drive to the spindles for a cleaner, more consistent cut in heavy conditions.



## PRODUCT FEATURES.



TITAN ROLLER BEARING SYSTEM The Trimax Titan roller bearing system is maintenance-free. requiring no regular greasing, and provides excellent retention.



**AUTOMATIC BELT TENSIONING** Removes the need for belt adjustments and improves drive to the spindles and blades.



Available in uplift and flat formation to suit mowing requirements, the unique tilt forward design minimises tensioning are maintenance-free. hang back in tough conditions.



**LOW MAINTENANCE** 

Zero daily maintenance. Spindles, roller bearings and auto-belt



STEADFAST SEALED SPINDLES We've eliminated the tedious

task of regular greasing. Covered by our 3-year warranty, maintenance costs are reduced, and productivity is enhanced.



**FULL WIDTH ROLLERS** 

Full width rollers minimise scalping in undulating conditions and allow mowing over kerbsides and bunkers. Also aids in striping.



BELT CAVITY DUAL WASH FLAPS

Provides easy access for removal of grass and drainage of water from helt chamber.



**ACCURATE SPINDLE SETTING TECHNOLOGY** 

Spindle height is perfectly aligned providing the most accurate cut possible.



## PRECISE HEIGHT ADJUSTMENT

alterations.



Enables safe and easy access



Clearly displayed indicators in both metric and imperial units and a high-tensile 2mm pitch adjuster for precise cut height



## STAND ON COVERS

to the rear of the tractor when coupling the mower. Quick release latches allow easy removal for cleaning and servicing.



## **✓ ANTI-BOUNCE / WEAR SKIDS**

Eliminates scalping and bouncing and reduces side channel wear.

## **✓** ROLLER SCRAPERS

Cleans rollers and reduces clumping in wet conditions.

## **✓ LIGHTING KIT WITH** STORAGE BRACKET

LED road lights, safety triangle, and bracket for storage box.

## **✓ STORAGE BOX**

Easy access to spare parts and tools. **✓ FRONT MOUNT** 

Convenient visibility. Only for tractors with front PTO drive.

## **✓ SINGLE ROLLER**

Allows greater grass intake at the front of the mower.

**✓** GALVANIZED SURFACE COATING Protect against corrosion in harsh environments.

## **✓ QUATTRO BLADES**

Four blades (flat, upturned or mixed) per spindle for a finer cut.

## **✓ NEXABLADES**

Scientifically designed for high-end turf giving a superior cut and spread when it matters most.

**✓** ON CALL KIT

Each kit contains bearings blades and belts for a quick replacement in the field.



## TRIMAX PROCUT/S5 SR

The original ProCut found phenomenal success in long grass applications due to its rigid construction, cut quality and manoeuvrability. With the ProCut S5 we have taken this to another level.

The Single Roller ProCut S5 is a long grass mower that provides a market leading cut and finish. Engineered with a low body profile and increased under deck clearance it provides excellent clipping distribution without any daily maintenance requirements.

Built with industry leading strength and durability, this is the machine you need for any commerical long grass applications.



The ProCut is over and above what we ever expected. We knew we needed more than just a slasher, the fine cut and even dispersion of the ProCut leaves

DALE COOK | Copelands Estate, Warragul, VIC, AUSTRALIA





ENVIRONMENTS.

SPECIFICATIONS	178	210	237	290
<b>Cutting Width</b>	1.74m (5' 8 ½")	2.06m (6' 9")	2.32m (7' 7")	2.89m (9' 6")
Overall Width	1.91m (6' 3")	2.22m (7' 3 ½")	2.48m (8'1½")	3.05m (10' ½")
Overall Length	1.36m (4' 5")	1.43m (4' 8")	1.36m (4' 5")	1.36m (4' 5")
Height	1.08m (3' 6 ½")	1.08m (3' 6 ½")	1.08m (3′ 6 ½″)	1.08m (3' 6 ½")
Cut Height Range	10 - 110mm (¾" - 4 ¼")	10 - 110mm (¾" - 4 ⅓")	10 - 110mm (¾" - 4 ⅓")	10 - 110mm (¾" - 4 ¼")
No. of Blade Spindles	3	3	4	5
Approx. Weight	462kg (1019lbs)	509kg (1122lbs)	568kg (1252lbs)	663kg (1462lbs)
Min PTO Output	35hp	40hp	45hp	55hp

## \*Minimum PTO output is a guide only. Requirement varies with the type of work and the terrain

## KEY APPLICATIONS.

✓ Horticulture ✓ Municipal & Contractors ✓ Aviation ✓ Racecourses ✓ Lifestyle & Estates

## WHAT'S NEW ON PROCUT/S5 SR

Maintaining your mower has never been easier with all daily greasing requirements being removed with the implementation of the new Titan Roller Bearings. The new auto-belt tensioning system reduces belt maintenance and improves drive to the spindles for a cleaner, more consistent cut in heavy conditions.



## **PRODUCT** FEATURES.



TITAN ROLLER BEARING SYSTEM The Trimax Titan roller bearing system is maintenance-free. requiring no regular greasing, and provides excellent retention.



AUTOMATIC BELT TENSIONING Removes the need for belt adjustments and improves drive to the spindles and blades.



Available in uplift and flat formation to suit mowing requirements, the unique tilt forward design minimises tensioning are maintenance-free. hang back in tough conditions.



**LOW MAINTENANCE** Zero daily maintenance. Spindles, roller bearings and auto-belt

\*OPTIONAL FEATURES.

wet conditions.

environments.

**✓** ON CALL KIT

**✓ STORAGE BOX** 

**▼** REAR ROLLER SCRAPER Cleans rollers and reduces clumping in

**✓ STORAGE & LIGHTING KIT** 

safety triangle to mower.

Mounts toolbox, LED road lights and

**✓ GALVANIZED SURFACE COATING** 

Each kit contains bearings blades and

belts for a quick replacement in the

Easy access to spare parts and tools.

Protect against corrosion in harsh



STEADFAST SEALED SPINDLES We've eliminated the tedious task of regular greasing. Covered by our 3-year warranty, maintenance costs are reduced, and productivity is enhanced.

**FULL WIDTH ROLLER** 

and aids in striping.

Full width roller minimises

scalping in undulating conditions



BELT CAVITY DUAL WASH FLAPS Provides easy access for removal of grass and drainage of water from belt chamber.

**ACCURATE SPINDLE SETTING** 

Spindle height is perfectly aligned

providing the most accurate cut

**TECHNOLOGY** 

possible.



Clearly displayed indicators in both metric and imperial units and a high-tensile 2mm pitch adjuster for precise cut height alterations.



PRECISE HEIGHT ADJUSTMENT



Enables safe and easy access coupling the mower. Quick release



## STAND ON COVERS

to the rear of the tractor when latches allow easy removal for cleaning and servicing.



## TRIMAX PROCUT/S5 FM

The front mounted version of the ever-popular rear linkage mounted Trimax PROCUT.

The Trimax ProCut FM is a robust machine engineered to withstand everyday use in the toughest commercial environments yet will deliver a clean cut - every time. In operation, the front-mounted ProCut Series 5 rides on the ground on its front wheels and rear roller. The front castor wheels and rear roller follow ground contours allowing easy manoeuvrability and prevent scalping. With out-front mowing the need for the operator to look behind is reduced and the tractor wheels do not flatten the uncut grass.







SPECIFICATIONS	178	210	237	290
<b>Cutting Width</b>	1.74m (5′ 8 ½″)	2.06m (6' 9")	2.32m (7' 7")	2.89m (9' 6")
Overall Width	1.91m (6' 3")	2.22m (7′ 3 ½″)	2.48m (8′ 1½″)	3.05m (10′ ½″)
Overall Length	1.65m (5' 5")	1.72m (5' 8")	1.65m (5' 5")	1.65m (5' ½")
Height	1.08m (3′ 6 ½″)			
Cut Height Range	10 - 110mm (¾" - 4 ¼")	10 - 110mm (¾" - 4 ⅓")	10 - 110mm (¾" - 4 ⅓")	10 - 110mm (¾" - 4 ¼")
No. of Blade Spindles	3	3	4	5
Approx. Weight	569kg (1254lbs)	616kg (1358lbs)	675kg (1488lbs)	770kg (1697lbs)
Min PTO Output	35hp	40hp	45hp	55hp

<sup>\*</sup>Minimum PTO output is a guide only. Requirement varies with the type of work and the terrain

## KEY APPLICATIONS.

- ✓ Municipal & Contractors
  ✓ School & Sport Fields
  ✓ Golf & Country Clubs
  ✓ Horticulture
- ✓ Aviation ✓ Racecourses

## WHAT'S NEW ON PROCUT/S5 FM

Maintaining your mower has never been easier with all daily greasing requirements being removed with the implementation of the new Titan Roller Bearings. The new auto-belt tensioning system reduces belt maintenance and improves drive to the spindles for a cleaner, more consistent cut in heavy conditions.

## **PRODUCT** FEATURES.



TITAN ROLLER BEARING SYSTEM The Trimax Titan roller bearing system is maintenance-free. requiring no regular greasing, and provides excellent retention.



AUTOMATIC BELT TENSIONING Removes the need for belt adjustments and improves drive to the spindles and blades.



LAZERBLADEZ™ Available in uplift and flat formation to suit mowing requirements, the unique tilt forward design minimises hang

back in tough conditions.

PRECISE HEIGHT ADJUSTMENT

Clearly displayed indicators in

both metric and imperial units

and a high-tensile 2mm pitch

adjuster for precise cut height



**LOW MAINTENANCE** 

Zero daily maintenance. Spindles, roller bearings and auto-belt tensioning are maintenance-free.

## \*OPTIONAL FEATURES.

## **▼ REAR MOUNT**

Available in rear three-point linkage configuration with front and rear rollers for unmatched safety.

### **▼** ROLLER SCRAPERS

Cleans rollers and reduces clumping in wet conditions.

**✓ QUATTRO BLADES** 

Four blades (flat, upturned or mixed) per spindle for a finer cut.

### **✓ NEXABLADES**

Scientifically designed for high-end turf giving a superior cut and spread when it matters most.

## **✓ ON CALL KIT**

Each kit contains bearings blades and belts for a quick replacement in the field.



belt chamber.



## STEADFAST SEALED SPINDLES

We've eliminated the tedious task of regular greasing. Covered by our 3-year warranty, maintenance costs are reduced, and productivity is enhanced.



## **FULL WIDTH ROLLER** Full width roller minimises

scalping in undulating conditions and aids in striping.



BELT CAVITY DUAL WASH FLAPS

Provides easy access for removal of

grass and drainage of water from

## **ACCURATE SPINDLE SETTING TECHNOLOGY**

Spindle height is perfectly aligned providing the most accurate cut possible.



## STAND ON COVERS

alterations.

Enables safe and easy access to the rear of the tractor when coupling the mower. Quick release latches allow easy removal for cleaning and servicing.



TALK TO US TODAY ABOUT THE CAPABILITIES OF PROCUT SERIES 5 FM IN YOUR ENVIRONMENT.



## TRIMAX TOPPER/S3

The Trimax TOPPER cuts pasture quickly and efficiently and has multiple features enabling its use on lower hp tractors.

Developed on a New Zealand dairy farm in 1993, the Topper uses small diameter blades turning at high speed resulting in more cuts per forward metre than comparable pasture toppers, giving a finer cut and increasing regrowth and pasture quality. The high under-body clearance and open deck design allows good flow of grass into the mowing deck and a clean ejection of cut grass.

Powered by a proven belt drive system that now has auto belt tensioners, the Trimax Topper is more efficient than comparable shaft drive pasture toppers. Short in body from front to rear and mounting close to the tractor, the Topper is able to be used on smaller tractors for large cut widths and also enables a smaller turning radius for easier access into tight corners.

TALK TO US TODAY ABOUT THE CAPABILITIES OF TOPPER SERIES 3 IN YOUR ENVIRONMENT.







SPECIFICATIONS	237	282
Cutting Width	2.32m	2.74m
Overall Width	2.48m	2.91m
Overall Length	1.32m	1.39m
Height	0.99m	0.99m
Cut Height Range	20 - 160mm	20 - 160mm
No. of Blade Spindles	4	4
Approx. Weight	643kg	685kg
Min PTO Output	37hp	45hp
**************************************	d t . D	that are a few along the same to

\*Minimum PTO Output is a guide only. Requirement varies with the type of work and the terrain.



We love the simplicity of the Topper and it does a beautiful job! The lightness of the machine enables us to utilise our compact tractor fully and swap between implements and we like that it's belt driven, it's so much easier to

PETER TERSGASKIS | Dairy Farmer, Shepparton VIC

## KEY APPLICATIONS.

✓ Dairy Farms
✓ Agriculture
✓ Aviation
✓ Racecourses

## WHAT'S NEW **ON TOPPER**

The Topper is now fitted with an automatic belt tensioning system improving its performance in heavy conditions. Stand on covers bring added durability whilst providing safe and easy access to the rear of a tractor when coupling.

## THE BENEFITS OF PASTURE TOPPING.

✓ Improves feed quality
✓ Increases farm profitability
✓ Increases MS production
✓ Promotes faster re-growth

## **PRODUCT** FEATURES.



**EASIER MAINTENANCE** 

New latch system provides easier access to drive system and access to roller bearing grease nipple has been improved.



## LOW HP REQUIREMENTS

Open deck design for grass processing, efficient belt drive system and a short mower front to rear allows for use on lower HP tractors.



### ANTI-BLOCK SYSTEM

High tensile spindles feature antiwrap pins preventing frustrating blockages around spindles in extreme conditions.



## **AUTOMATIC BELT TENSIONER** Eliminates the need for belt

adjustments and improves drive to the spindles and blades in longer grass.



## LAZERBLADEZ™

Available in uplift and flat formation to suit mowing requirements, the unique tilt forward design minimises hang back in tough conditions.



## IMPROVES FEED OUALITY

Topping controls poor quality pasture components such as seedheads and thistles and prevents their reoccurance.



## STAND ON BELT COVERS

Provides safe and easy access to the rear of tractor when coupling.



INCLUDES SPINDLES

EXPERIENCED SERVICE

## **ACCURATE HEIGHT SYSTEM**

Height indicators are clearly displayed allowing for accurate and easy in field height adjustments



## ADVANCED DESIGN

Short front to rear and mounting close to the tractor allowing better manoeuvrability. High under body clearance and open deck design for increased grass production.



resulting in clean cut pasture.



## **REAR ROLLER**

The Topper is fitted with a rear roller, which ensures that in undulating environments you'll have increased protection from scalping.







## TRIMAX STEALTH S3

The STEALTH SERIES 3 has been designed to give a higher quality of cut, operate in a wider range of conditions, be safer, more robust, easier to operate and take less time to maintain than any previous STEALTH.

Backed by 30 years' of experience in market, the concept of Stealth Series 3 was born from the demand of our Australian customers for a mower that was more versatile in terms of long grass performance and more user friendly for both the operator and the workshop.

Backed by our industry leading 3-year warranty and our parts and technical support team, we know the Stealth Series 3 to be the best linkage wing mower for passive and active turf in the market.

TALK TO US TODAY ABOUT THE CAPABILITIES OF STEALTH SERIES 3 IN YOUR ENVIRONMENT.

## **SPECIFICATIONS** 340 **Cutting Width** 3.4m (11' 2") **Overall Width** 3.55m (11' 8") 2.42m (7' 11") **Transport Width Overall Length** 1.63m (5' 4") Height (wings up) 1.21m (3' 11½") **Cut Height Range** 10 - 90mm ( $\frac{3}{8}$ " - 3 $\frac{1}{2}$ ") No. of Blade Spindles 5 Approx. Weight 940kg (2070lbs) Min PTO Output 70hp \*Minimum PTO output is a guide only. Requirement varies with the type of work and the terrain

## The Stealth has brilliant decks with excellent grass dispersion and minimal greasing required. We can just jump in and cut grass!

ROSS HAMNER | Downer, Auckland, NZ

## KEY APPLICATIONS.

✓ Municipal & Contractors
✓ School & Sports Fields
✓ Racecourses
✓ Aviation
✓ Lifestyle & Estates

## WHAT'S NEW ON STEALTH S3

We've reduced the need for greasing through the introduction of new features such as SteadFast maintenancefree spindles and composite maintenance-free bushes. Stealth wing locks can now be operated from inside the tractor cab. Modifications have been made to the cutting chamber and the baffle design for improved cut quality and easy cleaning.

## **PRODUCT** FEATURES.



### LOCTEK

A stubless roller bearing system for vastly improved roller retention, alignment, bearing life and minimal



## **GREATER MOWING VERSATILITY**

The improved cutting chamber and baffle design directs airflow from the blades out and over the rear roller for a better cut and spread.



### **ANTI-WEAR SKIDS**

Anti-wear skids reduce wear on side channels when operating in rough or uneven terrain.



## **LOW MAINTENANCE**

Reduced greasing requirements mean operators can spend more time mowing and less on maintenance.



## **EASY TO CLEAN**

The improved belt chamber design results in easy cleaning, with the front openings allowing any grass to be easily washed out or removed.



## IN-CAB UNLOCK SYSTEM

Remote unlock operates the mower wing locks with the push of a button from within the tractor cab. Electric or hydraulic actuation is available.



## LAZERBLADEZ"

Available in up-lift and flat formation to suit mowing requirements, the unique tilt forward design minimises hang back in tough conditions.



## **EASY HEIGHT ADJUSTMENT**

Clearly displayed stainless steel height environments. indicators allow the easy adjustment of cut heights without having to raise Upgrade to electric actuation for the or lower the wings and deck.



Enables safe and easy access to the rear of the tractor when coupling to the mower. Quick release latches allow easy removal for cleaning and servicing.

## \*OPTIONAL FEATURES.

### **▼** ROLLER SCRAPERS

Cleans rollers and reduces clumping in wet conditions.

## **✓ INDIVIDUAL WING LIFT**

Individual wing lift allows independent lift of either side deck for reduced cutting in confined

### **✓ QUATTRO BLADES**

Four blades (flat, upturned or mixed) per spindle for a finer cut.

## ✓ SERVICE STANDS

Lockable stands for safe underside access.

## **✓ LIGHTING KIT WITH** STORAGE BRACKET

LED road lights, safety triangle, and bracket for storage box.

### ✓ STORAGE BOX

Easy access to spare parts and tools.

## **✓ GALVANIZED SURFACE COATING**

Protect against corrosion in harsh

## **✓ ELECTRIC UNLOCK**

mower wings' transport lock.





# TRIMAX STEALTH/SR

The Trimax STEALTH SR combines the cut quality, safety, robustness, decreased maintenance time, and easy operation of STEALTH SERIES 3 with enhanced performance in long grass.

With even more versatility than the Stealth Series 3 for long grass applications, the Stealth SR is purpose-built for an excellent cut for grass up to 500mm. The cutting chamber and baffle design are optimised to provide a better finish and spread at higher cut heights.

New and improved design features make the Stealth SR safer, more operator friendly, and easier to maintain than ever

TALK TO US TODAY ABOUT THE CAPABILITIES OF **STEALTH SR** IN YOUR ENVIRONMENT.







340
3.4m (11' 2")
3.55m (11' 8")
2.42m (7' 11")
1.63m (5' 4")
1.21m (3' 11½")
40 - 90mm (1½" - 3½")
5
900kg (1984lbs)
60hp

 $<sup>\</sup>hbox{*Minimum PTO output is a guide only. Requirement varies with the type of work and the terrain}$ 

## KEY APPLICATIONS.

- ✓ Passive Turf & Open Space ✓ Municipal & Contractors ✓ Racecourses ✓ Aviation
- → Horticulture → Lifestyle & Estates

## WHAT'S NEW ON STEALTH/SR

The Stealth SR incorporates all the new features of the Stealth S3. An anti-scalp roller on the front of the main mowing deck and bubble rollers on the wings are added to protect against scalping over contours.



## PRODUCT FEATURES.



## LOCTEK

A stubless roller bearing system for vastly improved roller retention, alignment, bearing life and minimal



## ANTI-SCALP ROLLER

A raised front roller provides anti-scalp protection for your turf without impacting long grass performance.



## IN-CAB UNLOCK SYSTEM

Unlock the mower wings' transport lock from the convenience of the tractor seat using the tractor's hydraulic control lever.



#### LONG GRASS PERFORMANCE

Designed to mow grass up to 500mm high and achieve the quality cut you expect from Trimax.



## **EASY TO CLEAN**

The improved belt chamber design results in easy cleaning, with the front openings allowing any grass to be easily washed out or removed.



## LOW MAINTENANCE

Reduced greasing requirements mean operators can spend more time mowing and less on maintenance.



#### LAZERBLADEZ

Available in up-lift and flat formation to suit mowing requirements, the unique tilt forward design minimises hang back in tough conditions.



## **EASY HEIGHT ADJUSTMENT**

Clearly displayed stainless steel height mower wings' transport lock. indicators allow the easy adjustment of cut heights without having to raise or lower the wings and deck.



## STAND ON COVERS

Enables safe and easy access to the rear of the tractor when coupling to the mower. Quick release latches allow easy removal for cleaning and servicing.

## \*OPTIONAL FEATURES.

## **▼** ROLLER SCRAPERS

Cleans rollers and reduces clumping in wet conditions.

## **✓ INDIVIDUAL WING LIFT**

Individual wing lift allows independent lift of either side deck for reduced cutting in confined

## **✓ SERVICE STANDS**

Lockable stands for safe underside access.

## ✓ LIGHTING KIT WITH STORAGE BRACKET

LED road lights, safety triangle, and bracket for storage box.

V STORAGE BOX

Easy access to spare parts and

## **✓** GALVANIZED SURFACE COATING

Protect against corrosion in harsh environments.

## **✓ ELECTRIC UNLOCK**

Upgrade to electric actuation for the mower wings' transport lock.





The Trimax SNAKE is used on some of the most prestigious golf courses around the world. The cutting system has been studied by the Sports Turf Institute of New Zealand and declared to produce a cut of equal quality to cylinder mowers however with the versatility and reliability of our famous rotary design.

SNAKE/S2

An accumulation of over 40 years of Trimax innovation, engineering and customer insight, the Snake has been designed specifically for sports turf and golf courses. We've seamlessly combined our world class cut quality and articulation capabilities and believe we've created the best sports turf rotary mower in the world. Built for agility, incredibly robust and extremely low maintenance the Trimax Snake won't fail to impress.

TALK TO US TODAY ABOUT THE CAPABILITIES OF SNAKE SERIES 2 IN YOUR ENVIRONMENT.

#### **SPECIFICATIONS** 400 **Cutting Width** 3.23m (10'7") 3.99m (13'1") **Overall Width** 3.37m (11'1") 4.11m (13' 6") **Overall Length** 3.5m (11' 6") 3.5m (11' 6") **Transport Width** 2.1m (6' 101/2") 2.14m (7' 1/4") **Transport Height** 1.82m (5' 111/2") 2.21m (7' 31/2") **Cut Height Range** 10 - 100mm (<sup>3</sup>/<sub>8</sub>" - 4") 10 - 100mm (<sup>3</sup>/<sub>8</sub>" - 4") No. of Blade Spindles 9 11 Approx. Weight 1250kg (2756lbs) 1390kg (3064lbs) Min PTO Output 45hp 35hp

<sup>\*</sup>Minimum PTO output is a guide only. Requirement varies with the type of work and the terrain



The first time I saw the Snake cut the grass I was really impressed at the speed and the striping finish. I'd recommend the Snake to anyone. ROY | Head Groundsman, Hampton Downs, NZ

## KEY APPLICATIONS.

- ✓ Golf Courses (Roughs & Fairways)
  ✓ School & Sports Fields
  ✓ Municipal & Contractors
- ✓ Turf ✓ Lifestyle & Estates

## WHAT'S NEW ON SNAKE S2

The Snake Series 2 includes the new Trimax LocTEK stubless roller bearing retention system. The roller thickness has been increased to 5mm. The Snake now features replaceable axle stubs, a 90-degree rotatable jack stand, and maintenance-free pivot bushes.

## PRODUCT FEATURES.



#### LOCTEK

A stubless roller bearing system for vastly improved roller retention. alignment, bearing life and minimal



### **FULL WIDTH ROLLERS**

Full width rollers minimise scalping in undulating conditions and allow mowing over kerbsides and bunkers. Also aides in striping.



## **ZERO TURN**

Allows continuous cutting while turning sharply for maximum productivity.



#### AUTOMATIC BELT TENSIONERS

Automatic belt tensioners eliminate the need for belt adjustments and improves drive to the spindles and blades.



### **QUIKLIFT**

QuikLIFT enables decks to be raised slightly for traversing paths without the need to disengage the PTO. Also aides in striping.



## ARTICULATION ABILITY

With three articulating decks the Snake has the ability to follow contours.



Available in uplift and flat formation to suit mowing requirements, the unique tilt forward design minimises hang back in tough conditions.



### **EASY HEIGHT ADJUSTMENT**

Clearly displayed stainless steel height indicators allow the easy adjustment of cut heights without having to raise or lower the decks.



## LOW MAINTENANCE

SteadFast sealed spindles have eliminated the tedious task of regular greasing. Snake Series 2 now also features maintenance free pivot bushes.

## \*OPTIONAL FEATURES.

**✓ ANTI-BOUNCE / WEAR SKIDS** Eliminates scalping and bouncing and reduces side channel wear.

**▼** ROLLER SCRAPERS Cleans rollers and reduces clumping in wet conditions.

## **✓ MULTI LIFT SYSTEM**

Five different lift functions for mower decks. Now with Drive Protect.

## **▼** ROAD RATED TYRE

Tow at highway speeds on the road. **✓ ELECTRIC UNLOCK** 

Unlocks decks electronically or hydraulically from the tractor seat. **✓** MUDGUARDS, LIGHTS, & CHAINS Add LED tail light clusters, safety chains, and transport wheel mudguards for increased safety during road transportation. **✓** MULCH KIT

Save on purchasing dedicated leaf blowing and collection units with the Snake Mulch Kit. Retrofittable to existing Snake S1 & S2 models. **✓ NEXABLADES** 

Scientifically designed for high-end turf giving a superior cut and spread when it matters most.



✓ Municipal & Contractors
✓ Turf
✓ Racecourses
✓ Polo
✓ School & Sport Fields

## WHAT'S NEW ON PEGASUS S5

The Pegasus chassis and outrigger arms have been completely redesigned to increase strength without adding unnecessary weight. Larger wheels decrease ground pressure and support a wider range of tyre options. Maintenance-free features have been introduced.



## PRODUCT FEATURES.



### **ROBUST CHASSIS**

10% stronger under tough travel conditions, twice the durability in deck lifting and lowering, and a 60% increase in rigidity in the outrigger arms from Pegasus S4.



## IMPACT PROTECTION

Outrigger arms and side channel leading edges have been redesigned for increased impact protection.



## SUSPENSION

The new Pegasus S5 Flexiride Torque Suspension System is designed for increased strength and smoother travel at highway



## LOW MAINTENANCE

Zero daily greasing for an 80% reduction in annual grease consumption. Spindles, roller bearings, and auto-belt tensioning are maintenance-free.



## OUIKLIFT

Enables mower decks to be raised without disengaging the PTO to traverse driveways, footpaths and pavements. Now a standard inclusion for all Pegasus models.



## **HEIGHT ADJUSTMENT**

Clearly displayed indicators in both metric and imperial units and a high-tensile 2mm pitch adjuster for precise cut height alterations.



## TITAN ROLLER BEARING SYSTEM

The Trimax Titan roller bearing system is maintenance-free, requiring no regular greasing, and provides excellent retention.



## **SAFETY COMPLIANT**

Complies with international safety standards and can be used with confidence on the roads and in public spaces.



Fully compliant with ADR regulations allowing road registration.

## \*OPTIONAL FEATURES.

## **✓ ANTI-BOUNCE / WEAR SKIDS**

Eliminates scalping and bouncing and reduces side channel wear.

## **▼** ROLLER SCRAPERS

Cleans rollers and reduces clumping in wet conditions.

## **✓ QUATTRO BLADE SYSTEM**

Four blades (flat, upturned or mixed) per spindle for a finer cut.

## **✓** ELECTRIC UNLOCK

Unlocks decks electronically from the tractor seat.

## **✓** MULTI-LIFT SYSTEM

Five different lift functions for mower decks. Now with Drive Protect.

## **✓** TURF TYRES

Distributes mower weight for less ground disturbance.

## **✓ SPARE ROAD TYRE & MOUNT**

Mounts a spare wheel to the rear mowing deck.

## **✓ STORAGE KIT**

Mounts a toolbox to the mower chassis.

## **✓** GALVANIZED

Protect against corrosion in harsh environments.

## **✓ ELECTRIC BRAKES** WITH BREAKAWAY

Reduces braking force required by the tractor.

## **✓ ROAD KIT**

Adds lights, signage, and beacons to the mower.

## **✓ TURF MUDGUARDS**

Available for both road tyres and turf tyres.

## **✓** NEXABLADES

Scientifically designed for high-end turf giving a superior cut and spread when it matters most.



TRIMAX


PEGASUS/S5

The Trimax PEGASUS sets the benchmark in wide area mowing for parks, reserves. airports, racecourses, sports fields, turf farms, and more.

For over 20 years, the Trimax Pegasus has been leading the way in wide-area mowing. Introduced in 2001 as the world's first multideck roller mower, the Pegasus is renowned for its robustness and versatility. Its fast spindle speeds and deep mowing decks deliver the highest quality cut and finish every time, and articulating decks provide a consistent cut over light to moderate

The Pegasus S5 builds on the incredible strength, durability, versatility, and efficiency of the previous series to increase machine life and decrease downtime in full-time commercial applications.

TALK TO US TODAY ABOUT THE CAPABILITIES OF TRIMAX PEGASUS S5 IN YOUR ENVIRONMENT.



**SPECIFICATIONS** 

**Cutting Width** 

**Overall Width** 

**Overall Length** 

**Transport Width** 

**Transport Height** 

**Cut Height Range** 

Approx. Weight

No. of Blade Spindles 9

493

4.94m (16' 2")

5.1m (16' 9")

4.65m (15' 3")

2.53m (8' 3 ½")

2.62m (8'7")

10 - 110mm

 $(\frac{3}{8}^{11} - 4\frac{1}{3}^{11})$ 

2200kg (4895lbs)

STRONGER.

SECOND TO NONE.

610

6.09m (19' 11")

6.25m (20' 6")

4.65m (15' 3")

2.53m (8' 3 ½")

3.2m (10' 6")

10 - 110mm

 $(\frac{3}{8}''' - 4\frac{1}{3}''')$ 

11

SMARTER.

722

7.23m (23' 9")

7.39m (24' 3")

4.65m (15' 3")

2.53m (8' 3 ½")

3.8m (12' 6")

10 - 110mm

 $(\frac{3}{8}^{11} - 4\frac{1}{3}^{11})$ 

13 2440kg (5380lbs) 2660kg (5865lbs)

SAFER.





## TRIMAX PEGASUS SS SR

Since its introduction in 2001, the Trimax Pegasus series has established itself as the benchmark in wide-area mowing where cut quality and presentation are key. The Pegasus SR builds on the Pegasus's legendary versatility and cut quality by taking its long grass performance to another level.

The Pegasus SR variant allows larger volumes of grass to enter the deck by replacing the front roller with castor wheels, allowing the mower to tackle long grass more effectively.

Containing all the industry leading features included with the Pegasus S5, the Pegasus SR has a range of features that increase machine life, reduce maintenance, and decrease downtime in full-time commercial applications.

Built with industry leading strength and durability, the Pegasus SR is the machine you need for any commercial wide area long grass applications.

TALK TO US TODAY ABOUT THE CAPABILITIES OF TRIMAX PEGASUS S5 SR IN YOUR ENVIRONMENT.







SPECIFICATIONS	493	610	722
Cutting Width	4.94m (16' 2")	6.09m (19' 11")	7.23m (23' 9")
Overall Width	5.1m (16' 9")	6.25m (20' 6")	7.39m (24' 3")
Overall Length	4.65m (15' 3")	4.65m (15' 3")	4.65m (15' 3")
Transport Width	2.49m (8' 3")	2.49m (8' 3")	2.49m (8' 3")
Transport Height	2.62m (8' 7")	3.2m (10' 6")	3.8m (12' 6")
Cut Height Range	20 - 180mm (½" - 7½")	20 - 180mm (%" - 7½")	20 - 180mm (½" - 7½")
No. of Blade Spindles	9	11	13
Approx. Weight	2300kg (5071lbs)	2500kg (5512lbs)	2700kg (5952lbs)
Min PTO Output	50hp	55hp	60hp

\*Minimum PTO output is a guide only. Requirement varies with the type of work and the terrain

## KEY APPLICATIONS.

✓ Passive Turf & Open Space ✓ Municipal & Contractors ✓ Aviation ✓ Racecourses





## **LONG GRASS PERFORMANCE**

Designed to mow grass up to 500mm high (depending on conditions) with a cut height range of 20 - 180mm.



## SINGLE ROLLER

Replacing the front roller with castor wheels allows more grass into the cutting chamber, resulting in a clean cut in long grass.



## TITAN ROLLER BEARING SYSTEM AUTOMATIC BELT TENSIONING

The Trimax Titan roller bearing system is maintenance-free, requiring no regular greasing, and provides excellent retention.



Provides more drive to the spindles in long grass applications.

> **OPTIONAL** FEATURES. **▼** REAR ROLLER SCRAPER Cleans rollers and reduces clumping in wet conditions. **✓ QUATTRO BLADE SYSTEM** Four blades (flat, upturned or mixed) per spindle for a finer cut.

**✓** ELECTRIC UNLOCK



## IMPACT PROTECTION

Outrigger arms and side channel leading edges have been redesigned for increased impact protection.



## QUIKLIFT

Enables mower decks to be raised without disengaging the PTO to traverse driveways, footpaths and pavements. Now a standard inclusion for all Pegasus models.



public spaces.



## **SAFETY COMPLIANT**

Complies with international safety standards and can be used with confidence on the roads and in



## the tractor seat.

**✓** TURF TYRES Distributes mower weight for less ground disturbance.

Unlocks decks electronically from

## **✓ SPARE ROAD TYRE & MOUNT** Mounts a spare wheel to the rear mowing deck.

## **✓ STORAGE KIT**

Mounts a toolbox to the mower chassis.

### **✓ ELECTRIC BRAKES WITH BREAKAWAY**

Reduces braking force required by the tractor.

## **✓** ROAD KIT

Adds lights, signage, and beacons to the mower.

## **✓** TURF MUDGUARDS

Available with turf tyre option.



10% stronger under tough travel conditions, twice the durability in deck lifting and lowering, and a 60% increase in rigidity in the outrigger arms from Pegasus S4.

ROBUST CHASSIS









AREA MOWING WHEN QUALITY COUNTS.

## TRIMAX X-MAM

The X-WAM has superior contourfollowing abilities based on the unique combination of five individual floating decks on an articulated axis.

With the potential to cut 13 hectares per hour and the ability to perform zero-turns without having to lift any of the mower decks, the X-WAM will increase your productivity and efficiency using only one tractor, one driver, and one mower.

Providing an even discharge of clippings and with the ability to mow in wet conditions and produce a cylinderlike patterned finish, X-WAM is the ultimate wide area mower.

TALK TO US TODAY ABOUT THE CAPABILITIES OF TRIMAX X-WAM IN YOUR ENVIRONMENT.

THE ULTIMATE IN WIDE

SPECIFICATIONS	10400
Cutting Width	10.41m (34' 2")
Overall Width	10.54m (34' 7")
Overall Length	5.83m (19' 1")
Transport Width	2.74m (9')
Transport Height	4.45m (14' 7")
Cut Height Range	10 - 100mm (¾" - 4")
No. of Blade Spindles	19
Approx. Weight	4880kg (10759lbs)
Min PTO Output	90hp

\*Minimum PTO output is a guide only. Requirement varies with the type of work and the terrain



Trimax X-WAM is great equipment. It replaced one tractor, one employee and reduced mowing time. Less equipment to maintain and less equipment expense has increased our profitability.

- LYNN GIBB | Hope Plantation Turf, Texas USA

## KEY APPLICATIONS.

✓ Turf / Sod Farm

## WHAT'S NEW ON X-WAM

The X-WAM is Trimax's widest mower, with 5 full-sized mowing decks. It is available as a complete model or as a kit to add to the Trimax Pegasus 610. The decks can be retracted for transport.

## **PRODUCT** FEATURES.



## LOCTEK

A stubless roller bearing system for vastly improved roller retention, alignment, bearing life and minimal maintenance.



## WHEELS RUN ON CUT GRASS

As the rear deck is located between the rear transport wheels, grass is not flattened by wheels prior to mowing, a feature unique to Trimax.



Trimax Turf Tyres help distribute the weight of the mower for less ground disturbance. Recommended for Turf Farms or fine turf applications.



## **FULL HYDRAULIC OPERATION**

The X-WAM uses full hydraulic operation for deck retraction into road transport mode.



## LOW MAINTENANCE

All moving surfaces have long life synthetic bushes or greasable bearings and remote grease points for hassle-free maintenance.



## ULTIMATE CONTOUR FOLLOWING

Contour following and cut quality is compromised when decks are over 3m wide. The X-WAM features multiple smaller decks for superior cut quality.



### LAZERBLADEZ"

Available in uplift and flat formation to suit mowing requirements, the unique tilt forward design minimises hang back in tough conditions.



## **RAPIDSET HEIGHT ADJUSTMENT**

Clearly displayed stainless steel height indicators allow the easy adjustment of cut heights without having to raise or lower the wings.



## STEADFAST SEALED SPINDLES

We've eliminated the tedious task of regular greasing. Covered by our 3-year warranty, maintenance costs are reduced, and productivity is enhanced.

## \*OPTIONAL FEATURES.

## **✓ ANTI-BOUNCE / WEAR SKIDS**

Eliminates scalping and bouncing and reduces side channel wear.

## **▼ ROLLER SCRAPERS**

Cleans rollers and reduces clumping in wet conditions.

## **✓ QUATTRO BLADES**

Four blades (flat, upturned or mixed) per spindle for a finer cut.

## **✓** GALVANIZED SURFACE COATING

Protect against corrosion in harsh environments.

## **✓ NEXABLADES**

Scientifically designed for high-end turf giving a superior cut and spread when it matters most.

## **✓ ELECTRIC UNLOCK**

Replaces the standard in-cab transport lock release rope with an electric actuator. This is operated by a push-button remote.





## TRIMAX FLAILDEK FX

The Trimax FlailDek FX offers a high-performance alternative to standard factory-fitted rotary mowing attachments.

FlailDek FX has the ability to deliver an exceptionally clean cut and disperse clippings safely and is used by contractors, councils, schools and land owners around the world. A highly versatile mower, FlailDek FX is also able to mulch branches up to 25mm in diameter, mow high grass and using the unique converter flap is suitable for sports fields and other fine turf applications.

The FlailDek FX has been designed to have minimal maintenance requirements and a low total cost of ownership yet deliver maximum reliability.

TALK TO US TODAY ABOUT THE CAPABILITIES OF FLAILDEK FX IN YOUR ENVIRONMENT.

#### SPECIFICATIONS 135 155 185 **Cutting Width** 1.36m (4' 6") 1.52m (5') 1.83m (6') 1.56m (5' 1½") 2.05m (6' 8½") **Overall Width** 1.72m (5' 8") 1.1m (3" 7) 1.1m (3'7") 1.1m (3'7") Overall Length **Overall Height** 0.37m (1' 2½") 0.37m (1' 2½") 0.37m (1' 2½") **Cut Height Range** 20 - 100mm $\binom{3}{4}$ " - 4") 20 - 100mm $\binom{3}{4}$ " - 4") 20 - 100mm $\binom{3}{4}$ " - 4") Approx. Weight 210kg (460lbs) 225kg (495lbs) 250kg (550lbs) 2 2 **Total Belts** 28 No. of Flails 32 40 Min PTO Output N/A N/A N/A

\*Minimum PTO output is a guide only. Requirement varies with the type of work and the terrain



This year I could not have coped without anything other than a Trimax FlailDek, it's versatile, cuts rough and fine grass even in the wet conditions and copes with it easily.

ANDREW HALL | Truelink Ltd

## KEY APPLICATIONS.

- ✓ Municipal & Contractors
  ✓ School & Sports Fields
  ✓ Golf & Country Clubs (Roughs)
- ✓ Lifestyle & Estates ✓ Racecourses ✓ Horticulture

## WHAT'S NEW ON FLAILDEK/FX

Strength and durability are increased from the original FlailDek design with the incorporation of a high tensile steel body, a 70% stronger rotor, a stronger gearbox, and forged steel Trimax Gamma Flails. The unique converter has also been added.



## **PRODUCT** FEATURES.



## **UNIQUE CONVERTER**

Superb short grass cutting ability by creating airflow that lifts grass before it's cut. Open converter for increased productivity in long grass environments.



## SAFE CLIPPING DISPERSION

Safety is paramount when mowing in public areas. This is why Trimax has designed the FlailDek FX to expel debris in a downward direction behind the mower.



## **REAR ROLLER**

Full width rear roller prevents scalping, permits the edge of the mower to be run along kerbs, adds to overall safety and produces striping.



## FRONT CASTOR WHEELS

Front castor wheels allow the FlailDek FX to follow ground contours independently from the tractor. The semi-pneumatic tires are impossible to puncture.



## **POWER SAVING FLAILS**

Strong forged steel flail with an aerodynamic profile reduces hp requirements yet generates sufficient draught to lift grass for a clean cut.



## **NEW IMPROVED ROTOR**

Dynamically balanced and designed for durability to withstand everyday use in the toughest mowing environments.



from abrasion-resistant steel extends bearing life and enables high productivity in the most challenging environments.







## TRIMAX EZEEMOWEX

The EZEEMOW FX is the ideal partner for your compact tractor where versatility and robustness is needed.

With its compact dimension, Ezeemow FX can fit closely to the tractor and manoeuvre into tight corners. Able to mow anything from fine turf to small prunings, vegetation up to 25mm in diameter and high grass, the Ezeemow FX can transform areas into tidy mown lawn in a single pass. This versatility makes the Ezeemow FX ideal for contractors, councils, roadsides, estates, and orchard applications.

The Ezeemow FX has been designed to have minimal maintenance requirements and low total cost of ownership yet deliver maximum reliability.

TALK TO US TODAY ABOUT THE CAPABILITIES OF EZEEMOW FX IN YOUR ENVIRONMENT.

#### SPECIFICATIONS 135 1.36m (4' 6") 1.83m (6') **Cutting Width** 1.52m (5') **Overall Width** 1.56m (5'1½") 1.72m (5' 8") 2.05m (6' 8½") Overall Length 0.58m (1' 11") 0.58m (1'11") 0.58m (1'11") 0.37m (1' 2½") 0.37m (1' 2½") 0.37m (1' 2½") **Overall Height** Cut Height Range 10 - 100mm 10 - 100mm 10 - 100mm (3/11 - 411) (3/11 - 411) (3/11 - 411) **Approx. Weight** 180kg (396lbs) 200kg (440lbs) 225kg (495lbs) 2 **Total Belts** No. of Flails 28 32 40 Min PTO Output 17hp 20hp 24hn

\*Minimum PTO output is a guide only. Requirement varies with the type of work and the terrain



I've been mowing 30hrs a week for over 28 years and my Ezeemow still has the same gearbox. It produces a beautiful cut and if I had to, I'd replace it with the exact same model..no two ways about it!

STEVE DE BRUIN | Grass Cutting Services, Tauranga NZ

## KEY APPLICATIONS.

✓ Municipal & Contractors
✓ Horticulture
✓ Lifestyle & Estates

## WHAT'S NEW ON EZEEMOW/FX

Strength and durability are increased from the original Ezeemow design with the incorporation of a high tensile steel body, a 70% stronger rotor, a stronger gearbox, and forged steel Trimax Gamma Flails. The unique converter, an improved belt tensioning system, and easy height adjustment on the full width roller have also been added.



## **PRODUCT** FEATURES.



## UNIQUE CONVERTER

Superb short grass cutting ability by creating airflow that lifts grass before it's cut. For work in heavy environments, lift converter for increased productivity.



## **REAR ROLLER**

**EZEEZMOW OFFSET** 

CENTRE MOUNT OR OFFSET POSITIONS

ONLY AVAILABLE IN FIXED

DIAGRAM

Full width rear roller prevents scalping, permits the edge of the mower to be run along kerbs, adds to overall safety and produces striping.



## SAFE CLIPPING DISPERSION

Safety is paramount when mowing in public areas. This is why Trimax has designed the Ezeemow FX to expel debris in a downward direction



### **POWER SAVING FLAILS**

Strong forged steel flail with an aerodynamic profile reduces hp draught to lift grass for a clean cut.



### \*RIGHT-HAND OFFSET

Comes standard with a centre mount but is available in a right-hand requirements yet generates sufficient offset to suit your specific mowing





use in the toughest mowing




environments.









VIEW MORE PHOTOS, VIDEOS, AND INFORMATION ABOUT THE TRIMAX EZEEMOW FX ONLINE HERE:







## TRIMAX FORCE

Tough on roadsides, efficient in open spaces, and versatile for everything in between, the Trimax FORCE is the multitool mower and mulcher you need to get the job done, no matter what that job might be.

As Trimax's strongest and most adaptable flail mower yet, with a wide range of options available for custom configuration, the Force can easily be tailored to produce a pristine cut and superior finish in almost any application. For reliable productivity and excellent results, the Trimax Force is the ultimate choice.

TALK TO US TODAY ABOUT THE CAPABILITIES OF THE TRIMAX FORCE IN YOUR ENVIRONMENT.







115	145	175	205	235
1.15m	1.44m	1.73m	2.02m	2.3m
(3' 9 ½")	(4' 8 ¾")	(5' 8 ½")	(6' 7 ¾")	(7' 6 ¾")
1.45m	1.73m	2.02m	2.31m	2.59m
(4' 8 ½")	(5' 8 ½")	(6' 7 ¾")	(7' 7")	(8' 5 %")
1.15m	1.15m	1.15m	1.15m	1.15m
(3' 9 ½")	(3' 9 ½")	(3' 9 ½")	(3' 9 ½")	(3' 9 ½")
0.5m	0.5m	0.5m	0.5m	0.5m
(1' 7 ¾")	(1' 7 ¾")	(1' 7 ¾")	(1' 7 ¾")	(1' 7 ¾")
0 - 60mm	0 - 60mm	0 - 60mm	0 - 60mm	0 - 60mm
(2 ¾")	(2 ¾")	(2 ¾")	(2 ¾")	(2 ¾")
590kg	650kg	755kg	815kg	870kg
(1300lbs)	(1435lbs)	(1665lbs)	(1795lbs)	(1920lbs)
16	20	24	28	32
30hp	35hp	40hp	45hp	50hp
	1.15m (3' 9 ½") 1.45m (4' 8 ½") 1.15m (3' 9 ½") 0.5m (1' 7 ¾") 0 - 60mm (2 ¾") 590kg (1300lbs) 16	1.15m	1.15m	1.15m

PTO Output is a guide only. Requirement varies with the type of work and the terrain

## KEY APPLICATIONS.

✓ Municipal & Contractors
✓ Horticulture
✓ Aviation
✓ Racecourses
✓ Lifestyle & Estates

## WHAT'S NEW ON FORCE.

Strength and durability have been increased, including 50% thicker endplates and a newly designed rotor bearing assembly with over 35% higher load capacity than Trimax's previous flail mowers. Zero-maintenance features and a wider array of options have also been introduced.

## **PRODUCT** FEATURES.



## MOW AND MULCH WITH **ONE MACHINE**

Mow grass to a fine finish and mulch prunings up to 90mm in diameter with one machine.



## **SAFETY COMPLIANT**

Meets international safety standards for thrown object protection in every configuration. Safe to operate in public spaces.



## **AUTO BELT TENSIONING**

The belt system is equipped with automatic tensioners to optimize drive to the rotor without requiring manual adjustments.



## REPLACEABLE INTERNAL LINER

A 6mm replaceable internal liner reduces noise and increases durability in the mower's highimpact zones.



## MAINTENANCE-FREE **ROLLER BEARINGS**

New highly-rated sealed roller bearing stacks require no regular greasing.



## **OFFSET CAPABILITIES**

The Force can come with a leftor right-hand offset with an additional 500mm of hydraulic side shift.



## LOW MAINTENANCE

Easily accessible grease locations and maintenance-free features make regular service quicker and easier than ever.



## **HEAVY-DUTY SKIDS**

Heavy-duty wear skids on the mower trailing arms prolong mower life in demanding terrain and are easily removed or replaced.

## \*OPTIONAL FEATURES.

### **→** HEAVY DUTY LINER

Increases durability in the mower's high impact zone.

**→** HEAVY DUTY ROLLER

Increases roller wall thickness from 5mm to 11mm.

## **✓** ROLLER SCRAPERS

Cleans rollers and reduces clumping in wet conditions.

## **✓** MULCHING COUNTERBLADES

## Produces an ultra-fine mulch. **✓ PRUNING RAKES**

Collects prunings into the cutting chamber.

## **✓ LIGHTING KIT WITH** STORAGE BRACKET

LED road lights, safety triangle, and bracket for storage box.

### **✓ STORAGE BOX**

Easy access to spare parts and

## **✓ SAFETY DISPERSION GUARD**

Recommended for all mowers operating in public spaces, the Safety Dispersion Guard ensures that debris exits the cutting chamber safely.

## **✓ FRONT MOUNT**

Available in front mount threepoint linkage configuration for increased visibility.





## TRIMAX WARLORD S3

Extremely versatile, the Trimax WARLORD S3 is bound to dominate any environment you put it in - handling long and short grass, prunings up to 75mm in diameter, turf ribbons and offcuts with ease.

Tame rough patches full of scrub and branches in one pass and leave behind a field of evenly distributed mulch and clippings. Control the coarseness of discharge with Warlord's adjustable rear flap while safely dispersing clippings. The Trimax Warlord is tough and durable, requiring minimal maintenance and simplifying repairs to keep your machine running for years. Spend less time and money keeping your mower operating at 100%.

The Trimax Warlord S3 is a medium duty mower/mulcher suitable for a wide range of applications including sod and turf farming, horticulture, passive turf management, contracting/hire, and land reclamation.

TALK TO US TODAY ABOUT THE CAPABILITIES OF WARLORD SERIES 3 IN YOUR ENVIRONMENT.







SPECIFICATIONS	175	205	235
Cutting Width	1.74m (5' 9")	2.04m (6' 8")	2.34m (7' 8")
Overall Width	2.04m (6' 8")	2.34m (7' 8")	2.66m (8' 8")
Overall Length	1.05m (3' 5")	1.05m (3' 5")	1.05m (3' 5")
Overall Height	0.55m (1' 10")	0.55m (1' 10")	0.55m (1' 10")
Cut Height Range	0 - 70mm (0 - 2¾")	0 - 70mm (0 - 2¾")	0 - 70mm (0 - 2 <sup>3</sup> / <sub>4</sub> ")
Approx. Weight	690kg (1520lbs)	750kg (1650lbs)	810kg (1780lbs)
No. of Flails	24	28	32
Min PTO Output	40hp	44hp	49hp

<sup>\*</sup>Minimum PTO output is a guide only. Requirement varies with the type of work and the terrain



We do a lot of roadside work for councils, shires and local government. We use the Warlord where it's too tough for other machines, from my past experience it stands head and shoulders above the rest.

ALAN CHAPEL | AML Turf, Wodonga QLD

## KEY APPLICATIONS.

✓ Horticulture ✓ Municipal & Contractors ✓ Turf ✓ Aviation ✓ Racecourses

## WHAT'S NEW ON WARLORD S3

The hydraulic side shift and discharge control capabilities are new from the previous Warlord series, further increasing the versatility of the machine.



\*OPTIONAL

in wet conditions.

FEATURES. **▼** ROLLER SCRAPERS

Cleans rollers and reduces clumping

## **PRODUCT FEATURES**



### HYDRAULIC SIDE SHIFT

The Warlord can be quickly offset to the right by up to 500mm. Perfect for transport and manoeuvring around obstacles whilst mowing.



### REPLACEABLE INTERNAL LINER

WARLORD **OFFSET** 

DIAGRAM

HYDRAULIC SIDE SHIFT / RIGHT-HAND SIDE SHIFT ONLY

A bolt-in 6mm replaceable internal liner increases the life of the body, minimises damage and reduces noise. can be replaced when required.



in the lowest position. Controlling

public spaces. Lift flap open for easy

discharge assists with safety in

## REPLACEABLE SKIDS

DISCHARGE CONTROL


flail servicing.


Skids on Warlord trailing arms prolong Warlord is configured with rightmower life in demanding terrain and



## **RIGHT HAND OFFSET**

hand offset for increased over-theshoulder visibility.





VIEW MORE PHOTOS, VIDEOS, AND INFORMATION ABOUT THE TRIMAX WARLORD SERIES 3 ONLINE HERE:

## TRIMAX BLADES.

NOT JUST ONE. BUT A RANGE OF BLADE OPTIONS!

## **TRIMAX LAZER**BLADEZ

Fitted as standard to all Trimax Rotary Mowers. Available in uplift or flat configuration.

Trimax LAZERBLADEZ are optimised to deliver a consistently clean cut across a range of applications.

- > Fling-tip blades are easier and more cost-effective to replace than full blade beams
- "Tilt-forward" design prevents blade hang-back in tough conditions
- > Wider than other blades in its class for higher impact in heavy mowing
- > Blade angles have been engineered specifically for optimum grass lift and discharge
- Ultra-precise blade carrying system made from heavy spring steel with minimal flex for excellent cut
- Made from a unique steel alloy specially produced for Trimax and hardened for long life
- > Full-length cutting edge ensures that all grass is struck by the sharpened part of the blade
- > Heavy-duty blade bolts are larger and stronger than competitors to stand up to high-energy wear





## **TRIMAX QUATTRO** BLADE CARRIER

Available upgrade. Available in uplift or flat configuration, or a mixture of both.

The Trimax Quattro Blade System adds two extra Trimax LAZERBLADEZ to each spindle for an ultrafine cut and premium presentation in any application.

- Double your cut frequency without changing your mowing speed
- > Use two flat and two uplift LAZERBLADEZ for optimal lift and discharge, or four flat LAZERBLADEZ for the lowest cut heights on warm season turf
- More cuts per forward meter travel = less grass processed per cut = a cleaner, finer finish

## **TRIMAX** NEXABLADES

For fine turf applications such as Golf, Sports Field or Sod Farms. The geometry of Trimax NEXABLADES has been scientifically designed and all angles are perfectly relative to ensure the most optimal performance possible upon interaction with turf. Compared to the industry-leading Trimax LAZERBLADEZ, NEXABLADES have been tested and shown to:

- Improve clipping and spread by 70%
- > Reduce clumping by 51%
- Improve cleanliness of cut by 14%
- Use 5% less PTO power
- Increase resistance to erosive wear by 50%
- Reduce aerodynamic noise by 15%
- \* Tested in controlled conditions





## TRIMAX FLAILS.

AERODYNAMIC. SUPER EFFICIENT. THE FIRST OF ITS KIND!

## **TRIMAX GAMMAFX FLAIL**

Fitted as standard to all Trimax Flail Mowers. Available in a range of sizes to suit mower model.

It used to be generally accepted that flail mowers demanded more horsepower to run than other mowers, until we developed the GammaFX Flail - patented and unique to Trimax.

- The unique aerodynamic design decreases drag resistance as the rotor turns and allows cuttings to flow freely outwards between the flails and mower body
- Lower horsepower requirements, decreased fuel consumption, and the ability to operate at a faster speed while still delivering an exceptional cut and spread
- Manufactured from high quality heat treated and hardened steel and proven over 40 years of commercial use around the world
- Faster tip speed than competitor mulchers means you can mulch heavy debris yet also mow grass to a fine, striped presentation finish
- > Smaller flails in a higher number which take small bites rather than big chunks, makes for a finer mulch
- Cheaper replacement cost means lower cost of ownership
- > The face of the GammaFX Flail is angled forward so it presents to the material being cut at the optimum angle for a cleaner cut





## WANT TO KNOW MORE? FIND US ONLINE.

## THE TRIMAX WEBSITE.

The Trimax website contains more information, photos, and videos of our products and features.

## TRIMAXMOWERS.COM.AU



OR USE THIS OR CODE

## THE TRIMAX RESOURCE CENTRE.

Easily accessed from the main website, the **Trimax Resource** Centre provides everything you need to easily service and maintain your Trimax mower. Best of all. it's completely free.



()trimax

## THE TRIMAX **CUSTOMER CENTRE.**

- Watch step-by-step service and setup videos.
- Download maintenance checklists.
- Access the operator manual and parts manual for your mower.
- Read instructions for installing Trimax Genuine Spare Parts.
- Register warranty or file a claim.



- Order Trimax Genuine Parts and Service Kits
- Review past orders.
- Upload bulk orders for quick and easy fleet maintenance.
- Quickly find common parts.
- Now with improved search functionality find exactly the part you need.





## **TRIMAX MOWING SYSTEMS**

80 Agar Drive, Truganina, Melbourne 3029

**P**+61 3 8361 7868 / **E** info@trimaxmowers.com.au

## **FOR MOWER SALES**

P 1800 874 629 / E info@trimaxmowers.com.au

## **FOR PARTS ORDERS**

**P** +61 3 8361 7868 / **E** parts@trimaxmowers.com.au

