

UHH Series Rotary Hoe

The European designed COSMO Bully UHH Series Rotary Hoes are ideal for large scale domestic and commercial operations and working virgin ground. The multi speed gearbox (rated up to 140hp) is fixed to a robust and rigid main frame, constructed with box section reinforcing, so the implement can operate for prolonged periods of time in a range of soil types and conditions.

The COSMO Bully UHH Series produces a super fine finish. The spring loaded tailgate keeps soil inside and in contact with the blades until it is well pulverised. The multi speed gearbox allows the operator to customise the rotor speed. The rotor design, Ø 530mm from blade to blade, allows a large amount of soil to be worked without clogging up the chamber. And the speed blade configuration, a design where six (6) L shaped blades (per flange) are slightly staggered, reduces the tractor horsepower required.

The COSMO Bully UHH Series is suitable for a range of domestic and commercial horticultural and gardening applications including nurseries, vineyards and orchards.





Code	TBUHH080	TBUHH100	TBUHH120
Description	Bully UHH80 Rotary Hoe	Bully UHH100 Rotary Hoe	Bully UHH120 Rotary Hoe
Side transmission	Gear drive		
Gearbox	140hp, 540/1000rpm, multi speed		
PTO shaft/clutch	W2600 Series with 200mm (8") friction (slip) clutch		
Skids	Height adjustable		
Finish	Powder coated		
Rotor diameter (mm)	530		
Rotor speed (rpm)	224 - 248 at 540rpm 251 - 278 at 1000rpm		
No. of rotor flanges	8	10	12
No. of blades p/flange	6	6	6
Total no. of blades	48	60	72
Blades	Square/L shaped standard Curved/speed on request		
Linkage	Category 2 and 3 (quick hitch compatible)		
Guarding	Standard with CE guards		
Overall width (mm)	2300	2800	3300
Working width (mm)	2100	2550	3050
Working depth (mm)	250		
Tractor range (hp)	60 - 140	90 - 140	110 - 140
Weight (kg)	934	1061	1170

Options
TBUHH080-CR 450mm cage roller with manual adjustment (suit UHH80) TBUHH100-CR 450mm cage roller with manual adjustment (suit UHH100) TBUHH120-CR 450mm cage roller with manual adjustment (suit UHH120)

VH/UHH square/L shaped blade (right) VH/UHH square/L shaped blade (left) VH/UHH curved/speed blade (right) 3029 1374 23160 23159 VH/UHH curved/speed blade (left)