



UM Series Rotary Hoe

The European designed COSMO Bully UM Series Rotary Hoes are a single speed, side gear driven implement specifically for tractors in the 35 to 50hp range.

Engineered to include multiple features and accessories traditionally found in much larger rotary hoes, the UM Series is suitable for use in nurseries, vineyards and orchards.

The rotor features six (6) C shaped, heat treated blades (per flange) in a speed configuration.

The speed configuration, a design where the blades are slightly staggered from flange to flange, reduces the horsepower required to produce a fine finish in a variety of soil conditions.



Code	TBUM60	TBUM72
Description	Bully UM60 Rotary Hoe	Bully UM72 Rotary Hoe
Side transmission	Gear drive	
Gearbox	50hp, 540rpm, single speed	
PTO shaft/clutch	Series 4 with 150mm (6") friction (slip) clutch	
Skids	Height adjustable	
Finish	Powder coated	
Rotor diameter (mm)	434	
Rotor speed (rpm)	241	
No. of rotor flanges	8	9
No. of blades p/flange	6	6
Total no. of blades	48	54
Blades	Curved/speed	
Linkage	Category 1 (quick hitch compatible)	
Guarding	Standard with CE guards	
Overall width (mm)	1775	1970
Working width (mm)	1650	1830
Working depth (mm)	180	
Tractor range (hp)	30 - 50	35 - 50
Weight (kg)	285	310

Parts

4724	UM curved/speed blade (right)
4723	UM curved/speed blade (left)
4722	UM square/L shaped blade (right)
4721	UM square/L shaped blade (left)